


00401-0000

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Cadmium Red Light, Cadmium Red Medium, Cadmium Red Deep, Cadmium Orange, Cadmium Orange Deep Artists' Oil Colors

SECTION I -- PRODUCT IDENTITY

Date updated: 8-23-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 2

Flammability 1

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Compound paint, N.O.S., Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
Cadmium sulfide	1306-23-6	59-97	5/mg/m3	10/2 mg/m3 (as Cd)
Cadmium selenide	1306-24-7	3-55	5 mg/m3	10/2 mg/m3 (as Se)
Barium Sulfate	7727-43-7	0-40		
Zinc Sulfide(PNOC)	1314-98-3	0-5	15/5mg/m3	10mg/m3

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

Hazards Identification

Ingestion: Not toxic for acute exposure to animals.

Chronic Effects/Carcinogenicity:

OSHA has chosen to regulate occupational exposure to all cadmium compounds, including pigments, as a single category. The standard states that substances containing cadmium are a cancer hazard and can cause lung and kidney disease.

Cadmium and cadmium compounds are listed in the Annual NTP Report as carcinogenic to animals, but with only limited evidence of carcinogenicity to humans. This information is based on test results for cadmium compounds other than pigmentary forms.

Although certain cadmium compounds are known to cause kidney damage in humans and have been shown to cause lung cancer in laboratory animals, no chronic health effects have been shown to result from exposure to cadmium pigments. Cadmium pigments have been shown to be significantly less biologically available and less active than other cadmium compounds.



SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A
Vapor pressure: N/A
Vapor density: N/A

Specific gravity: 1 - 1.4
% volatile (volume): 0
Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.
Appearance and odor: Red paste, linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 650 degree F
Extinguishing media: CO₂, dry chemical, water fog
Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.
Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.
Reactivity: product is stable
Hazardous polymerization: will not occur
Conditions to avoid: avoid extreme heat
Hazardous decomposition products:
Usual products of combustion: CO, CO₂ and possibly acrolein.

SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects:
Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Cadmium and certain cadmium compounds are listed in IARC and the Annual NTP Report as carcinogenic, but with only limited evidence of carcinogenicity to humans. These listings are based on test results for cadmium compounds other than the pigmentary forms. No known adverse health effects to linseed oil. No known medical conditions aggravated by exposure to cadmium oil paints.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition.
Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water.
Small amounts can be dried and disposed of as ordinary trash.



SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required

Ventilation: none normally required

Protective gloves: use of gloves is suggested when prolonged or repeated contact with hands is likely. Individuals having sensitive skin may find it beneficial to use a barrier cream or moisturizer when excessive or prolonged contact with skin is likely.

Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293

Product: Hansa Yellow Light, Hansa Yellow Medium, Hansa Yellow Deep Artists' Oil Colors

SECTION I -- PRODUCT IDENTITY

Date updated: 8-24-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Chemical formula: N/A (mixture)

Reactivity 0

DOT shipping class: Compound paint, N.O.S., Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under OSHA Standard 1910.1200 (29 CFR 1910.1200)

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Yellow paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.

SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A

Ingestion: No known adverse health effects
Skin contact: No know adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.

No known adverse health affects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Chromium Oxide Green, Viridian Artists' Oil Colors

SECTION 1 -- PRODUCT IDENTITY

Date updated: 8-23-07 Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin	HMIS Information
	Health 2
Chemical name: Vegetable oil/pigment mixture	Flammability 1
	Reactivity 0
Chemical formula: N/A (mixture)	

DOT shipping class: Compound paint, N.O.S., Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
Chromium(III) Oxide *	12001-99-9	60-80	0.5mg/m3	0.5mg/m3

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A	Specific gravity: 1 - 1.4
Vapor pressure: N/A	% volatile (volume): 0
Vapor density: N/A	Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Green paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V – HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA: repeated and prolonged exposure to trivalent chromium compounds may cause delayed effects involving the respiratory system.
No known adverse health effects to linseed oil.

SECTION VI – SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII – STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Perylene Red Artists' Oil Color

SECTION I -- PRODUCT IDENTITY

Date prepared: 8-24-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Compound paint, N.O.S.. Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard.

These are reportable chemicals under 40 CFR 372, SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Red paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.


Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.



MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
PO Box 15009
Portland, OR 97293

Product: Cadmium Lemon, Cadmium Yellow Light, Cadmium Yellow Medium, Cadmium Yellow Deep Artists' Oil Colors

SECTION I -- PRODUCT IDENTITY

Date updated: 6-18-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 2
Flammability 1
Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Compound paint, N.O.S., Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
Cadmium Sulfide	1306-23-6	64-100	200/5mg/m3	10/2mg/m3 as Cd)
Barium Sulfate	7727-43-7	0-25	10/5mg/m3	10mg/m3
Zinc Sulfide	1314-98-3	0-15	10/5mg/m3	10mg/m3

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

Hazards Identification


Ingestion: Not toxic for acute exposure to animals.

Chronic Effects/Carcinogenicity:

OSHA has chosen to regulate occupational exposure to all cadmium compounds, including pigments, as a single category. The standard states that substances containing cadmium are a cancer hazard and can cause lung and kidney disease.

Cadmium and cadmium compounds are listed in the Annual NTP Report as carcinogenic to animals, but with only limited evidence of carcinogenicity to humans. This information is based on test results for cadmium compounds other than pigmentary forms.

Although certain cadmium compounds are known to cause kidney damage in humans and have been shown to cause lung cancer in laboratory animals, no chronic health effects have been shown to result from exposure to cadmium pigments. Cadmium pigments have been shown to be significantly less biologically available and less active than other cadmium compounds.



SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A
 Vapor pressure: N/A
 Vapor density: N/A

Specific gravity: 1 - 1.4
 % volatile (volume): 0
 Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.
 Appearance and odor: Yellow paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F
 Extinguishing media: CO₂, dry chemical, water fog
 Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.
 Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.
 Reactivity: product is stable
 Hazardous polymerization: will not occur
 Conditions to avoid: avoid extreme heat
 Hazardous decomposition products:
 Usual products of combustion: CO, CO₂ and possibly acrolein.

SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
 Acute health effects: Eye contact may cause redness or irritation
 Inhalation: N/A
 Ingestion: No known adverse health effects
 Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:


Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
 Inhalation: N/A
 Skin contact: N/A

CHRONIC HEALTH EFFECTS:

The NTP & IARC list cadmium as a carcinogen; however, there is conflicting evidence as to whether cadmium pigments offer any risk to human health.
 No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
 Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.



SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required

Protective gloves: use of gloves is suggested when prolonged or repeated contact with hands is likely. Individuals having sensitive skin may find it beneficial to use a barrier cream or moisturizer when excessive or prolonged contact with skin is likely.

Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
PO Box 15009
Portland, OR 97293



Product: Cadmium Green, Phthalo Green, Sap Green Art Student Oils

SECTION I -- PRODUCT IDENTITY

Date updated: 8-24-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Compound paint, N.O.S., Not Regulated by DOT as a hazardous material

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard. (29 CFR 1910.1200)

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Green paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.

Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Dioxazine Purple (Carbazole Violet) Artists' Oil Color

SECTION I -- PRODUCT IDENTITY

Date updated: 8-23-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Compound paint, N.O.S.. Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard. (29CFR 1910.1200)

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Violet paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects:
Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA: no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame.
Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Phthalo Blue, Ultramarine Blue, Prussian Blue, Ultramarine Violet Artists' Oil Colors

SECTION I -- PRODUCT IDENTITY

Date updated: 8-24-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Chemical formula: N/A (mixture)

Reactivity 0

DOT shipping class: Compound paint, N.O.S. Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard. (29 CFR 1910.1200)

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Blue paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V – HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame.
Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Indanthrone Blue Artists' Oil Color

SECTION I -- PRODUCT IDENTITY

Date updated: 8-23-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Health 1

Chemical name: Vegetable oil/pigment mixture

Flammability 1

Reactivity 0

Chemical formula: Anthraquinone

DOT shipping class: Compound paint, N.O.S.. Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard.

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Blue paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO₂, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO₂ and possibly acrolein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
PO Box 15009
Portland, OR 97293



Product: Transparent Earth Orange Artists' Oil Color

SECTION I -- PRODUCT IDENTITY

Date updated: 8-24-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Compound paint. N.O.S., Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard.

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Orange paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Ivory Black Artists' Oil Color

SECTION I -- PRODUCT IDENTITY

Date updated: 8-23-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Chemical name: Vegetable oil/pigment mixture

Health 1

Flammability 1

Chemical formula: N/A (mixture)

Reactivity 0

DOT shipping class: Compound paint. N.O.S., Not regulated by DOT as a hazardous material.

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
----------------	------	-----	----------	-----------

This product contains no hazardous materials under the current OSHA standard.

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: N/A

Specific gravity: 1 - 1.4

Vapor pressure: N/A

% volatile (volume): 0

Vapor density: N/A

Evaporation rate (BuOAc = 1): N/A

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Black paste; linseed oil odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 620 degree F

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.

Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA


Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame.
Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint
Acute health effects: Eye contact may cause redness or irritation
Inhalation: N/A
Ingestion: No known adverse health effects
Skin contact: No known adverse health effects

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.
Inhalation: N/A
Skin contact: N/A

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.
No known adverse health effects to linseed oil.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.
Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: none normally required
Ventilation: none normally required
Protective gloves: none normally required
Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO
 PO Box 15009
 Portland, OR 97293



Product: Neo Megilp Painting Medium

SECTION I -- PRODUCT IDENTITY

Date prepared: 5-25-07

Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin

HMIS Information

Health 2

Chemical name: Alkyd Resin/Petroleum Solvent Mixture

Flammability 2

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Combustible Liquid UN 1255

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
Mineral Spirits	64742-47-8	40-60	100ppm	500ppm

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: 300-405 degree F

Specific gravity: .8-.9

Vapor pressure: 2mm Hg @

% volatile (volume): 40-60

Vapor density: 4.9

Evaporation rate (BuOAc = 1): 0.13

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Honey-colored liquid; petroleum distillate odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: Neo Megilp 137 degree F

Flammable Limits: LEL: 1.0 VEL: 6.0

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.


Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein and oxides of nitrogen.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint, inhalation, and skin contact.

Acute health effects:

Eye contact: May cause redness or irritation

Inhalation: dizziness, headache, nausea, and possible nervous system depression.

Ingestion: Nausea, gastrointestinal irritation, or vomiting.

Skin contact: May cause rash, cracking, dryness or defatting of skin.

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.

Inhalation: Move individual to fresh air. If breathing has stopped, apply artificial respiration: get medical attention

Ingestion: **DO NOT INDUCE VOMITING.** Give water or milk to drink; get medical attention.

Skin contact: Wash area with soap and water. If irritation persists, get medical attention.

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA: no adverse long-term effects are known.

Medical Conditions aggravated by exposure: Existing lung or skin conditions may be aggravated by repeated exposure.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.

Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: Wear NIOSH approved respirator for organic vapors.

Ventilation: Adequate to keep exposure below TLV

Protective gloves: Neoprene or rubber if prolonged skin contact is likely.

Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
 PO Box 15009
 Portland, OR 97293



Product: Galkyd Painting Medium #1, Galkyd Lite, Galkyd Gel, Galkyd Slow Dry

SECTION I -- PRODUCT IDENTITY

Date prepared: 5-24-07 Emergency telephone no. 503/235-1945

Preparer's Name: R. Gamblin HMIS Information
 Health 2
 Chemical name: Alkyd Resin/Petroleum Solvent Mixture Flammability 2
 Reactivity 0
 Chemical formula: N/A (mixture)

DOT shipping class: Combustible Liquid UN 1255

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
Mineral Spirits	64742-47-8	40-60	100ppm	500ppm

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: 300-405 degree F Specific gravity: .8-.9
 Vapor pressure: 2mm Hg @ % volatile (volume): 40-60
 Vapor density: 4.9 Evaporation rate (BuOAc = 1): 0.13

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.
 Appearance and odor: Honey-colored liquid; petroleum distillate odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: Galkyd Lite 138 degree F
 Galkyd 136 degree F
 Galkyd Gel 147 degree F
 Galkyd Slow Dry 142 degree F

Flammable Limits: LEL: 1.0 VEL: 6.0

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.


Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein and oxides of nitrogen.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint, inhalation, and skin contact.

Acute health effects:

Eye contact: May cause redness or irritation

Inhalation: dizziness, headache, nausea, and possible nervous system depression.

Ingestion: Nausea, gastrointestinal irritation, or vomiting.

Skin contact: May cause rash, cracking, dryness or defatting of skin.

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.

Inhalation: Move individual to fresh air. If breathing has stopped, apply artificial respiration; get medical attention.

Ingestion: **DO NOT INDUCE VOMITING.** Give water or milk to drink; get medical attention.

Skin contact: Wash area with soap and water. If irritation persists, get medical attention.

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.

Medical Conditions aggravated by exposure: Existing lung or skin conditions may be aggravated by repeated exposure.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.

Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: Wear NIOSH approved respirator for organic vapors.

Ventilation: Adequate to keep exposure below TLV

Protective gloves: Neoprene or rubber if prolonged skin contact is likely.

Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.

MATERIAL SAFETY DATA SHEET

Manufacturer's Name: GAMBLIN ARTISTS COLORS CO.
PO Box 15009
Portland, OR 97293



Product: Cold Wax Medium

SECTION I -- PRODUCT IDENTITY

Date prepared: 5-25-07

Emergency telephone no. (503) 235-1945

Preparer's Name: R. Gamblin

HMIS Information

Health 2

Chemical name: Natural Wax/Petroleum Solvent/ Mixture

Flammability 2

Reactivity 0

Chemical formula: N/A (mixture)

DOT shipping class: Combustible Liquid UN 1255

SECTION II -- HAZARDOUS INGREDIENTS

Chemical names	CAS#	Wt%	OSHA PEL	ACGIH TLV
Odorless Mineral Spirits	64742-48-9	30-40	300ppm	500ppm

These are reportable chemicals under 40 CFR 372. SARA Title III Section 313

SECTION III -- PHYSICAL CHARACTERISTICS

Boiling range: 300-405 degree F

Specific gravity: .8-.9

Vapor pressure: 2mm Hg @

% volatile (volume): 40-60

Vapor density: 4.9

Evaporation rate (BuOAc = 1): 0.13

Solubility (specify solvents): Insoluble in water. Soluble in most petroleum solvents.

Appearance and odor: Honey-colored liquid; petroleum distillate odor.

SECTION IV -- FIRE & EXPLOSION DATA

Flash point: 149 degree F

Flammable Limits: LEL: 1.0 VEL: 6.0

Extinguishing media: CO2, dry chemical, water fog

Special firefighting procedures: water or foam may cause frothing if directed into container of burning material. Use water to cool containers exposed to heat.

Unusual fire & explosion hazards: contaminated rags or other easily ignited organic materials are spontaneously combustible. Immerse in water after use.


Reactivity: product is stable

Hazardous polymerization: will not occur

Conditions to avoid: avoid extreme heat

Hazardous decomposition products:

Usual products of combustion: CO, CO2 and possibly acrolein and oxides of nitrogen.



SECTION V -- HEALTH HAZARD DATA

Route(s) of entry: Eye contact, ingestion of paint, inhalation, and skin contact.

Acute health effects

Eye contact: May cause redness or irritation

Inhalation: dizziness, headache, nausea, and possible nervous system depression.

Ingestion: Nausea, gastrointestinal irritation, or vomiting.

Skin contact: May cause rash, cracking, dryness or defatting of skin.

EMERGENCY FIRST AID PROCEDURES:

Eye contact: wash with clean water for at least fifteen minutes. If irritation persists, get medical attention.

Inhalation: Move individual to fresh air. If breathing has stopped, apply artificial respiration; get medical attention

Ingestion: **DO NOT INDUCE VOMITING.** Give water or milk to drink; get medical attention.

Skin contact: Wash area with soap and water. If irritation persists, get medical attention.

CHRONIC HEALTH EFFECTS:

Not listed as a carcinogen by the NTP, IARC, or OSHA; no adverse long-term effects are known.

Medical Conditions aggravated by exposure: Existing lung or skin conditions may be aggravated by repeated exposure.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in case material is spilled: remove all sources of ignition. Soak up spill with absorbent materials.

Waste disposal method: Rags and absorbent materials should be immersed in water. Small amounts can be dried and disposed of as ordinary trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory protection: Wear NIOSH approved respirator for organic vapors.

Ventilation: Adequate to keep exposure below TLV

Protective gloves: Neoprene or rubber if prolonged skin contact is likely.


Eye protection: safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: store away from high temperature, sparks or open flame. Read and observe all precautions on product label.

Other precautions: wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.



SECTION V -- HEALTH HAZARD DATA

Route(s) of Entry: Eye contact, ingestion, inhalation, or skin contact

Acute Health Effects:

Eye contact may cause redness or irritation.

Inhalation: Dizziness, nausea, headache, and possible nervous system depression

Ingestion: Nausea, gastrointestinal irritation, or vomiting

Skin Contact: May cause rash, cracking, dryness, or defatting of the skin

EMERGENCY FIRST AID PROCEDURES:

Eye Contact: Wash with clean water for at least 15 minutes. If irritation persists, get medical attention.

Inhalation: If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen if available.

Ingestion: *Do not induce vomiting.* Give water or milk to drink, get medical attention.

Skin Contact: In case of skin contact, wash skin thoroughly with soap and water.

CHRONIC HEALTH EFFECTS: Skin contact may aggravate existing dermatitis.

SECTION VI -- SPILL OR LEAK PROCEDURE

Steps to be taken in Case of Material Spill: Remove all sources of ignition. Soak up spill with absorbent materials.

Waste Disposal Method: Rags and other absorbent materials should be immersed in water. Small amounts can be dried and disposed of as regular trash.

SECTION VII -- SPECIAL PROTECTION DATA

Respiratory Protection: Use supplied air respiratory protection in confined or enclosed spaces, if needed.

Ventilation: Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in the air. No smoking, flame, or other ignition sources.

Protective Gloves: Use chemical resistant gloves, if needed, to avoid prolonged or repeated skin contact.

Eye Protection: Safety glasses if eye contact is likely; eyewash fountain should be accessible.

SECTION VIII -- STORAGE & HANDLING DATA

Precautions to be taken in handling and storage: Store away from high temperatures, sparks, or open flame. Read and observe all precautions on the product label.

Other Precautions: Wash hands after use. Immerse contaminated rags in water.

The information contained herein is based on the data available to use and is believed to be correct. However, Gamblin Artists Colors Co. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Gamblin assumes no responsibility for injury from the use of the product described herein.