
Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: John Howard Sanden ProMix® Oil Colors and Set – CL Cautionary Labeling Required
(Note: See additional MSDS for those John Howard Sanden ProMix® Oil Colors bearing the AP Non-Toxic Seal of the Art & Creative Materials Institute)

1.2 ITEM NUMBER AND SIZES: 2501 – 2503, 2505 – 2509 - 37ml tubes,
2520 - Set of 10 ProMix Flesh Tone Colors

1.3 COMPANY IDENTIFICATION:

Martin/F. Weber Co.
2727 Southampton Road • Philadelphia, PA 19154 USA
Phone: 215-677-5600 • Fax: 215-677-3336
Email: compliance@weberart.com • Web: www.weberart.com

SECTION 2 – COMPOSITION INFORMATION

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
Cadmium Pigments	1306-23-6	<13

SECTION 2 – COMPOSITION INFORMATION

ITEM NO.	37 ML COLOR	HAZARDOUS INGREDIENT
2501	SANDEN PRO MIX O/C LIGHT 1	Cd
2502	SANDEN PRO MIX O/C LIGHT 2	Cd
2503	SANDEN PRO MIX O/C LIGHT 3	Cd
2505	SANDEN PRO MIX O/C HALFTONE 2	Cd
2506	SANDEN PRO MIX O/C DARK 1	Cd
2507	SANDEN PRO MIX O/C DARK 2	Cd
2508	SANDEN PRO MIX O/C NEUTRAL 3	Cd
2509	SANDEN PRO MIX O/C NEUTRAL 5	Cd
2520	SANDEN PRO MIX SET OF 10	Cd

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
Cd – Cadmium Pigment	1306-23-6	33

SECTION 3 – HAZARDS IDENTIFICATION
3.1 EMERGENCY OVERVIEW

Appearance: Colored Paste

Physical State: Paste

Odor: Characteristic Linseed Oil or Safflower Oil

Hazards of Product: DO NOT SPRAY APPLY CADMIUM CONTAINING COLORS – CANCER HAZARD BY INHALATION.

3.2 POTENTIAL HEALTH EFFECTS**EFFECTS OF SINGLE ACUTE OVEREXPOSURE:** n/a**CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE: INHALATION HAZARD -** Avoid spraying or aerosolizing this product. If sprayed, use a protective mask, which provides clean filtered air to the wearer and will remove all cadmium particulates from the breathed air.**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** n/a**3.3 POTENTIAL ENVIRONMENTAL EFFECTS:** n/a**SECTION 4 – FIRST AID PROCEDURES****4.1 INHALATION:** Move to fresh air. Get prompt medical attention.**4.2 EYE CONTACT:** Wash eyes with tap water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.**4.3 SKIN CONTACT:** Wash affected area with soap and water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.**4.4 SWALLOWING:** If swallowed, get prompt medical attention.**4.2 NOTES TO PHYSICIAN:** n/a**SECTION 5 - FIRE FIGHTING MEASURES****5.1 FLAMMABLE PROPERTIES**

Identification Number:	n/a
Flash Point – Closed Cup:	> 350° F (177° C)
Flash Point – Open Cup:	n/a
Auto-Ignition Temperature:	n/a
Flammable Limits in Air:	n/a

5.2 EXTINGUISHING MEDIA Foam, CO₂, Dry Chemical (Class B) or Halon®, Water Fog**5.3 EXTINGUISHING MEDIA TO AVOID** n/a

5.4 SPECIAL FIRE FIGHTING PROCEDURES

n/a

5.5 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS

As with any fire situation, full face, self contained breathing apparatus and appropriate protective clothing should be worn.

5.6 UNUSUAL FIRE AND EXPLOSION HAZARDS

n/a

5.7 HAZARDOUS COMBUSTION PRODUCTSUnder fire conditions, this product may release CO, CO₂ and other decomposition products of undetermined hazard.**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Clean up paint and paint mixed with solvents using rags or paper towels. Place in airtight containers for disposal.

SECTION 7 – HANDLING AND STORAGE

7.1 GENERAL HANDLING: After use, wash hands before eating, drinking or smoking

7.2 STORAGE: n/a

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**8.1 EXPOSURE LIMITS:**

n/a

8.2 PERSONAL PROTECTION:**Respiratory Protection:**

Do Not Spray Apply Colors that contain Cadmium Pigment

Ventilation:

n/a

Eye Protection:

n/a

Protective Gloves:

Rubber or vinyl gloves, or a barrier cream are useful for general cleanliness

Other Protective Equipment:

n/a

8.3 ENGINEERING CONTROLS:

n/a

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**Physical State:**

Paste

Appearance:

Viscous Colored Paste

pH:

<7

Solubility in Water (by weight):

Negligible

Odor:

Characteristic Linseed Oil or Safflower Oil

Flash Point – Closed Cup:

>350°F (177°C)

Flash Point – Open Cup:

n/a

Percent Volatiles:

Non-Volatile

Boiling Point (760mm Hg):

n/a

Freezing Point:

n/a

Specific Gravity (H₂O = 1):

>1

Vapor Pressure at 20°C:

n/a

Vapor Density (air = 1):

n/a

Evaporation Rate

n/a

(Butyl Acetate = 1):**Melting Point:**

n/a

Section 10 – STABILITY AND REACTIVITY

10.1 STABILITY / INSTABILITY Stable under ordinary conditions of use and storage
Conditions to Avoid n/a
Incompatible Materials n/a

10.2 HAZARDOUS POLYMERIZATION: Will not occur

10.3 INHIBITORS / STABILIZERS n/a

SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: n/a

CHRONIC TOXICITY: Cadmium pigments present a risk of cancer by inhalation.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 ENVIRONMENTAL FATE n/a
12.2 ECOTOXICITY n/a
12.3 FURTHER INFORMATION n/a

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 WASTE DISPOSAL METHOD Dispose of in accordance with local, state and federal regulations
13.2 DISPOSAL CONSIDERATIONS n/a

SECTION 14 – TRANSPORTATION INFORMATION

U.S. D.O.T n/a

SECTION 15 – REGULATORY INFORMATION

15.1 FEDERAL / NATIONAL n/a

15.2 STATE / LOCAL California Proposition 65 Labeling: WARNING, This product contains cadmium, a chemical known to the State of California to cause cancer by means of inhalation.

SECTION 16 – OTHER INFORMATION

The information presented here is current as of the date of this Material Safety Data Sheet and is believed to be accurate but is not warranted to be, whether originating with the company or not. Since use of this information and the product are not under the control of Martin/F. Weber Company, it is the user's obligation to determine conditions of safe use, in advance of use, and to carefully read the product label and follow all instructions for safe use of the product.