

<b>00445-2013</b>	<b>-2302</b>
<b>-2014</b>	<b>-2304</b>
<b>-2016</b>	<b>-2305</b>

REVISION DATE: 01/07/08

## SAFTETY DATA SHEET WINSOR & NEWTON LIQUIN LIGHT GEL

### 1 IDENTIFICATON OF THE SUBSTANCE/ PREPARATION AND COMPANY UNDERTAKING

PRODUCT NAME            WINSOR & NEWTON LIQUIN LIGHT GEL

APPLICATION                Alkyd Medium for art and creative use

SUPPLIER                    ColArt America Inc.  
11 Constitution Avenue  
Piscataway  
New Jersey  
08855-1396

Emergency telephone number    1-800-628-3385  
Tel. number for information      732-562-0770

### 2. COMPOSITION INFORMATION ON INGREDIENTS

COMPOSITION COMMENTS:

Hazardous Components	CAS Number	OSHA PEL	TLV
Low aromatic petroleum hydrocarbons	64742-47-8	No data	No data
2-butanone oxime	96-29-7	No data	No data

### 3. HAZARD IDENTIFICATION

CLASSIFICATION

In accordance with ASTM D-4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Effects this product labeled as:

**DANGER. HARMFUL. VAPOR HARMFUL. CONTAINS PETROLEUM DISTILLATES.** Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

If swallowed, do not induce vomiting. Call a physician or poison control center immediately. Get prompt medical attention.

### 4. FIRST AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

INGESTION

**DO NOT INDUCE VOMITING!** Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort

1

**SKIN CONTACT**

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get prompt medical attention if any discomfort continues.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lid. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5. FIRE FIGHTING MEASURES****EXTINGUISHING MEDIA**

This product is not flammable. Use fire extinguishing media appropriate for surrounding materials.

**6. ACCIDENTAL RELEASE MEASURES****SPILL CLEAN UP METHODS**

Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place in to containers. Do not contaminate water courses or sewer. Dispose of the colour in accordance with local regulations.

**7. HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapors.

**STORAGE PRECAUTIONS**

Keep in original container. Store at moderate temperatures in dry, well ventilated area. Persons susceptible for allergic reactions should not handle this product.

**8. EXPOSURE CONTROLS/ PERSONAL PROTECTION****ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contamination.

**EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

**HYGEINE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Liquid
COLOR	Lightly colored
ODOR	Hydrocarbon
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	150 - 200 760 mm Hg
RELATIVE DENSITY	0.9
VOLATILE BY VOL (%)	80
FLASH POINT (°C)	70 (Closed cup)
FLAMMABLE LIMITS	LEL = 0.9; UEL = 6.0
pH-VALUE CONC. SOL .	Not applicable

**10. STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid contact with acids and oxidizing substances. Avoid excessive heat for prolonged periods of time.

**HAZARDOUS DECOMPOSITION PRODUCTS**

High temperature generates fumes of carbon dioxide and carbon monoxide.

**11. TOXICOLOGICAL INFORMATION****GENERAL INFORMATION****INHALATION**

May cause sensitization by inhalation.

**INGESTION**

May cause discomfort if swallowed

**SKIN CONTACT**

Prolonged contact may cause sensitization.

**EYE CONTACT**

Spray and vapor in the eyes may cause irritation and smarting.

**ROUTE OF ENTRY**

Inhalation. Skin and eye contact.

**MEDICAL SYMPTOMS**

Inhalation of large quantities of vapor may cause dizziness, headache. Prolonged contact with skin may cause irritation.

**12. ECOLOGICAL INFORMATION****ECOTOXICITY**

Not regarded as dangerous to the environment

**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14. TRANSPORT INFORMATION**

RAIL TRANSPORT NOTES Not classified

SEA TRANSPORT NOTES Not classified

AIR TRANSPORT NOTES Not classified

**15. REGULATORY INFORMATION**

This product has been evaluated by a toxicologist and is labeled for acute and chronic health hazards in accordance with the Labeling of Hazardous Art Materials Act and Federal regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act.

This product conforms to ASTM D 4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Hazards. The warning given on the product label is:

**DANGER. VAPOR HARMFUL. CONTAINS PETROLEUM DISTILLATES.** Use only with adequate ventilation. **KEEP OUT OF REACH OF CHILDREN.**

If swallowed, do not induce vomiting. Call a physician or poison control center immediately. Get prompt medical attention.

**16. OTHER INFORMATION****INFORMATION SOURCE**

Material Safety ~Data Sheet, Misc. manufacturers.

**REVISION DATE**

01/07/08