

| |
|-------------------|
| 00448-1113 |
| -1114 |

MATERIAL SAFETY DATA SHEET

MSDS #: P069

Page 1 of 3

Sanford NA
 2707 Butterfield Road
 Oak Brook, IL 60523
 Phone: 630-481-2000 or 800-323-0749

Emergency Medical Number: 888-786-0972

Creation Date: August 1, 2005

Section One: Product Information

Product Name: Grumbacher Pre-Tested Oil Colors
 Product Sizes: 37 and 150 ml
 Product Class: Artists' Oil Paint

Section Two: Ingredients

| Ingredients | CAS Number | % by Weight | PEL/TLV |
|----------------|------------|-------------|------------|
| Lead Carbonate | 598-63-0 | 75.0% | 0.05 mg/m3 |
| Zinc Oxide | 7727-43-7 | 5.0% | 10 mg/m3 |

Section Three: Hazards Identification

WARNING: MAY BE HARMFUL IF SWALLOWED. CANCER AGENT BASED ON EXPERIMENTAL DATA. EXPOSURE MAY CAUSE HARM TO THE DEVELOPING FETUS, OR DAMAGE TO THE TESTES, OR DIFFICULTY WITH REPRODUCTION (CHILD BEARING), OR NERVOUS SYSTEM, KIDNEY, OR BONE MARROW DAMAGE.

CONTAINS: LEAD. SOLUBLE LEAD. PRECAUTIONS: Wash hands immediately after use. When using, do not eat, drink, or smoke. Wear a work apron. Keep in original container. **AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. NOT FOR USE IN HEALTH CARE FACILITIES. KEEP OUT OF REACH OF CHILDREN. FIRST AID:** If swallowed, get prompt medical attention. For further health information, contact a poison control center or call 888-786-0972.

****WARNING: DO NOT SPRAY APPLY --** This product contains cadmium, a chemical known to the State of California to cause cancer by means of inhalation.

****WARNING:** This product contains lead, a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Section Four: First Aid Measures

Inhalation: Move to fresh air.
 Skin Contact: Wash immediately with soap and water.
 Eye Contact: Flush with flowing water.
 Ingestion: If swallowed, get prompt medical attention. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: P069

MATERIAL SAFETY DATA SHEET

MSDS #: P069

Page 2 of 3

Section Five: Fire Fighting Measures

Flash Point: Not flammable

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: As appropriate for surrounding area.

Special Fire Fighting Measures: No special fire fighting procedures.

Unusual Fire and Explosion Hazards: Not combustible

Section Six: Accidental Release Measures

No special spill procedures required

Section Seven: Handling and Storage

Handling: When using, do not eat, drink, or smoke.

Storage: Keep in original container. KEEP OUT OF REACH OF CHILDREN.

Section Eight: Exposure Controls and Personal Protection

Respiratory Protection and Special Ventilation Requirements: None required

Other Protective Equipment (Gloves, Goggles, Etc.): None

Work/Hygiene Practices: PRECAUTIONS: Wash hands immediately after use. When using, do not eat, drink, or smoke. Wear a work apron. Keep in original container. AVOID USING IF PREGNANT OR CONTEMPLATING PREGNANCY. NOT FOR USE IN HEALTH CARE FACILITIES. KEEP OUT OF REACH OF CHILDREN.

Section Nine: Physical and Chemical Properties

Boiling Point: Not determined Melting Point: Not determined

Vapor Pressure: Not determined Specific Gravity: Not determined

Specific Vapor Density (AIR = 1): Not determined Evaporation Rate (Butyl Acetate = 1): Not determined

Solubility in Water: Not determined Reactivity in Water: Non-reactive

Appearance and Odor: Colored paints; oily odor

Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Excessive heat

Chemical Incompatibility: None known

Hazardous Decomposition: None known

Hazardous Polymerization: Will not occur

MATERIAL SAFETY DATA SHEET

MSDS #: P069

Page 3 of 3

| | |
|------------------------|----------------------------------|
| Section Eleven: | Toxicological Information |
|------------------------|----------------------------------|

IARC Monographs: No

National Toxicology Program: No

OSHA Regulated: No

Effects/Symptoms of Acute Exposure: May be harmful if swallowed.

Effects/Symptoms of Chronic Exposure: Exposure may cause difficulty with reproduction. Exposure may cause nervous system, kidney, or bone marrow damage.

Medical Conditions Usually Aggravated By Overexposure of This Product: Unknown

| | |
|------------------------|-------------------------------|
| Section Twelve: | Ecological Information |
|------------------------|-------------------------------|

Not available

| | |
|--------------------------|--------------------------------|
| Section Thirteen: | Disposal Considerations |
|--------------------------|--------------------------------|

Dispose in accordance with Federal, State, and Local Regulations.

| | |
|--------------------------|------------------------------|
| Section Fourteen: | Transport Information |
|--------------------------|------------------------------|

Toxic Liquid, Inorganic, n.o.s. (lead), 6, UN3287, PGIII Limited Quantities, EmS# 6.1-02
Toxic Liquid, inorganic, n.o.s. (lead), 6, UN3287, PGIII Limited Quantities, EmS# 6.1-02, packing instruction Y611

| | |
|-------------------------|-------------------------------|
| Section Fifteen: | Regulatory Information |
|-------------------------|-------------------------------|

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

| | |
|-------------------------|--------------------------|
| Section Sixteen: | Other Information |
|-------------------------|--------------------------|

| HMIS Code | |
|---------------------|---|
| Health | 3 |
| Flammability | 0 |
| Reactivity | 0 |
| Personal Protection | C |

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Sanford Corporation is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.