

**00455-1004**

## Certificate of Compliance & Material Safety Data Sheet

For Health Emergencies: CALL A POISON CONTROL CENTER  
For Transportation Emergencies ONLY: Call Chem-Tel  
USA, Canada, Puerto Rico, US Virgin Islands: Call 800-255-3924  
Outside North America: Call Collect 813-248-0585

Date Prepared  
Rev: 15 October 2009  
Replaces: 30 June 2009

### Certificate of Compliance Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: Bob Ross® Oil Paint Medium

1.2 ITEM NUMBER AND SIZES: R6740 - 118ml

1.3 CPSC SAFETY REGULATION CITATION

This adult product is certified to comply with the Consumer Product Safety Act (CPSA), the Poison Prevention Packaging Act, the Federal Hazardous Substances Act (FHSA) and its Labeling for Hazardous Art Materials Amendment (LHAMA.)

1.4 MANUFACTURER IDENTIFICATION:

Martin F. Weber Co.  
2727 Southampton Road • Philadelphia, PA 19154 USA  
Phone: 215-677-5600 • Fax: 215-677-3336  
Email: [compliance@weberart.com](mailto:compliance@weberart.com) • Web: [www.weberart.com](http://www.weberart.com)

1.5 CONTACT INFORMATION:

Regulatory & Compliance Manager  
Martin F. Weber Co.  
2727 Southampton Road • Philadelphia, PA 19154 USA  
Phone: 215-677-5600 • Fax: 215-677-3336  
Email: [compliance@weberart.com](mailto:compliance@weberart.com)

1.6 DATE & PLACE OF MANUFACTURE:

For purposes of the Consumer Product Safety Improvement Act (CPSIA), this product is deemed to be manufactured as of the date of shipment, at the above address.

1.7 DATE & PLACE PRODUCT TESTED FOR COMPLIANCE WITH THE REGULATIONS ABOVE (1.4):

Date: 29 August 2006  
Place: Duke University Medical Center  
2200 West Main Street, Suite 400  
Durham NC 27705

1.8 THIRD-PARTY LABORATORY(S) ON WHICH THIS CERTIFICATE DEPENDS

None

---

 MSDS Section 1 - PRODUCT AND COMPANY IDENTIFICATION
 

---

1.1 PRODUCT NAME: Bob Ross® Oil Paint Medium

1.2 ITEM NUMBER AND SIZES: R6740 - 118ml

1.3 COMPANY IDENTIFICATION:

Martin F. Weber Co.  
 2727 Southampton Road • Philadelphia, PA 19154 USA  
 Phone: 215-677-5600 • Fax: 215-677-3336  
 E-mail: [compliance@weberart.com](mailto:compliance@weberart.com) • Web: [www.weberart.com](http://www.weberart.com)

---

 SECTION 2 – COMPOSITION INFORMATION
 

---

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
Linseed Oil	8001-26-1	75
Aliphatic Hydrocarbon	8052-41-3	25

---



---

 SECTION 3 – HAZARDS IDENTIFICATION
 

---

3.1 EMERGENCY OVERVIEW

**Appearance:** Clear light yellow colored liquid

**Physical State:** Liquid

**Odor:** Light to negligible petroleum solvent and characteristic linseed oil

**Hazards of Product:** Combustible, Harmful or fatal if swallowed. Vapor harmful.

3.2 POTENTIAL HEALTH EFFECTS

EFFECTS OF SINGLE ACUTE OVEREXPOSURE: Harmful or fatal if swallowed. Vapor harmful.

CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE: May be harmful by breathing vapors.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: n/a

3.3 POTENTIAL ENVIRONMENTAL EFFECTS: n/a

---

 SECTION 4 – FIRST AID PROCEDURES
 

---

4.1 INHALATION: Move to fresh air. Get prompt medical attention.

4.2 EYE CONTACT: Wash eyes with tap water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.

4.3 SKIN CONTACT: Wash affected area with soap and water for five to ten (5 – 10) minutes. Apply hand cream to affected areas. If irritation persists, seek prompt medical attention.

4.4 SWALLOWING: If swallowed, do not induce vomiting. Aspiration Hazard. Call a physician or poison control center immediately. Get prompt medical attention.

4.2 NOTES TO PHYSICIAN: n/a

---

**SECTION 5 - FIRE FIGHTING MEASURES**
**5.1 FLAMMABLE PROPERTIES**

<b>Identification Number:</b>	UN 1263
<b>Flash Point – Closed Cup:</b>	125°F (52°C)
<b>Flash Point – Open Cup:</b>	n/a
<b>Auto-Ignition Temperature:</b>	n/a
<b>Flammable Limits in Air:</b>	n/a

**5.2 EXTINGUISHING MEDIA** Foam, CO<sub>2</sub>, Dry Chemical (Class B) or Halon®

**5.3 EXTINGUISHING MEDIA TO AVOID** Water

**5.4 SPECIAL FIRE FIGHTING PROCEDURES** n/a

**5.5 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS** As with any fire situation, full face, self contained breathing apparatus and appropriate protective clothing should be worn.

**5.6 UNUSUAL FIRE AND EXPLOSION HAZARDS** Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Waste soaked with this material should be placed in approved waste cans

**5.7 HAZARDOUS COMBUSTION PRODUCTS** Under fire conditions, this product may release CO, CO<sub>2</sub>, and other decomposition products of undetermined hazard.

---

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Keep sources of ignition away. Clean up spills with rags, paper towels, vermiculite or other inert material. Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Waste soaked with this material should be placed in approved waste cans and / or soaked with water, for disposal in accordance with local state and federal regulations.

---

**SECTION 7 – HANDLING AND STORAGE**

**7.1 GENERAL HANDLING:** Avoid ingestion. Avoid breathing vapors. Use exhaust fan to remove vapors and assure adequate ventilation. Do not transfer contents to unlabeled containers. **KEEP OUT OF THE REACH OF CHILDREN.** Keep from sources of ignition, oxidizing materials, heat and flame. **KEEP AWAY FROM OPEN FLAMES. NO SMOKING** in areas of use or storage.

**7.2 STORAGE:** Keep from sources of ignition, oxidizing materials, heat and flame. Keep containers closed when not in use.

---

**SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**8.1 EXPOSURE LIMITS:** OSHA PEL 500ppm TWA, OSHA VPEL 100ppm TWA, ACGIH TLV-100ppm.

**8.2 PERSONAL PROTECTION:**  
**Respiratory Protection:** Not required if adequate cross ventilation is maintained.

**Ventilation:** Use a local exhaust fan along with fresh air source to avoid vapor buildup  
**Eye Protection:** Use OSHA approved chemical splash goggles with side shields  
**Protective Gloves:** Wear resistant (Rubber or vinyl) gloves to minimize skin contact.  
**Other Protective Equipment:** Body protection suitable for the work environment

8.3 ENGINEERING CONTROLS: n/a

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid  
**Appearance:** Clear light yellow liquid  
**pH:** n/a  
**Solubility in Water (by weight):** Negligible  
**Odor:** Light to negligible petroleum solvent and characteristic linseed oil  
**Flash Point – Closed Cup:** 125°F (52°C)  
**Flash Point – Open Cup:** n/a  
**Percent Volatiles:** 25%, VOC = 169g/l  
**Boiling Point (760mm Hg):** 340 - 400° F (171° - 204° C)  
**Freezing Point:** n/a  
**Specific Gravity (H<sub>2</sub>O = 1):** 0.89  
**Vapor Pressure at 20°C:** 33mg Hg  
**Vapor Density (air = 1):** n/a  
**Evaporation Rate** <1  
**(Butyl Acetate = 1):** n/a  
**Melting Point:** n/a

## Section 10 – STABILITY AND REACTIVITY

**10.1 STABILITY / INSTABILITY** Spontaneous combustion can occur  
**Conditions to Avoid** Keep from heat, open flame and sources of ignition  
**Incompatible Materials** Avoid contact with: excessive heat, strong oxidizing agents  
**10.2 HAZARDOUS POLYMERIZATION** Will not occur  
**10.3 INHIBITORS / STABILIZERS** n/a

## SECTION 11 – TOXICOLOGICAL INFORMATION

**ACUTE TOXICITY:** ACUTE TOXICITY: LD 50 and LC 50 Data  
 Petroleum Distillates (CAS# 8052-41-3)  
 Oral LD (rat): >5000mg/kg  
 Dermal LD (rabbit): >3000mg/kg  
 Inhalation LC (rat, 4 hour): >5500mg/m<sup>3</sup>

**CHRONIC TOXICITY:** n/a

## SECTION 12 – ECOLOGICAL INFORMATION

**12.1 ENVIRONMENTAL FATE** n/a  
**12.2 ECOTOXICITY** n/a  
**12.3 FURTHER INFORMATION** n/a

---

**SECTION 13 – DISPOSAL CONSIDERATIONS**

13.1 WASTE DISPOSAL METHOD      Dispose of in accordance with local, state and federal regulations  
13.2 DISPOSAL CONSIDERATIONS      Keep from heat, open flame, sparks and sources of ignition

---

**SECTION 14 – TRANSPORTATION INFORMATION**

U.S. D.O.T                              Ground Transportation: Not Regulated  
    Ocean Transportation: UN 1263 Paint Related Material, Class 3, PG III,  
    Limited Quantity  
    DO NOT SHIP via air freight without special packaging and  
    labeling. Contact your air carrier for detailed instructions.

---

**SECTION 15 – REGULATORY INFORMATION**

15.1 FEDERAL / NATIONAL              n/a  
15.2 STATE / LOCAL                      n/a  
15.3 CANADA                              Class A - Compressed Gas - Does Not Meet Criteria  
    Class B - Flammable & Combustible Material - B3 Flammable &  
    Combustible Material - Combustible Liquid  
    Class C - Oxidizing Material - Does Not Meet Criteria  
    Class D - Poisonous & Infectious - Division 1 - Does Not Meet Criteria  
    Class D - Poisonous & Infectious - Division 2 - Does Not Meet Criteria  
    Class E - Corrosive Material - Does Not Meet Criteria  
    Class F- Dangerously Reactive Material - - Does Not Meet Criteria

---

**SECTION 16 – OTHER INFORMATION**

The information presented here is current as of the date of this Material Safety Data Sheet and is believed to be accurate but is not warranted to be, whether originating with the company or not. Since use of this information and the product are not under the control of Martin/F. Weber Company, it is the user's obligation to determine conditions of safe use, in advance of use, and to carefully read the product label and follow all instructions for safe use of the product.