

**00624-2009**

**00624-all codes except:**

**MATERIAL SAFETY DATA SHEET**

IDENTITY (AS USED ON LABEL AND LIST)

May be used to comply with OSHA's 29 CFR 1910.1200

Note: Blank spaces are not permitted. If any item is not applicable.

**DICK BLICK ACRYLIC COLORS**

or no information available, the space must be marked appropriately

**SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION**

ROCK PAINT DISTRIBUTING CORP.	(608) 868-6873
MANUFACTURER	TELEPHONE NUMBER FOR INFORMATION
365 SUNNYSIDE DR. P.O. BOX 482	(920) 563-8545
ADDRESS	EMERGENCY TELEPHONE NUMBER
MILTON, WI 53563	JULY 2007
	DATE PREPARED

<b>-0129 -1009 -1029 -3093</b>
<b>-3094 -3095 -3096 -3103</b>
<b>-3104 -3105 -3106 -4073</b>
<b>-4074 -4075 -4076 -4093</b>
<b>-4094 -4095 -4096 -4533</b>
<b>-4534 -4535 -4536 -7083</b>
<b>-7084 -7085 -7086</b>

**SECTION 2 - MATERIAL IDENTIFICATION AND INFORMATION**

COMPONENTS	CHEMICAL NAME & COMMON NAMES	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
------------	------------------------------	---	----------	-----------	--------------------------

Contains no hazardous substand per OSHA 29 CFR 1910.1200

Material is a water based product with the AP Seal. Products with the AP Approved Products Seal of the Art and Craft Materials Institute Inc. are certified in a program of toxicological evaluation by a medium expert to contain no material in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified by the Institute to be in accordance with the voluntary chronic hazard labeling standard ASTM D-4236. In addition, there is no physical hazard as defined within 29 CFR Part 1910.1200 (c).

**SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS**

BOILING POINT	Range 215-225 F	SPECIFIC GRAVITY (H <sub>2</sub> O = 1)	Range 1.03-1.68
VAPOR PRESSURE (mm Hg & TEMPERATURE)	N/A	MELTING POINT	N/A
VAPOR DENSITY (AIR = 1)	lighter than air	EVAPORATION RATE (WATER = 1)	wer than ether
SOLUBILITY IN WATER	completely soluble in water	WATER REACTIVE	N/A
APPEARANCE & ODOR	various colors and odorless		

**SECTION 4 - FIRE AND EXPLOSION HAZARD DATA**

FLASH POINT & METHOD USED	N/A	FLAMMABILITY LIMITS IN AIR % BY VOLUME	N/A
EXTINGUISHER MEDIA	CO <sub>2</sub> , Foam or Water		N/A
SPECIAL FIRE FIGHTING PROCEDURES	None known		
UNUSUAL FIRE AND EXPLOSION HAZARDS	None		

**SECTION 5 - REACTIVITY HAZARD DATA** BLICKRYLIC COLORS Page 2 of 2

## STABILITY                      CONDITIONS TO AVOID

 STABLENone UNSTABLEINCOMPATIBILITY (MATERIALS TO AVOID)    N/AHAZARDOUS DECOMPOSITION PRODUCTS    N/A

HAZARDOUS POLYMERIZATION                      CONDITIONS TO AVOID

 MAY OCCURN/ANone known WILL NOT OCCUR**SECTION 6 - HEALTH HAZARD DATA**PRIMARY ROUTES OF EN<sup>T</sup>                      N/A                      CARCINOGEN LISTED IN                      N/A INHALATION INGESTION NTP OSHA SKIN ABSORPTION NOT HAZARDOUS IARC MONOGRAPH NOT LISTED

HEALTH HAZARDS

 ACUTE

Refer to Section 2

 CHRONIC

SIGNS AND SYMPTOMS

Not known

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Not knownEMERGENCY FIRST AID PROCEDURES - Consult a Physician immediately.**SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES**

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

Usual Clean Up Procedure

WASTE DISPOSAL METHODS

Dispose of in accordance with Federal and Local State Regulations

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store at room temperature.

OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS

Not known**SECTION 8 - CONTROL AND PROTECTIVE MEASURES**

RESPIRATORY PROTECTION (SPECIFY TYPE)

None required

VENTILATION TO BE USED

 LOCAL EXHAUSE MECHANICAL (GENERAL) SPECIALNone required OTHER (SPECIFY)

PROTECTIVE GLOVES

N/A

EYE PROTECTION

N/A

OTHER PROTECTIVE CLOTHING AND EQUIPMENT

N/A

HYGIENIC WORK PRACTICES

N/A

00624 - 3093
- 3094
- 3095
- 3096

**Material Safety Data Sheet**  
**U.S. Department of Labor**  
*Rev'd 01-24-01*

Occupational Safety and Health Administration  
(Non-Mandatory Form)

**IDENTITY (As Used on Label and List):** Acrylic Cadmium Red Light, 00624-309

**Section I**

Manufacturer's Name Creative Art Products	Telephone Number for Information/Emergency (309) 342-0179
Address (Number, Street, City, State, and ZIP Code) 1558 S. Henderson St., Galesburg, IL, 61401	Date Prepared 12/27/99

**Section II - Hazard Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Pigment Red 108:1, C.I. #77202:1	0.2 mg/M3 Cd	No info	Dust TWA 8 Hr	
Cadmium	No info	No info	No info	

**Section III - Physical/Chemical Characteristics**

Boiling Point: No info	Specific Gravity (H <sub>2</sub> O = 1): 1.40
Vapor Pressure (mm Hg.): No info	Melting Point: No info
Vapor Density (AIR = 1): Heavier than air	Evaporation Rate (Butyl Acetate = 1): Slower than ether
Solubility in Water: Soluble	
Appearance and Odor: Opaque, viscous liquid with ammonia odor	

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used): No info	Flammable Limits:	LEL: No info	UEL: No info
Extinguishing Media: Foam, alcohol foam, CO <sub>2</sub> , dry chemical, water fog, other			
Special Fire Fighting Procedures: Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.			
Unusual Fire and Explosion Hazards: None known			

**Section V - Reactivity Data**

Stability:	Unstable	Conditions to Avoid: Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.
	Stable: X	
Incompatibility (Materials to Avoid): Alkaline materials, strong acids and oxidizing materials.		
Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide, oxides of nitrogen, and possibly acrolein.		
Hazardous Polymerization: Will not occur		

**Section VI - Health Hazard Data**

Route(s) of Entry: Inhalation, Skin, Ingestion
Health Hazards (Acute and Chronic): Inhalation: Dizziness, breathing difficulty, headaches, and loss of coordination. Eye contact: Severe irritation, tearing, redness, and blurred vision. Skin contact: Can dry and defat skin causing cracks, irritation, and dermatitis. Ingestion: Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea. See warning below for chronic health hazards.

V-1888

<b>Carcinogenicity:</b> <b>WARNING: DO NOT SPRAY APPLY</b> – This product contains cadmium, a chemical known to the State of California to cause cancer by means of inhalation.	<b>NTP?</b> No info	<b>IARC Monographs?</b> No info	<b>OSHA Regulated?</b> No info
<b>Signs and Symptoms of Exposure:</b> See above.			
<b>Medical Conditions Generally Aggravated by Exposure:</b> None known			
<b>Emergency and First Aid Procedures:</b> Inhalation exposure: Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Eye contact: Flush with large quantities of water for 15 minutes. Skin contact: Wash thoroughly with soap and water and see a doctor. Ingestion: Do not induce vomiting, can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.			

## Section VII - Precautions for Safe Handling and Use

<b>Steps to Be Taken in Case Material is Released or Spilled:</b> Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Thoroughly wet with water and mix.
<b>Waste Disposal Method:</b> Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state, and federal hazardous waste regulation before disposing into approved hazardous waste landfills. Obey relevant laws.
<b>Precautions to be Taken in Handling and Storing:</b> Use non-sparking utensils when handling this material. Avoid hot metal surface. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.
<b>Other Precautions:</b> Smoking in area where this material is used should be strictly prohibited. Tools used with this material should be made from aluminum, brass or copper. Plastic utensils should not be used. <b>NOTE:</b> This information is accurate to the best knowledge of Creative Art Products, Inc., but is furnished without any expressed or implied warranties.

## Section VIII - Control Measures

<b>Respiratory Protection (<i>Specify Type</i>):</b> Do not spray apply. When using this material use a NIOSH approved cartridge respirator or gas mask suitable to keep airborne mists and vapor concentrations below the time weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.	
<b>Ventilation:</b> General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion-proof.	
<b>Protective Gloves:</b> Impermeable chemical handling gloves for skin protection	<b>Eye Protection:</b> Use chemical safety glasses, goggles, and faceshields for eye protection.
<b>Other Protective Clothing or Equipment:</b> Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended.	
<b>Work/Hygienic Practices:</b> Eye washes and safety showers in the workplace are recommended.	

00624 - 4533  
 - 4534  
 - 4535  
 - 4536

Material Safety Data Sheet  
 U.S. Department of Labor

Occupational Safety and Health Administration  
 (Non-Mandatory Form)

Revised 01-24-01

IDENTITY (As Used on Label and list): Acrylic Cadmium Orange

Section I

Manufacturer's Name Rock Paint Distributing Corp.	Telephone Number for Information/Emergency (608) 868-6873
Address (Number, Street, City, State, and ZIP Code) 365 Sunnyside Dr. P.O. Box 482	Date Prepared January 17, 2001

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Pigment Org 20:1, C.I. #77202:1	0.2 mg/M3 Cd	No info	Dust TWA 8 Hr	
Cadmium	No info	No info	No info	

Section III - Physical/Chemical Characteristics

Boiling Point:	No info	Specific Gravity (H2O = 1):	1.40
Vapor Pressure (mm Hg):	No info	Melting Point:	No info
Vapor Density (AIR=1):	Heavier than air	Evaporation Rate (Butyl Acetate = 1):	Slower than ether
Solubility in Water:	Soluble		
Appearance and Odor:	Opaque, viscous liquid with ammonia odor		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used):	No info	Flammable Limits:	LEL: No info UEL: No info
Extinguishing Media:	Foam, alcohol foam, CO2, dry chemical, water fog, other		
Special Fire Fighting Procedures:	Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.		
Unusual Fire and Explosion Hazards:	None known		

Section V - Reactivity Data

Stability:	Unstable:	Conditions to Avoid: Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.
	Stable: X	
Incompatibility	(Materials to Avoid):	Alkaline materials, strong acids and oxidizing materials.
Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide, oxides of nitrogen, and possibly acrolein.		
Hazardous Polymerization: Will not occur		

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation, Skin, Ingestion	
Health Hazards (Acute and Chronic):	Inhalation: Dizziness, breathing difficulty, headaches, and loss of coordination. Eye contact: Sever irritation, tearing, redness, and blurred vision.	
Skin contact:	Can dry and defat skin causing cracks, irritation, and dermatitis.	Ingestion: Can cause gastrointestinal irritation, vomiting, nausea, and diarrhea. See warning below for chronic health hazards.

V-1988

<b>Carcinogenicity:</b> <b>WARNING: DO NOT SPRAY APPLY</b> This product contains cadmium, a chemical known to the State of California to cause cancer by means of inhalation.	<b>NTP?</b> No info	<b>IARC Monographs?</b> No info	<b>OSHA Regulated?</b> No info
<b>Signs and Symptoms of Exposure:</b> See above			
<b>Medical Conditions Generally Aggravated by Exposure:</b> None known			
<b>Emergency and First Aid Procedures:</b> If breathing stops, apply artificial respiration and seek immediate medical attention. <b>Eye Contact:</b> Flush with large quantities of water for 15 minutes. and water and see a doctor. <b>Ingestion:</b> Do not induce vomiting. can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.	<b>Inhalation Exposure:</b> Move person to fresh air.		
	<b>Skin contact:</b> Wash thoroughly with soap		

**Section VII - Precautions for Safe Handling and Use**

<b>Steps to Be Taken in Case Material is Released or Spilled:</b> Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Thoroughly wet with water and mix	
<b>Waste Disposal Method:</b> Collect absorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local, state, and federal hazardous waste regulation before disposing into approved hazardous waste landfills. Obey relevant laws.	
<b>Precautions to be Taken in Handling and Storing:</b> Use non-sparking utensils when handling this material. Avoid hot metal surface. Use in cool, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat and open flames.	
<b>Other Precautions:</b> Smoking in area where this material is used should be strictly prohibited. Tools used with this material should be made from aluminum, brass or copper. Plastic utensils should not be used.	
<b>NOTE:</b> This information is accurate to the best knowledge of Rock Paint Distributing Corp., but is furnished without any expressed or implied warranties.	

**Section VIII - Control Measures**

<b>Respiratory Protection (Specify Type):</b> Do not spray apply. When using this material use a NIOSH approved cartridge respirator or gas mask suitable to keep airborne mists and vapor concentrations below the time weighted threshold limit values. When using in poorly ventilated and confined spaces, use a fresh-air supplying respirator or a self-contained breathing apparatus.	
<b>Ventilation:</b> General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion-proof.	
<b>Protective Gloves:</b> Impermeable chemical handling gloves for skin protection.	<b>Eye Protection:</b> Use chemical safety glasses, goggles, and faceshields for eye protection.
<b>Other Protective Clothing or Equipment:</b> Use impermeable aprons and protective clothing whenever possible to prevent skin contact. The use of head caps whenever possible is strongly recommended.	
<b>Work/Hygienic Practices:</b> Eye washes and safety showers in the workplace are recommended.	