

Nov 23 2002 12:43PM HP LASERJET 3200

00667 - all Codes except -
3093 - 3723 - 4533 - 7913 - 7953 - 1034
3103 - 4093 - 4543 - 7923 - 1014
3713 - 4353 - 4553 - 7933 - 1024

12-15-03 ✓

MATERIAL SAFETY DATA SHEET
SHA Hazard Communication
Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 9/18/91 at 12:28:39 pm

Material Identity
Lascaux Acrylic Artists Colors
NON CADMIUM CONTAINING COLORS)

Sec. No. 5 Rev. No. 1
ASTM D4236-89 Yes
Certification

SECTION I MANUFACTURER'S NAME AND LOCATION

Manufact. Name Lascaux Farbenfabrik AG.
Address line 1 42 Zurichstrasse
Address line 2 Brütisellen, CH-8306
Address line 3 Switzerland
Address line 4
Info. Tel. No. 011-41-1-833-0786 Emerg. Tel. No. 1(800)468-6942
Prep. Date 09/05/91 Responsible Person Alois K. Diethelm

SECTION II HAZARDOUS INGREDIENTS/IDENTITY/STANDARDS/CONTENT INFORMATION

Ingredient Listing CAS No. OSHA PEL ACGIH TLV STEL % COMP
Trade Secret
Non Hazardous Water
Based Paint Mixture

This product is intended for professional use. While it is not intended for use by children, such use is possible. Successful art use may require adult supervision. Not intended to be used in spray applications. If so used, provide adequate ventilation and avoid breathing paint mist.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point N/A Deg. F (Cel) Spec. Grav. N/A
Melting Point N/A Deg. F (Cel) (H2O=1)
Vapor Pressure N/A Vapor Density N/A
Evaporation Rate N/A Water Solubility N/A
Odor Latex paint odor Appearance Paints in various colors

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point N/A Deg. F. (Cel) Flash Pt. Method N/A
Lower Flam. Limit N/A Upper Flam. Limit N/A
Exting. Medium Water, foam, carbon dioxide or dry chemical.
Specialized Fire None required for this material. However, when fighting any fire, wear positive pressure self-contained NIOSH approved breathing equipment.

Unusual Fire & Explosion Hazard Sealed containers may rupture; Paint films may burn. This product presents no unusual fire or explosion hazards.

SECTION V REACTIVITY DATA

Stable (Unstable) Conditions Strong oxidizing agents.
Stable (yes/no) Yes to avoid
(Stable)
Incompat. (Avoid) Avoid strong oxidizing agents
Haz. Decomp. (y/n) Not Likely to Haz. Polym. (yes/no) No
Cond. to Avoid. None Known

Confirm all information prior to use
Abbreviations: Not Applicable N/A.. Not Flammable N/F Ceiling Value C
Not Known N/K Not Determined N/D
Not Listed N/L
Permissible Exposure Limit PEL ACGIH Threshold Limit Value TLV
The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given. (TLV Reg. TM, ACGIH)

V.3671

Nov 23 2002 12:44PM HP LASERJET 3200

p. 12

Artist non-cadmium

MATERIAL SAFETY DATA SHEET
SHA Hazard Communication
Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 9/18/91 at 12:28:42pm

Material Identity Lascaux Acrylic Artists Colors

SECTION VI HEALTH HAZARD DATA

Routes of Entry: Inhalation Vapors can be inhaled; not likely in toxic amounts.
Skin Not likely in toxic amounts Ingest. Liquids may be ingested.
Health Hazards None Known for the usual and ordinary professional uses of
this product.
TP Carcinogen No IARC Carcinogen No OSEA Carcinogen No
Signs/Symptoms None Likely under normal professional use
Pre-Exposure
Medical Conditions None Known
First Aid
Inhalation: Remove to fresh air and support respiration. Eyes:
carefully wash or rinse for 15 minutes. Contact a physician if
irritation occurs or persists. Skin; Wash area with soap and water
Ingestion: Drink water or milk to dilute, contact a physician.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Contain Spill. Spill area will be slippery. Recover as
much as possible for reuse. Spread commercial absorbant
over remainder and place into sealed container for
disposal.
Waste Disp Dispose as directed by all Federal, State and Local
regulations. Most states prohibit disposal of liquids in
landfills.
Precautions Wash thoroughly after handling product. Use under well
ventilated conditions. Avoid contact with eyes and skin.
Other Precautions As with all chemical good industrial hygiene and proper
work habits should be observed.

SECTION VIII CONTROL MEASURES

Resp. Protect. Not normally needed
Local Exhaust May be used to prevent routine inhalation.
Mech. Local. Exh. Use with normal room ventilation
Mech. Exhaust None Specifically required
Other Mech. Exhaust None
Skin Contact. Gloves
Gloves are recommended when handling large amounts.
Eye Protect. May be used if desired during close work.
Skin Contact. Clothing Artist's smock or other similar protective garment.
Work Practices Do not spray or use with air brush systems. Good
industrial hygiene and proper work habits should be
observed at all times. Clean up work area after use. This
product is intended for professional use only.

Confirm all information prior to use
Approximations: Not Applicable N/A -- Not Flammable N/F
Not Known N/K
Permissible Exposure Limit (PEL) N/A
ACGIH Threshold Limit Value (TLV) N/A
Ceiling Value C
Not Determined N/D
Not Listed N/L
TLV
The data shown here is taken from sources published by the American Chemical Society and should be used as a guide only. For more information, contact the American Chemical Society, 11 Dupont Circle, N.W., Washington, D.C. 20036.