

Nov 23 2002 12:43PM HP LASERJET 3200

00667 - all Codes except -
3093 - 3723 - 4533 - 7913 - 7953 - 1034
3103 - 4093 - 4543 - 7923 - 1014
3713 - 4353 - 4553 - 7933 - 1024

12-15-03 ✓

MATERIAL SAFETY DATA SHEET
SHA Hazard Communication
Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 9/18/91 at 12:28:39 pm

Material Identity: Lascaux Acrylic Artists Colors
NON CADMIUM CONTAINING COLORS)
Seq. No. 5 Rev. No. 1
ASTM D4236-89 Yes
Certification

SECTION I MANUFACTURER'S NAME AND LOCATION

Manufact. Name: Lascaux Farbenfabrik AG.
Address line 1: 42 Zurichstrasse
Address line 2: Brütisellen, CH-8306
Address line 3: Switzerland
Info. Tel. No.: 011-41-1-833-0786
Prep. Date: 09/05/91
Emerg. Tel. No.: 1(800)468-6942
Responsible Person: Alois K. Diethelm

SECTION II HAZARDOUS INGREDIENTS/IDENTITY/STANDARDS/CONTENT INFORMATION

Ingredient Listing: Trade Secret, Non Hazardous Water Based Paint Mixture
CAS No., OSHA PEL, ACGIH TLV, STEL, % COMP

This product is intended for professional use. While it is not intended for use by children, such use is possible. Successful art use may require adult supervision. Not intended to be used in spray applications. If so used, provide adequate ventilation and avoid breathing paint mist.

SECTION III PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A Deg. F (Cel)
Melting Point: N/A Deg. F (Cel)
Vapor Pressure: N/A
Evaporation Rate: N/A
Odor: Latex paint odor
Spec. Grav. (H2O=1): N/A
Vapor Density: N/A
Water Solubility: N/A
Appearance: Paints in various colors

SECTION IV FIRE and EXPLOSION HAZARD DATA

Flash Point: N/A Deg. F. (Cel)
Lower Flam. Limit: N/A Upper Flam. Limit: N/A
Exting. Medium: Water, foam, carbon dioxide or dry chemical.
Specialized Fire Fighting Proc.: None required for this material. However, when fighting any fire, wear positive pressure self-contained NIOSH approved breathing equipment.

Unusual Fire & Explosion Hazard: Sealed containers may rupture; Paint films may burn. This product presents no unusual fire or explosion hazards.

SECTION V REACTIVITY DATA

Stable (Unstable): Stable
Stable (yes/no): yes
Incompat. (Avoid): Avoid strong oxidizing agents
Haz. Decomp. (y/n): Not Likely to Haz. Polym. (yes/no) No
Cond. to Avoid: None Known
Conditions Strong oxidizing agents. to avoid

Confirm all information prior to use
Abbreviations: Not Applicable N/A.. Not Flammable N/F
Permissible Exposure Limit PEL
The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.
Ceiling Value C
Not Determined N/D
Not Listed N/L
ACGIH Threshold Limit Value TLV
(TLV Reg. TM, ACGIH)

Nov 23 2002 12:44PM HP LASERJET 3200

P. 12

Artist non-cadmium

MATERIAL SAFETY DATA SHEET
SHA Hazard Communication
Standard (29 CFR 1910.1200)

SIMILAR TO OSHA FORMS 20 AND 174
US Department of Labor
Printed on 9/18/91 at 12:28:42pm

Material Identity Lascaux Acrylic Artists Colors

SECTION VI HEALTH HAZARD DATA

Routes of Entry: Inhalation Vapors can be inhaled; not likely in toxic amounts.
Skin Not likely in toxic amounts Ingest. Liquids may be ingested.
Health Hazards None Known for the usual and ordinary professional uses of this product.
TP Carcinogen No IARC Carcinogen No OSEA Carcinogen No
Signs/Symptoms None Likely under normal professional use
Pre-Exposure
Medical Conditions None Known
First Aid
Inhalation: Remove to fresh air and support respiration. Eyes: carefully wash or rinse for 15 minutes. Contact a physician if irritation occurs or persists. Skin: Wash area with soap and water
Ingestion: Drink water or milk to dilute, contact a physician.

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Spill Contain Spill. Spill area will be slippery. Recover as much as possible for reuse. Spread commercial absorbant over remainder and place into sealed container for disposal.
Waste Disp Dispose as directed by all Federal, State and Local regulations. Most states prohibit disposal of liquids in landfills.
Precautions Wash thoroughly after handling product. Use under well ventilated conditions. Avoid contact with eyes and skin.
Other Precautions As with all chemical good industrial hygiene and proper work habits should be observed.

SECTION VIII CONTROL MEASURES

Resp. Protect. Not normally needed
Local Exhaust May be used to prevent routine inhalation.
Mech. Local. Exh. Use with normal room ventilation
Mech. Exhaust None Specifically required
Other Mech. Exhaust None
Protect. Gloves
Gloves are recommended when handling large amounts. May be used if desired during close work.
Eye Protect. Artist's smock or other similar protective garment.
Protect. Clothing Do not spray or use with air brush systems. Good industrial hygiene and proper work habits should be observed at all times. Clean up work area after use. This product is intended for professional use only.
Work Practices

Confirm all information prior to use
Abbreviations: Not Applicable N/A -- Not Flammable N/F
Permissible Exposure Limit (PEL) N/A
Ceiling Value C
Not Determined N/D
Not Listed N/L
ACGIH Threshold Limit Value TLV
The data shown here is from sources published by the American Chemical Society and should be used as a guide only. For more information, contact the American Chemical Society.