

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29CFR 1910.1200. Standard must be consulted for specific requirements.

00714-2624 -3164 -5214 -5294
-6174 -7054 -9504

U. S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB NO. 1218-0072

IDENTITY (AS USED ON LABEL AND LIST) PRISM METALLICS 9917(80- NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, OR NO INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT

SECTION I

MANUFACTURER'S NAME PALMER PAINT PRODUCTS, INC	EMERGENCY TELEPHONE NUMBER 1-(248)-588-4500
ADDRESS (NUMBER, STREET, CITY, AND ZIP CODE) 1291 ROCHESTER RD. TROY, MI 48083	TELEPHONE NUMBER FOR INFORMATION 1-(248)-588-4500
	DATE PREPARED May-08
	SIGNATURE OF PREPARER (OPTIONAL)

SECTION II -- HAZARDOUS INGREDIENTS/ IDENTITY IN FORMATION

Hazardous Components (Specific chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
VINYL ACETATE ACRYLIC COPOLYMER			TRADE SECRET	
WATER			CAS 7732-18-5	
VINYL ACETATE ACRYLIC RESIN			TRADE SECRET	
PROPYLENE GLYCOL			CAS 57-55-6	
MINERAL CLAY			CAS 1302-78-9	



Conforms to
ASTM D 4236

"PRODUCTS BEARING THE AP APPROVED PRODUCT SEAL OF ACMI ARE CERTIFIED IN A PROGRAM OF TOXICOLOGICAL EVALUATION BY A MEDICAL EXPERT TO CONTAIN NO MATERIALS IN SUFFICIENT QUANTITIES TO BE TOXIC OR INJURIOUS TO HUMANS OR TO CAUSE ACUTE OR CHRONIC HEALTH PROBLEMS. THIS PROGRAM IS REVIEWED BY ACMI'S TOXICOLOGICAL ADVISORY BOARD. THESE PRODUCTS ARE CERTIFIED BY ACMI TO BE LABELED IN ACCORDANCE WITH THE CHRONIC HAZARD LABELING STANDARD, ASTM D-4236 AND FEDERAL LAW, P.L. 100-695. IN ADDITION, THERE IS NO PHYSICAL HAZARD AS DEFINED WITHIN 29 CFR PART 1910.1200(C)."

SECTION III --PHYSICAL/ CHEMICAL CHARACTERISTICS

BOILING POINT	200°F	SPECIFIC GRAVITY (H20=1)	1.15
VAPOR PRESSURE (mm Hg)	N/A	MELTING POINT	N/A
VAPOR DENSITY (AIR=1)	LIGHTER	EVAPORATION RATE (BUTYL ACETATE=1)	SLOWER
SOLUBILITY IN WATER	MISCIBLE		
APPEARANCE AND ODOR	MINIMAL ODOR		

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED) NON FLAMMABLE IN LIQUID STATE	FLAMMABLE LIMITS	N/A	LEL	N/A	UEL	N/A
EXTINGUISHED MEDIA USE WATER SPRAY, CO2 , FOAM ON DRY PRODUCT						

SPECIAL FIRE FIGHTING PROCEDURES PERSONS EXPOSED TO PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING APPARATUS

UNUSUAL FIRE AND EXPLOSION HAZARDS POSSIBLE PRESSURE BUILDUP FOR BULK PRODUCT CONTAINERS IF HEATED.
USE WATER SPRAY TO COOL CONTAINERS.

(REPRODUCE LOCALLY)

OSHA 174 SEPT 1985

IDENTITY PRISM METALLICS

SECTION V -- REACTIVITY DATA

STABILITY UNSTABLE CONDITIONS TO AVOID N/A

STABLE		YES		
INCOMPATIBILITY (MATERIALS TO AVOID)			NONE KNOWN	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS			INCOMPLETE COMBUSTION MAY YIELD CARBON MONOXIDE	
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID NONE KNOWN	
	WILL NOT OCCUR	X		
SECTION VI -- HEALTH HAZARD DATA				
ROUTE(S) OF ENTRY	INHALATION?	N/A	SKIN?	N/A
HEALTH HAZARDS (ACUTE AND CHRONIC)		NON-TOXIC WATER BASED ACRYLIC COLORS NO ACUTE OR CHRONIC		
HAZARDS ASSOCIATED WITH PRODUCT AS DEFINED BY 29 CFR 1910.1200... AND IN COMPLIANCE TO THE ASTM D-4236 LABELING REGULATIONS.				
CARCINOGENICITY:	NTP?	NO	IARC MONOGRAPHS?	NO
SIGNS AND SYMPTOMS OF EXPOSURE		NONE KNOWN		
MEDICAL CONDITIONS				
GENERALLY AGGRAVATED BY EXPOSURE		NONE KNOWN		
EMERGENCY AND FIRST AID PROCEDURES				
CONSULT A PHYSICIAN IF EYE OR SKIN IRRITATION SHOULD PERSIST AFTER IRRIGATING AREA WITH WATER.				
SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE				
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED				
WIPE UP WITH CLOTH OR INERT ABSORBENT MATERIAL.				
WASTE DISPOSAL METHOD				
USE NORMALLY ACCEPTED PROCEDURES FOR WASTE DISPOSAL WHICH MEET ALL FEDERAL, STATE, AND LOCAL REQUIREMENTS.				
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING				
DO NOT STORE IN AREAS WHERE TEMPERATURES EXCEED NORMAL ROOM TEMPERATURES.				
OTHER PRECAUTIONS				
NONE KNOWN				
SECTION VIII -- CONTROL MEASURES				
RESPIRATORY PROTECTION (SPECIFY TYPE)		NONE NEEDED		
VENTILATION	LOCAL EXHAUST	N/A		SPECIAL
	MECHANICAL (GENERAL)	RECOMMENDED		OTHER
PROTECTIVE GLOVES	SKIN CONTACT MAY BE IRRITATING		EYE PROTECTION	EYE CONTACT MAY BE IRRITATING
OTHER PROTECTIVE CLOTHING OR EQUIPMENT		NONE NEEDED		
WORK/ HYGIENIC PRACTICES		WASH HANDS WITH SOAP AND WATER BEFORE EATING.		