

Date of preparation: 19 JUN 1990 PRODUCT# ARTISTC ACRYLIC PAINT
 UPDATED- JANUARY 18, 1989

MSDS SAFETY DATA SHEET NFCA 1-72

01019-1087

For coatings, resins and related materials.

(Approved by U.S. Department of Labor (similar)-Form OSHA-20)

45105-06 ✓

SECTION I

NFCA/HMIS DATA

Health Hazard	0	0 Minimal Hazard
Flammability Hazard	0	1 Slight Hazard
Reactivity Hazard	0	2 Moderate Hazard
Max. Personal Protection	A	3 Serious Hazard
		4 Severe Hazard

Manufacturer's Name: CAL-WESTERN PAINTS
 Street Address: 11748 SLAUSON AVE., SANTA FE SPRING, CA 90670
 Emergency telephone #: (213) 723-6362
 Product Class: ACRYLIC EMULSION PAINT
 Manufacturer's Code Identification: 565
 Trade Name: VINYL ACRYLIC LATEX

COLOR NAME: BLOCKOUT WHITE

SECTION II-HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV	OSHA PEL	VAPOR
CAS#	BY WEIGHT	PPM	PPM	LEL PRESSURE-TEMP.

-NONE LISTED

SUSPECTED CANCER AGENT?: NO-This product's ingredients are not found on the following lists / Federal OSHA / NTP / IARC.

SECTION III-PHYSICAL DATA

Boiling Range: 212 degrees F	Vapor Density: Heavier than air
Evaporation Rate: Slower than ether	% Volatile by Volume: 59.80%
Weight per Gallon: 11.75 +/- .15	V.O.C. (grams/liter) (excluding water): LESS THAN 250

SECTION IV-FIRE & EXPLOSION HAZARD DATA

Dot Category: NON-COMBUSTIBLE (AQUEOUS SYSTEM)
 Flash Point: N/A

LEL: N/A
 UEL: N/A

Extinguishing Media: FOR RESIDUAL SOLIDS, USE WATER SPRAY.

Unusual Fire & Explosion Hazards: NONE.

Special Fire Fighting Procedures: NONE.

V-6607

Date of preparation: 19 Jun 1990 -PRODUCT# ARTISTIC-ACRYLICS- PAGE# 105

SECTION V - HEALTH HAZARD

Threshold Limit Value: SEE SECTION II

Effects of Overexposure:

ACUTE	SKIN ABSORPTION, INHALATION - NO EVIDENCE OF ADVERSE EFFECTS FROM AVAILABLE INFORMATION. SKIN CONTACT - MAY CAUSE TRANSIENT REDDENING OF SKIN. EYE CONTACT - DIRECT CONTACT WITH PRODUCT MAY RESULT IN EYE IRRITATION.
CHRONIC	INHALATION MAY CAUSE HEADACHES. SKIN AND EYE CONTACT MAY CAUSE IRRITATION.

Emergency & First Aid Procedures:

SKIN CONTACT - WASH WITH SOAP AND WATER.
INHALATION - NO EMERGENCY CARE ANTICIPATED.
EYE CONTACT - FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES.

SECTION VI - REACTIVITY DATA

Stability: STABLE

Conditions to Avoid: N/A

Incompatibility: N/A

Hazardous Decomposition Products: N/A

Hazardous Polymerization: WILL NOT OCCUR

Conditions to Avoid: N/A

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: CONTAIN & REMOVE WITH INERT ABSORBENT.

Waste Disposal Method: DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED.

Ventilation: GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE SATISFACTORY.

Protective Gloves: N/A

Eye Protection: N/A

Other Protection: N/A

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: SHOULD BE STORED AT ROOM

Date of preparation: 19 Jun 1990 -PRODUCT# ARTISTIC-ACRYLICS- PAGE# 104
TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING. KEEP CONTAINER
CLOSED. KEEP OUT OF REACH OF CHILDREN, UNLESS THE PRODUCT IS USED UNDER
SUPERVISION OF QUALIFIED PERSONNEL.

HYGIENIC PRACTICES - WASH HANDS BEFORE EATING OR USING THE WASHROOM.

NOTICE: the data and recommendations presented herein are based upon our
research and the research of others, and are believed to be accurate. No
guarantee of their accuracy is made, however, and the product discussed are
distributed without warranty, expressed or implied, and the person
receiving said product shall make his own determination of the suitability
thereof for his particular purpose.