

Recd. 3-27-03

01101 - all except codes below

**Material Safety Data Sheet for R&F Encaustics**  
**OSHA Hazard Communication Standard (29 CFR 1910.1200)**  
**Similar to OSHA Forms 20 and 174U S Department of Labor**  
**Printed Date 3/27/98 at 10:23:2**

CC97-231DNNEW97 FCLINE COL

**Manufacturer's Name and Location**

R&F Handmade Paints, Inc.  
 506 Broadway  
 Kingston, NY 12401  
 Contact - Richard Frumess, P resident  
 For Information - 1.800.206.8088  
 Emergency Telephone # - 1.800.206.8088 or phone your local Poison Control Center  
 Preparation Date - 1/14/98                      Rev.# 00

. 0089	- 4120	- 4820	- 6910
- 3090	- 4130	- 5180	- 7210
. 3100	- 4180	- 5370	- 7620
- 3210	- 4530	- 6580	- 7930
. 4090			

**CONFIRM ALL INFORMATION PRIOR TO USE**

**Label Statements for R&F Encaustics**

Acute Toxicity - no label required  
 Chronic Toxicity - no label required

**California Prop 65 Warning Statement**

**Warning! This product contains an ingredient known to the state of California to cause cancer**

**Certification Assurance**

Conforms to ASTM D-4236

**Children's Hazard Warning**

Keep Out of Reach of Children

**Abbreviations:**

- Not Applicable: n/a
- Not Flammable: n/f
- Not Known: n/k
- Repirable Fraction: r
- Permissible Exposure Limit: pel
- Ceiling Value: c
- Not Determined: n/d
- Not Listed: n/l
- ACGIH Threshold Limit Value: tlv

The data shown is taken from sources judged to be reliable. The user should judge both the accuracy and the suitability of this information for any intention or purpose. No other warranty is given.

TLV Reg. TM, ACGIH

V-1811

**Data For All Colors Except Cadmium & Cobalt:****Hazardous Ingredients/Identity/Standards/Content Information**

Ingredient Listing - wax/oil base medium  
 CAS No. - mixture  
 OSHA PEL - n/a  
 ACGIH TLV - n/a  
 STEL - n/a  
 % COMP - <95

Ingredient Listing - pigments/colorants  
 CAS No. - mixture  
 OSHA PEL - n/a  
 ACGIH TLV - n/a  
 STEL - n/a  
 % COMP - <50

The ingredients in the wax base medium are judged to be non-hazardous, in this form, and are regarded as trade secrets

**Physical/Chemical characteristics**

Boiling Point - >260 degrees C.  
 Melting Point - <110 degrees F.  
 Vapor Pressure - n/a  
 Evaporation Rate - n/a  
 Odor - odor of wax  
 Specific Gravity - 0.927-0.970  
 Vapor Density - n/a  
 Water Solubility - insoluble  
 Appearance - colored wax

**Fire and Explosion Hazard Data**

Flash Point - >240 degrees F.  
 Flash Point Method - open cup  
 Lower Flammability Limit - n/l  
 Upper Flammability Limit - n/l  
 Extinguishing Medium - foam, dry chemical and CO2  
 Specialized Fire/Fighting Procedure - none  
 Unusual Fire and Explosion Hazard - none

**Reactivity Data**

Stable - yes  
 Incompatibility - none  
 Conditions to Avoid - none  
 Hazardous Polym. - no  
 Hazardous Decomposition - yes

**Health Hazard Data**

Not intended for use by children. Keep out of reach of children.

**Routes of Entry**

Inhalation - yes  
 Skin - no  
 Ingestion - n/k

**Carcinogen**

NTP - n/l  
 IARC - n/l  
 OSHA - n/l

**Signs/Symptoms of Exposure - n/l**

Medical Conditions to Avoid - none  
 First Aid - normally not needed

**Precautions for Safe Handling and Use:**

Spill - if heated, allow to cool  
 Waste Disposal - dispose in an appropriate manner which complies with local regulations  
 Precautions - do not store near heat, keep cool  
 Other Precautions - none

**Control Measures**

Respiratory Protection - normally not needed  
 Local Exhaust - use local exhaust if pigment sticks are heated  
 Specific Local Exhaust - normally not needed  
 Mechanical Exhaust - provide more ventilation if necessary  
 Other Mechanical Exhaust - normally not needed  
 Protective Gloves - wear gloves or barrier cream to protect against contact  
 Eye Protection - normally not needed  
 Protective Clothing - normally not needed, suggest freshly laundered artist's smock  
 Work Practices - wash hands and face after use

Page 4