

01405 - 8506

## MATERIAL SAFETY DATA SHEET

1317  
01 00

Rec'd 10-12-05

## Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

## PRODUCT NUMBER

1317

## HMIS CODES

Health	2
Flammability	4
Reactivity	0

## PRODUCT NAME

KRYLON\* Sandable Primer, Ruddy Brown

## MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

KRYLON Products Group

Cleveland, OH 44115

## DATE OF PREPARATION

08-OCT-05

## EMERGENCY TELEPHONE NO.

(216) 566-2917

## INFORMATION TELEPHONE NO.

(800) 832-2541

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS		VAPOR PRESSURE	
% by WT	CAS No.	INGREDIENT	UNITS
14	74-98-6	Propane	
		ACGIH TLV	2500 ppm
		OSHA PEL	1000 ppm
6	106-97-8	Butane	
		ACGIH TLV	800 ppm
		OSHA PEL	800 ppm
4	64742-89-8	V. M. & P. Naphtha	
		ACGIH TLV	300 ppm
		OSHA PEL	300 ppm
		OSHA PEL	400 ppm STEL
19	108-88-3	Toluene	
		ACGIH TLV	50 ppm (Skin)
		OSHA PEL	100 ppm (Skin)
		OSHA PEL	150 ppm (Skin) STEL
2	78-83-1	2-Methyl-1-propanol	
		ACGIH TLV	50 ppm
		OSHA PEL	50 ppm
35	67-64-1	Acetone	
		ACGIH TLV	500 ppm
		ACGIH TLV	750 ppm STEL
		OSHA PEL	1000 ppm
7	14807-96-6	Talc	
		ACGIH TLV	2 mg/m3 as Resp. Dust
		OSHA PEL	2 mg/m3 as Resp. Dust
1	471-34-1	Calcium Carbonate	
		ACGIH TLV	10 mg/m3 as Dust
		OSHA PEL	15 mg/m3 Total Dust
		OSHA PEL	5 mg/m3 Respirable Fraction

Continued on page 2

1317

page 2

---



---

 Section 3 -- HAZARDS IDENTIFICATION
 

---

## ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

## EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

## SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

## MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

## CANCER INFORMATION

 For complete discussion of toxicology data refer to Section 11.
 

---

 Section 4 -- FIRST AID MEASURES
 

---

 EYES: Flush eyes with large amounts of water for 15 minutes.  
 Get medical attention.

 SKIN: Wash affected area thoroughly with soap and water.  
 Remove contaminated clothing and launder before re-use.

 INHALATION: If affected, remove from exposure. Restore breathing.  
 Keep warm and quiet.

 INGESTION: Do not induce vomiting.  
 Get medical attention immediately.
 

---

 Section 5 -- FIRE FIGHTING MEASURES
 

---

## FLASH POINT

Propellant &lt; 0 F

LEL

0.9

UEL

12.8

## EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

## UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

 Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.
 

---

Continued on page 3

1317

page 3

---

---

**Section 6 -- ACCIDENTAL RELEASE MEASURES**

---

---

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.  
Remove with inert absorbent.

---

---

**Section 7 -- HANDLING AND STORAGE**

---

---

**STORAGE CATEGORY**

Not Available

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

---

---

**Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION**

---

---

**PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

**VENTILATION**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

Continued on page 4

1317

page 4

**PROTECTIVE GLOVES**

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

**EYE PROTECTION**

Wear safety spectacles with unperforated sideshields.

**OTHER PRECAUTIONS**

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

---

**Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES**


---

PRODUCT WEIGHT	6.76 lb/gal	809 g/l
SPECIFIC GRAVITY	0.81	
BOILING POINT	<0 - 325 F	<-18 - 162 C
MELTING POINT	Not Available	
VOLATILE VOLUME	91 %	
EVAPORATION RATE	Faster than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	N.A.	
pH	7.0	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)		
Volatile Weight	45.36 %	Less Water and Federally Exempt Solvents

---

**Section 10 -- STABILITY AND REACTIVITY**


---

STABILITY -- Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

---

**Section 11 -- TOXICOLOGICAL INFORMATION**


---

**CHRONIC HEALTH HAZARDS**

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**TOXICOLOGY DATA**

Continued on page 5

1317

page 5

CAS No.	Ingredient Name				
74-98-6	Propane	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
106-97-8	Butane	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
64742-89-8	V. M. & P. Naphtha	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
108-88-3	Toluene	LC50	RAT	4HR	4000 ppm
		LD50	RAT		5000 mg/kg
78-83-1	2-Methyl-1-propanol	LC50	RAT	4HR	Not Available
		LD50	RAT		2460 mg/kg
67-64-1	Acetone	LC50	RAT	4HR	Not Available
		LD50	RAT		5800 mg/kg
14807-96-6	Talc	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
471-34-1	Calcium Carbonate	LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

---

Section 12 -- ECOLOGICAL INFORMATION

---

ECOTOXICOLOGICAL INFORMATION  
No data available.

---

Section 13 -- DISPOSAL CONSIDERATIONS

---

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

---

Section 14 -- TRANSPORT INFORMATION

---

No data available.

---

Section 15 -- REGULATORY INFORMATION

---

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

Continued on page 6

1317

page 6

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
108-88-3	Toluene	19	

## CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

## Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.