



V# 4475

01508-1004

Material Safety Data Sheet

For Health Emergencies: CALL A POISON CONTROL CENTER
 For Transportation Emergencies ONLY: Call Chem-Tel
 USA, Canada, Puerto Rico, US Virgin Islands: Call 800-255-3924
 Outside North America: Call Collect 813-248-0585

Date Prepared
 Rev: 17 May 2007
 Replaces: 29 Mar 2004

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

1.1 PRODUCT NAME: Weber® Rapidry™ Quick Drying Oil Medium

1.2 ITEM NUMBER AND SIZES: 1711 - 118ml

1.3 COMPANY IDENTIFICATION:

Martin/F. Weber Co.
 2727 Southampton Road • Philadelphia, PA 19154 USA
 Phone: 215-677-5600 • Fax: 215-677-3336
 Email: info@weberart.com • Web: www.weberart.com

SECTION 2 – COMPOSITION INFORMATION

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
Aliphatic Hydrocarbon	8052-41-3	70
2-2' Bipyridyl	872-50-4	<1

SECTION 3 – HAZARDS IDENTIFICATION**3.1 EMERGENCY OVERVIEW****Appearance:** Clear brown liquid**Physical State:** Liquid**Odor:** Mild petroleum solvent odor**Hazards of Product:** DANGER: Combustible. Harmful or Fatal if Swallowed. Vapor Harmful**3.2 POTENTIAL HEALTH EFFECTS****EFFECTS OF SINGLE ACUTE OVEREXPOSURE:**

Harmful or fatal if swallowed. Vapor Harmful.

CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE:

Vapor Harmful.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: n/a**3.3 POTENTIAL ENVIRONMENTAL EFFECTS:** n/a**SECTION 4 – FIRST AID PROCEDURES****4.1 INHALATION:** Move to fresh air. Get prompt medical attention.

4.2 EYE CONTACT: Wash eyes with tap water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.

4.3 SKIN CONTACT: Wash affected area with soap and water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.

4.4 SWALLOWING: If swallowed, do not induce vomiting. Get immediate medical attention.

4.2 NOTES TO PHYSICIAN: n/a

SECTION 5 - FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

Identification Number:	UN 1263
Flash Point – Closed Cup:	118°F (48°C)
Flash Point – Open Cup:	n/a
Auto-Ignition Temperature:	n/a
Flammable Limits in Air:	n/a

5.2 EXTINGUISHING MEDIA Foam, CO₂, Dry Chemical (Class B) or Halon®

5.3 EXTINGUISHING MEDIA TO AVOID Water

5.4 SPECIAL FIRE FIGHTING PROCEDURES n/a

5.5 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS As with any fire situation, full face, self contained breathing apparatus and appropriate protective clothing should be worn.

5.6 UNUSUAL FIRE AND EXPLOSION HAZARDS n/a

5.7 HAZARDOUS COMBUSTION PRODUCTS Under fire conditions, this product may release CO, CO₂, and other decomposition products of undetermined hazard.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep sources of ignition away. Small quantities may be cleaned up with rags or paper towels and transferred to airtight containers for disposal. Rags or paper towels soaked with this material should be placed in approved waste cans and / or soaked with water, for disposal in accordance with local state and federal regulations.

SECTION 7 – HANDLING AND STORAGE

7.1 GENERAL HANDLING: Avoid ingestion. Avoid breathing vapors. Use exhaust fan to remove vapors and assure adequate ventilation. Do not transfer contents to unlabeled containers. **KEEP OUT OF THE REACH OF CHILDREN.** Keep from sources of ignition, oxidizing materials, heat and flame. **KEEP AWAY FROM OPEN FLAMES. NO SMOKING** in areas of use or storage.

7.2 STORAGE: Keep from sources of ignition, oxidizing materials, heat and flame. Keep containers closed when not in use.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 EXPOSURE LIMITS:	100 PPM ACGIH TLV
8.2 PERSONAL PROTECTION:	
Respiratory Protection:	Not required if adequate cross ventilation is maintained.
Ventilation:	Use local exhaust fan to assure adequate cross ventilation in working area and to remove fumes. Avoid vapor buildup.
Eye Protection:	Use OSHA approved chemical splash goggles with side shields
Protective Gloves:	Neoprene or rubber – impervious gloves
Other Protective Equipment:	Body protection suitable for the work environment
8.3 ENGINEERING CONTROLS:	n/a

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance:	Clear brown liquid
pH:	n/a
Solubility in Water (by weight):	Insoluble
Odor:	Mild petroleum solvent odor
Flash Point – Closed Cup:	118°F (48°C)
Flash Point – Open Cup:	n/a
Percent Volatiles:	70%
Boiling Point (760mm Hg):	n/a
Freezing Point:	n/a
Specific Gravity (H₂O = 1):	0.80
Vapor Pressure at 20°C:	4mg Hg
Vapor Density (air = 1):	>1
Evaporation Rate (Butyl Acetate = 1):	<1
Melting Point:	n/a

Section 10 – STABILITY AND REACTIVITY

10.1 STABILITY / INSTABILITY	Stable under ordinary conditions of use and storage
Conditions to Avoid	Keep from heat, open flame and sources of ignition
Incompatible Materials	Strong oxidizing agents, acids or acidic materials
10.2 HAZARDOUS POLYMERIZATION	Will not occur
10.3 INHIBITORS / STABILIZERS	n/a

SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Harmful or fatal if swallowed. Vapor Harmful.

CHRONIC TOXICITY: Vapor Harmful.

SECTION 12 – ECOLOGICAL INFORMATION

12.1 ENVIRONMENTAL FATE	n/a
12.2 ECOTOXICITY	n/a
12.3 FURTHER INFORMATION	n/a

SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 WASTE DISPOSAL METHOD	Dispose of in accordance with local, state and federal regulations
-----------------------------------	--

