

**01616-all codes except:****-1009 -3105 -3108 -3565****-3568 -4125 -4128 -4185****-4188 -4355 -4358 -4535 -4538**

CHROMA AUSTRALIA PTY LTD ACN 001 594 609  
 17 MUNDOWI RD  
 MT KURING-GAI NSW 2080, Australia  
 TEL: (02) 9457 9922 FAX: (02) 9457 8082  
 EMERGENCY TEL: AS ABOVE, or Poisons Information Centre

PAGE 1 of 2

DATE of ISSUE: 24 NOVEMBER 2005

**Material Safety Data Sheet**  
**Not Classified as Hazardous According to the Criteria of Worksafe Australia**

**IDENTIFICATION**

Product name: ATELIER INTERACTIVE ARTISTS ACRYLICS U.N. No: N/A  
 Other names: ---- Hazchem: N/A  
 Dangerous Goods Class & Sub Risk: N/A  
 Poisons Schedule: N/A  
 Manufacturer's Product Code: VARIOUS  
 Use: ARTISTS IMPASTO ACRYLIC PAINT  
 Physical Description/Properties  
 Appearance: THICK PASTE various colours Flash Point (°C): N/A  
 Boiling Point/Melting Point (°C) N/A Flammability limits (%): N/A  
 Vapour Pressure (pascals or mm of Hg at 25°C)  
 Specific Gravity Approx no greater than 1g/ml Solubility in Water (g/L): soluble  
 Other properties None

**Ingredients**

Chemical entity	CAS No.	Proportion
ACRYLIC EMULSIONS	NON HAZ	COMMERCIAL IN CONFIDENCE
PRESERVATIVE	149-30-4/2634-33-50.15%	
ALKALINE STABILISER	124-68-24	<1%
PIGMENT, varied	----	COMMERCIAL IN CONFIDENCE
THICKENERS	NON HAZ	<20%
WATER	7732-18-5	<10%

**HEALTH HAZARD INFORMATION****HEALTH EFFECTS:**

**Acute:** Swallowed NONE ALLOCATED  
 Eye DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION  
 Skin PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION  
 Inhaled INHALATION OF VAPOUR MAY CAUSE IRRITATION  
 Chronic NONE ALLOCATED

**FIRST AID:**

Swallowed IF SWALLOWED GIVE TWO GLASSES of WATER TO DRINK  
 Eye FLUSH EYES WITH A LARGE AMOUNT OF WATER  
 Skin WASH AFFECTED AREAS THOROUGHLY  
 Inhaled MOVE SUBJECT TO FRESH AIR

**ADVICE TO DOCTOR**

THIS PRODUCT CARRIES THE A.P. NON-TOXIC SEAL AND IS CERTIFIED BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE (ACMI), BOSTON Ma 02110, USA

<b>PRECAUTIONS FOR USE</b>
<p><b>EXPOSURE STANDARDS</b></p> <p>NONE</p> <p><b>ENGINEERING CONTROLS</b></p> <p>USE IN WELL VENTILATED AREAS</p> <p><b>PERSONAL PROTECTION</b></p> <p>NONE REQUIRED IF USED IN A WELL VENTILATED AREA</p> <p><b>FLAMMABILITY</b></p> <p>NOT APPLICABLE</p>
<b>SAFE HANDLING INFORMATION</b>
<p><b>STORAGE &amp; TRANSPORT</b></p> <p>KEEP FROM FREEZING. RECOMMENDED STORAGE CONDITIONS ARE BETWEEN 1° C AND 50 °C.</p> <p><b>SPILLS &amp; DISPOSAL</b></p> <p>FOR MINOR SPILLS, MOP UP WITH RAGS &amp; DISPOSE OF. FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH SAND AND TRANSFER TO CONTAINERS FOR DISPOSAL. CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL ADVICE.</p> <p><b>FIRE/EXPLOSION HAZARD</b></p> <p>NONE</p>
<b>OTHER INFORMATION</b>
<p><b>CONTACT POINT</b></p> <p>MT KURING-GAI AUSTRALIA</p>
<p><b>DATE OF ISSUE: 24 NOVEMBER 2005</b></p>