

01731-XXXX**MATERIAL SAFETY DATA SHEET**

4/15/2009

MANUFACTURER OR DISTRIBUTOR: **Holbein, Osaka**
P.O. Box 555
175 Commerce Street
Williston, Vermont 05495

INFORMATION TELEPHONE NUMBER: **800-682-6686**
 EMERGENCY TELEPHONE NUMBER: **802-862-4573**

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: **HOLBEIN DUO OIL** PRODUCT NUMBER: **DMV**
MEDIUMS & VARNISHES

PRODUCT SIZES: **50, 55, 200 ML** BRAND NAME: **HOLBEIN DUO OIL MEDIUMS &**
VARNISHES

PRODUCT CLASS: **ALKYD PAINTING**
MEDIUMS (LIQUID)

SECTION II - HAZARDOUS INGREDIENTS

| Ingredient | CAS # | PEL/TLV (MG/M#) | Max % Weight | NTP | IARC |
|------------------------------------|--------------|----------------------------|-------------------------|------------|-------------|
| ALKYLOXY POLY ETHYLENE OXY ETHANOL | 68131-40-8 | N/A | 4.00000 | N | N |
| PETROLEUM DISTILLATES | N/A | 525.00 | 55.00000 | N | N |

SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT: N/A MELTING POINT: N/A
 VAPOR PRESSURE: N/A
 SPECIFIC VAPOR DENSITY (AIR=1): N/A SPECIFIC GRAVITY: N/A
 SOLUBILITY IN WATER: N/A REACTIVITY IN WATER: NON-REACTIVE
 APPEARANCE AND ODOR:

SECTION IV - FIRE AND EXPLOSION INFORMATION

FLASH POINT (METHOD): N/A AUTOIGNITION TEMPERATURE: N/A
 EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
 EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
 FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS: RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. Rags or waste paper soaked with this material can burn spontaneously. Store in sealed metal container. Dispose of under water or by hanging out to dry. **COMBUSTIBLE.**

SECTION V - PHYSICAL HAZARDS/REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: NONE
 STABILITY: STABLE CONDITIONS TO AVOID: NONE

COMPANY: Holbein, Osaka
PRODUCT: DMV
BRAND NAME: HOLBEIN DUO OIL MEDIUMS & VARNISHES

4/15/2009

INCOMPATIBILITY (MATERIALS TO AVOID): NONE
HAZARDOUS DECOMPOSITION PRODUCTS: NONE

SECTION VI - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL: SEE SECTION II FOR COMPONENT PEL/TLVs
PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, EYE, SKIN

EFFECTS AND SYMPTOMS OF ACUTE EXPOSURE: SKIN IRRITANT. EYE IRRITANT. EXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. Exposure may result in nausea, headache, confusion or instability. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTACT MAY RESULT IN IRRITATION OF THE SKIN. CONTACT MAY RESULT IN REDNESS OR PAIN OF THE EYES.

EFFECTS AND SYMPTOMS OF CHRONIC EXPOSURE: NONE EXPECTED

CARCINOGEN LISTING: NTP: NO IARC: NOOSHA: NO

SEE SECTION II FOR COMPONENTS AFFECTED

MEDICAL CONDITIONS USUALLY AGGRAVATED BY OVER EXPOSURE TO THIS PRODUCT: NONE

FIRST AID MEASURES: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If swallowed, do not induce vomiting. Call a physician or poison control center immediately. If inhalation symptoms occur, move to fresh air. If skin contact occurs, wash with soap and water for 5 minutes. If symptoms persist, see a physician.

SECTION VII - SPILL OR LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Do not store or use near heat or flame.
KEEP OUT OF REACH OF CHILDREN.

FOR HOME USE, CHILD-PROOF PACKAGING REQUIRED IN CONFORMANCE WITH 16CFR1700.15 a), b), and c) and meet the child test protocol requirements of one of CSA-Z76.1, ISO 8317 or 16 CFR 1700.20 or a standard that is at least equivalent. Packaging is required for products containing 10% or more xylene, toluene, or petroleum hydrocarbons if the viscosity of the product is <100 SUS at 100o F, that contain 10% or more turpentine or ethylene glycol, that contain 10% or more sodium or potassium hydroxide in the powdered form or 2% or more in the liquid form when unneutralized, that contain 4% or more methanol, or that contain 10% or more sulfuric acid.

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: NO SPECIAL SPILL PROCEDURES REQUIRED.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION VIII - PROTECTIVE EQUIPMENT/CONTROL MEASURES

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use NIOSH-certified respirator with an organic vapor cartridge. Use only with adequate ventilation.

COMPANY: Holbein, Osaka
 PRODUCT: DMV
 BRAND NAME: HOLBEIN DUO OIL MEDIUMS & VARNISHES

4/15/2009

OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): Immediately after use, place soiled material in a sealed water-filled metal container. When using wear impermeable protective gloves.

WORK/HYGIENE PRACTICES: Avoid prolonged contact with skin. Avoid ingestion. Wash hands immediately after use. Keep away from eyes.

SECTION IX - ADDITIONAL INFORMATION AND WARNINGS

THIS INFORMATION SHEET IS FOR CONSUMER USE ONLY.

ADDITIONAL INFORMATION AND WARNINGS: NONE REQUIRED

SECTION X - COLOR INFORMATION

THIS MSDS APPLIES TO THE FOLLOWING COLORS WHICH ARE ASSOCIATED WITH HAZARDOUS AND/OR NON-HAZARDOUS INGREDIENTS

| <u>Product Color</u> | <u>Hazardous Ingredient</u> |
|---------------------------------|------------------------------------|
| DO522 STAND LINSEED OIL | (none) |
| DO529 QUICK DRYING LIQUID | (none) |
| DU466 QUICK DRYING MEDIUM GLOSS | (none) |
| DU467 QUICK DRYING MEDIUM MAT | (none) |
| DUO BRUSH CLEANER | ALKYLOXY POLY ETHYLENE OXY ETHANOL |
| DUO LINSEED OIL | (none) |
| DUO PAINTING OIL MEDIUM | PETROLEUM DISTILLATES |

COMPANY: Holbein, Osaka
PRODUCT: DMV
BRAND NAME: HOLBEIN DUO OIL MEDIUMS & VARNISHES

4/15/2009

Woodhall Stopford, MD, MSPH

4/15/2009