

02007-1065

CHROMA AUSTRALIA PTY LTD ACN 001 594 609 17 MUNDOWI RD MT KURING-GAI NSW 2080, Australia TEL: (02) 9457 9922 FAX: (02) 9457 8082 EMERGENCY TEL: AS ABOVE. or POISONS INFORMATION CENTRE		PAGE 1 of 2 DATE of ISSUE: 1 SEPTEMBER 2006
Material Safety Data Sheet Not Classified as Hazardous According to the Criteria of Worksafe Australia		
IDENTIFICATION		
Product name: Atelier Satin Painting Medium & Varnish Other names: ----		U.N. No: <i>N/A</i> Hazardchem: <i>N/A</i> Dangerous Goods Class & Sub Risk: <i>N/A</i> Poisons Schedule: <i>N/A</i>
Manufacturer's Product Code: AT72600 Use: Satin water based varnish and medium for artists' acrylic paints		
Physical Description/Properties		
Appearance: Milky Liquid Boiling Point/Melting Point (°C) <i>N/A</i> Vapour Pressure (pascals or mm of Hg at 25°C) <i>N/A</i> Specific Gravity APPROX 1 g/ml Other properties		Flash Point (°C): <i>> N/A</i> Flammability limits (%): <i>N/A</i> Solubility in Water (g/L): Soluble
Ingredients		
Chemical entity	CAS No.	Proportion
ACRYLIC EMULSION	NON HAZARDOUS	COMMERCIAL IN CONFIDENCE
AMMONIA	7-664-44-7	<2%
PRESERVATIVE	149-30-4/2634-33-5	0.2%
WATER	7732-15-5	COMMERCIAL IN CONFIDENCE
THICKENERS	NON HAZARDOUS	5%
HEALTH HAZARD INFORMATION		
HEALTH EFFECTS:		
Acute:	Swallowed NONE ALLOCATED	
	Eye DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION	
	Skin PROLONGED OR REPEATED CONTACT MAY CAUSE SLIGHT SKIN IRRITATION	
	Inhaled INHALATION OF VAPOUR MAY CAUSE IRRITATION	
	Chronic NONE ALLOCATED	
FIRST AID:		
	Swallowed IF SWALLOWED GIVE TWO GLASSES OF WATER TO DRINK	
	Eye FLUSH EYES WITH A LARGE AMOUNT OF WATER	
	Skin WASH AFFECTED SKIN AREAS THOROUGHLY	
	Inhaled MOVE SUBJECT TO FRESH AIR	
ADVICE TO DOCTOR:	THIS PRODUCT CARRIES THE C.P. NON-TOXIC SEAL AND IS CERTIFIED BY A TOXICOLOGIST IN ASSOCIATION WITH THE ART & CRAFT MATERIALS INSTITUTE, BOSTON, MA 02110 USA.	

ATELIER SATIN PAINTING MEDIUM & VARNISH

Page 2 of 2

PRECAUTIONS FOR USE**EXPOSURE STANDARDS**

NONE

ENGINEERING CONTROLS

USE IN WELL VENTILATED AREAS

PERSONAL PROTECTION

NONE REQUIRED IF USED IN A WELL VENTILATED AREA

FLAMMABILITY

N/A

SAFE HANDLING INFORMATION**STORAGE & TRANSPORT**

KEEP FROM FREEZING. RECOMMENED STORAGE CONDITIONS ARE BETWEEN 1°C AND 50°C.

SPILLS & DISPOSAL

FOR LARGER QUANTITIES, CONTAIN ANY SPILLS WITH INERT MATERIALS, (SAND, SAWDUST ETC) AND TRANSFER CONTAINERS FOR DISPOSAL. CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL METHODS. SOAK UP SMALLER SPILLS WITH A RAG AND DISPOSE OF CAREFULLY.

FIRE/EXPLOSION HAZARD

NONE

OTHER INFORMATION**CONTACT POINT:**

MT KURING-GAI N.S.W.

DATE OF ISSUE: 1 SEPTEMBER 2006