

MATERIAL SAFETY DATA SHEET (G5)

02012-1005
-1006
-1015
-1016

Golden Artist Colors, Inc.
Bell Road
New Berlin, NY 13411
Prepared by: Ben Gavett

Date Revised: 12/18/07
Phone: (607)847-6154

SECTION I - PRODUCT IDENTIFICATION

PRODUCT	HAZARDOUS COMPONENTS (Sec. II)
0037460 Gel Topcoat w/UVLS	1,5
0037470 Gel Topcoat w/UVLS (Semi-Gloss)	1,3,5
0077100 Polymer Varnish Gloss (w/UVLS)	1,5
0077150 Polymer Varnish Satin.(w/UVLS)	1,3,5
0077200 Polymer Varnish Matte (w/UVLS)	1,3,5
9037500 Stop-Out Varnish	1,12

HMIS ratings:

Health - 1
Flammability - 0
Reactivity - 0
Protective Equipment- X

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CODE	HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PERMISSIBLE EXPOSURE LIMITS		
			TWA	STEL	CEILING
1	Ammonia	7664-41-7	-	35 ppm	-
3	Amorphous Silica	68855-54-9	6 mg/M ³	-	-
5	Benzotriazolyl-OH-				
12	Butylphenyl Propionate Carbon Black	04810-42-2 1333-86-4	NE 3.5 mg/M ³	-	-

TWA = Time Weighted Average (ave. airborne exposure in 8 hr work shift of a 40 hr work week)

STEL = Short Term Exposure Limit (15 minute time weighted average exposure)

CEILING = exposure not to be exceeded during any part of the work day

ppm = parts of vapor or gas per million parts of contaminated air by volume

mg/M³ = approximate milligrams of substance per cubic meter of air

NE = None Established

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: >100°C/212°F

SPECIFIC GRAVITY (H20=1): 1.0-1.1

VAPOR DENSITY: Heavier than air

EVAPORATION RATE: Slower than ether

SOLUBILITY IN WATER: Dilutable

APPEARANCE AND ODOR: viscous liquid or gel, slightly sweet amine odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A

UPPER: N/A

EXTINGUISHING MEDIA: Carbon dioxide, water spray, foam or dry chemical

SPECIAL FIREFIGHTING PROCEDURES: Use self-contained breathing apparatus and full protective clothing.

MATERIAL SAFETY DATA SHEET (G5)

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material can splatter above 100°C/212°F. Dried film can burn, yielding toxic decomposition and combustion products.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY AND CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Thermal decomposition may yield oxides of carbon, monomer fumes and oxides of nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: None expected under normal conditions of use. Irritation of the nose, throat and lungs is associated with excessive exposure to ammonia. Overexposure to dusts and mists from sanding and spraying may be irritating to the respiratory tract. Prolonged exposure to excessive concentrations of silica dust may cause chronic pulmonary disease.

EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Prolonged or repeated contact may be irritating to the eyes.

SKIN CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Prolonged or repeated contact may be irritating to skin. The Benzotriazolyl compound may cause allergic reactions.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: May cause irritation to gastrointestinal system.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Pre-existing skin, eye, or respiratory conditions may be aggravated by exposure.

OTHER: CARBON BLACK- IARC classification as Group 2B, possibly carcinogenic to humans **WARNING:** This product contains a chemical known to the State of California to cause cancer.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Flush with water for 15 minutes. SEE DOCTOR if symptoms persist.

SKIN CONTACT: Wash with soap and water. SEE DOCTOR if skin irritation occurs.

INHALATION: Remove subject to fresh air. SEE DOCTOR if symptoms occur.

INGESTION: SEE DOCTOR if there are symptoms of exposure.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Floors may be slippery, care should be exercised to avoid falls. Dike and contain spill with inert material (e.g., sand, earth). Transfer material to containers for recovery or disposal. Keep solid diking material in separate containers for disposal.

WASTE DISPOSAL METHOD: Dispose as per local, state or EPA regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid extremes of temperature.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: None required under normal use. When sanding or spraying, use a NIOSH/MSHA certified dust and mist respirator.

VENTILATION: None required under normal use. For continuous use or when sanding or spraying, adequate ventilation is recommended.

PROTECTIVE GLOVES: Wear impermeable protective gloves.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wear protective clothing to avoid skin contact.

WORK/HYGIENIC PRACTICES: All Golden products should be used in accordance with safe handling practices, including: do not eat, drink or smoke when working with materials, avoid excessive skin contact, wash after working with materials, keep all professional materials out of reach of children.

SECTION IX - ADDITIONAL PRECAUTIONS AND INFORMATION**DISCLAIMER**

While Golden Artist Colors Inc. believes the data set forth herein is accurate as of the date hereof, Golden Artist Colors Inc. makes no warranty with respect to the accuracy of this data, and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.