


5-10-04V

* Jacquard Lumiere Paint

02953-XXXX
02900-XXXX

Rupert, Gibbon & Spider, Inc.
P.O. Box 425
Healdsburg, CA. 95448
800-442-0455

Date Issued: 9/22/1998



Material Safety Data Sheet

Section 1 General Information

Product Name (Number): Lumiere/Neopaque Fabric Paints
Chemical Family: Aqueous acrylic emulsion
D.O.T. Hazard Class: Non-regulated

Section 2 Compositional Information:

Ingredients	CAS #	% By Weight	OSHA TWA	ACGIH-TLV
Formaldehyde	50-00-0	.012 to .018	1.0	1C ppm
Acrylic Polymers	_____	25 - 30	NE	NE
Residual Monomers	_____	<0.1	NR	NR

V-1895

Section 3 Physical Data:

Published or Estimated Values

Boiling Point Deg. F.: 100C/212F Water (760 mm Hg)	Specific Gravity: 1 - 1.5 (H2O=1) (@ 77 deg. F)
Vapor Pressure: 17 20C/68F (mm Hg at 20 deg.C)	% Volatile By Weight: 52 - 56
Vapor Density (Air=1): <1 Water	Evaporation Rate (BUAC=1): <1 H2O
Solubility in Water: Dilutable	pH: 4 - 7

Appearance and Odor: Colored liquids with mild, pleasant odor

Section 4 Fire and Explosion Hazard Data:

Estimated Flammable Limits (% by Volume in Air) LEL: NA UEL: NA
Flash Point (Deg. F.): Non-Combustible
Extinguishing Media: NA

Special Fire Fighting Procedures: Material can splatter above 100C/212F. Polymer

Section 5A Health Hazard Data (Symptoms and Effects of Overexposure):

Inhalation: Vapor or spray mist can cause headache, nausea, and nose irritation. Heat setting should only be done with good ventilation. do not breathe resulting fumes.

Ingestion: Do not ingest.

Skin: Moderately irritating to skin.

Eyes: Moderately irritating to eyes.

Listed Carcinogens: Formaldehyde and trace amounts of acrylic monomers. Listed hazard values refer only to Formaldehyde in it's gaseous form. These liquid paints contain the *dissolved* form.

Section 5B Health Hazard Data (Emergency and First Aid Procedures):

Inhalation: Move subject to fresh air.

Ingestion: Give 2 glasses of water to drink. Consult a Physician. Never give anything by mouth to an unconscious person.

Skin Contact: Wash affected skin areas with soap and water. See a Physician if irritation persists.

Eye Contact: Flush eyes with a large amount of water for at least 15 minutes. See a Physician if irritation persists.

Section 6 Reactivity Data:

Stable: X **Unstable:** **Conditions to Avoid:**

Incompatibility (Materials to Avoid): NA

Hazardous Decomposition Products: NA

Hazardous Polymerization: **Will Occur:** **Will Not Occur:** X

Conditions to Avoid: NA

Section 7 Spill or Leak Procedures:**Steps to be taken in case material is released or spilled:**

Keep spectators away. Floor may be slippery; use care to avoid falling. dike and contain spill with inert material (e.g. sand, earth, absorbents). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep large spills and cleaning runoffs out of municipal sewers and open bodies of water. Keep spill area well ventilated.

