

V3406

02971-9013

SAFETY DATA SHEET (EC REGULATION No 1907/2006)
Version: N°1 (14/05/2009)
Name: Vitrail solvant : or / gold - 050038

Date: 14/05/2009 Page 1/7
Revision: N°2 (14/05/2009)
Company: PEBEO INDUSTRIES

SAFETY DATA SHEET

1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of the substance or preparation:

Name: Vitrail solvant : or / gold.
Product code: 050038.

Company/undertaking identification:

Registered company name: PEBEO INDUSTRIES.
Address: 305 AVENUE DU PIC DE BERTAGNE - BP106 - 13881.GEMENOS CEDEX.FRANCE.
Telephone: 33 (0) 4.42.32.08.08. Fax: 33 (0) 4.42.32.01.70.
cedecyne@pebeo.com
www.pebeo.com

Emergency telephone: 33 (0) 1.45.42.59.59.

Association/Organisation: INRS / ORFILA <http://www.centres-antipoison.net>.

Use of the substance/preparation:

Paint & Varnish

2 - HAZARDS IDENTIFICATION

This product is classed: Flammable.
May produce an allergic reaction.

Preparation classification:

Flammable

R 10

Flammable.

Other data:

Packaging < 125 ml.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 3: see section 16.

Hazardous substances present on their own:

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

No known substance in this category present.

Substances present at a concentration below the minimum danger threshold:

INDEX	CAS	EC	Name	Symb.	R:	%
	68551-41-7	271-376-3	ACIDES GRAS RAMIFIES EN C6-19 SELS DE CALCIUM SUPERBASQUES	Xi	36/38	0 <= x % < 2.5

Other substances with occupational exposure limits:

No known substance in this category present.

Other components:

INDEX	CAS	EC	Name	Symb.	R:	%
649-327-00-6	64742-48-9	265-150-3	NAPHITHA (PETROLEUM), HYDROTREATED HEAVY	Xn	65	25 <= x % < 50

May produce an allergic reaction:

INDEX	CAS	EC	Name	Symb.	R:	%
616-014-00-0	96-29-7	202-496-6	2-BUTANONE OXIME	Xn	40.C3 41 43 21	0 <= x % < 2.5

SAFETY DATA SHEET (EC REGULATION No 1907/2006)
Version: N°1 (14/05/2009)
Name: Vitrail solvant ; or / gold - 050038

Date: 14/05/2009 Page 2/7
Revision: N°2 (14/05/2009)
Company: PEBEO INDUSTRIES

4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation:

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

Suitable extinguishing media:

Carbon dioxide, chemical powders, foams, and other extinguishing gases.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing media which must not be used for safety reasons:

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special protective equipment for fire-fighters:

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions:

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.

Avoid inhaling the vapors.

Consult the safety measures listed under headings 7 and 8.

Environmental precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Methods for cleaning up:

Clean preferably with a detergent, do not use solvents.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

Handling:

Handle in well-ventilated areas.

The vapors are denser than air. They can spread along the ground and form explosive mixtures with air

SAFETY DATA SHEET (EC REGULATION No 1907/2006)
 Version: N°1 (14/05/2009)
 Name: Vitrail solvant : or / gold - 050038

Date: 14/05/2009 Page 3/7
 Revision: N°2 (14/05/2009)
 Company: PEBEO INDUSTRIES

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Fire prevention:

Prevent the accumulation of electrostatic charges with connections to earth

The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal safety, see §8.

Observe precautions stated on label and also industrial safety regulations

Packages which have been opened must be reclosed carefully and stored in an upright position

Avoid inhaling vapors.

Prohibited equipment and procedures:

Smoking, eating and drinking are prohibited in premises where the preparation is used

Never open the packages under pressure

Storage:

Keep the container tightly closed in a dry place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION



Use personal protection equipment as per Directive 89/686/EEC.

Technical measures:

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

Exposure limit values (2003-2006):

	TWA:	STEL:	Ceiling:	Definition:	Criterion:
Ireland					
96-29-7	3 ppm	10 ppm	-	-	-
Polska					
64742-48-9	300 mg/m3	900 mg/m3	-	-	-
USA/AIHA WEEL					
96-29-7	10 ppm	-	-	-	-

Respiratory protection:

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

Anti-gas filters :

- A1,A2,A3 (brown)

Hand protection:

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

In the event of prolonged or repeated contact with the hands, use appropriate gloves.

Type of gloves recommended :

- Nitrile
- PVA (polyvinylalcohol)

SAFETY DATA SHEET (EC REGULATION No 1907/2006)
 Version: N°1 (14/05/2009)
 Name: Vitrail solvant : or / gold - 050038

Date: 14/05/2009 Page 4/7
 Revision: N°2 (14/05/2009)
 Company: PEBEO INDUSTRIES

Eye and face protection:

Use eye protectors designed to protect against liquid splashes

Skin protection:

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical state: fluid liquid

Important health, safety and environmental information:

pH of the substance or preparation: not relevant.

The pH is impossible to measure or its value is not relevant.

Boiling point/boiling range: 180 °C.

Flash point interval: 23°C <= Flash point <= 55°C

Flash point: 36.30 °C.

Vapour pressure: Below 110 kPa (1.10 bar).

Density: < 1

Water solubility: Insoluble.

Other information:

Self-ignition temperature: not specified.

VOC (g/l): 447.90

10 - STABILITY AND REACTIVITY

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

Waste:

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

20 01 27 * paint, inks, adhesives and resins containing dangerous substances

SAFETY DATA SHEET (EC REGULATION No 1907/2006)
Version: N°1 (14/05/2009)
Name: Vitrail solvant : or / gold - 050038

Date: 14/05/2009 Page 5/7
Revision: N°2 (14/05/2009)
Company: PEBEO INDUSTRIES

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2007 - IMDG 2006 - ICAO/IATA 2007).

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.
	3	F1	III	3	30	LQ7	163 640E 650



IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.
	3	-	III	5 L	F-E,S-E	163 223 944 955

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note
	3	-	III	309	60 L	310	220 L	A3 A72
	3	-	III	Y309	10 L	-	-	-

15 - REGULATORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations In addition directive 2008/58/EC with the 30° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

In addition directive 2009/2/EC with the 31° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

In addition Regulation (EC) No 1272/2008 have been taken into account.

Packaging < 125 ml.

Preparation classification:
Flammable

Contains:


Contains 202-496-6 2-BUTANONE OXIME. May produce an allergic reaction.

Particular hazards associated with the preparation and safety recommendations:

R 10	Flammable.
S 2	Keep out of the reach of children.
S 46	If swallowed, seek medical advice immediately and show this container or label.
S 23	Ne pas respirer les vapeurs.
S 24	Avoid contact with skin.
S 51	Use only in well-ventilated areas.
S 62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Particular provisions:

NFPA 704 Label: Health=0 Flammability=3 Instability=1 Special Hazards=none



SAFETY DATA SHEET (EC REGULATION No 1907/2006)
Version: N°1 (14/05/2009)
Name: Vitrail solvant : or / gold - 050038

Date: 14/05/2009 Page 6/7
Revision: N°2 (14/05/2009)
Company: PEBEO INDUSTRIES

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

Full text of risk phrases appearing in section 3:

R 21	Harmful in contact with skin.
R 36/38	Irritating to eyes and skin.
R 40.C3	Limited evidence of a carcinogenic effect.
R 41	Risk of serious damage to eyes.
R 43	May cause sensitisation by skin contact.
R 65	Harmful: may cause lung damage if swallowed.

Difference Report

Revision: N°2 (14/05/2009) / Version: N°1 (14/05/2009)

~~Revision: N°1 (23/09/2005) / Version: N°1 (14/05/2009)~~

3 - COMPOSITION/INFORMATION ON INGREDIENTS

May produce an allergic reaction:

68409-81-4	270-066-5	ACIDES GRAS RAMIFIES EN C6-19, SELS DE COBALT	Xn N	38-43-51/53-22	0 <= x % < 2.5
------------	-----------	-----------------------------------------------	------	----------------	----------------

5 - FIRE-FIGHTING MEASURES

Special protective equipment for fire-fighters:

~~Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.~~

9 - PHYSICAL AND CHEMICAL PROPERTIES

General information:

Physical state:	viscous liquid
Physical state:	fluid liquid
Other information:	
melting point/melting range:	not specified.
Decomposition point/decomposition range:	not specified.
VOC (g/l):	447.90

13 - DISPOSAL CONSIDERATIONS

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

~~02 01 11 * waste paint and varnish containing organic solvents or other dangerous substances~~

20 01 27 * paint, inks, adhesives and resins containing dangerous substances

14 - TRANSPORT INFORMATION

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.
---------	-------	------	----------	-------	--------	----	---------

~~Not subject to this regulation if Q < 450L.~~

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.
------	-------	---------	----------	----	-----	---------

SAFETY DATA SHEET (EC REGULATION No 1907/2006)
 Version: N°1 (14/05/2009)
 Name: Vitrail solvant : or / gold - 050038

Date: 14/05/2009 Page 7/7
 Revision: N°2 (14/05/2009)
 Company: PEBEO INDUSTRIES

~~Not subject to this regulation if Q < 30t~~

15 - REGULATORY INFORMATION

~~In addition directive 2004/73/EC with the 29° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.~~

In addition directive 2008/58/EC with the 30° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

In addition directive 2009/2/EC with the 31° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

In addition Regulation (EC) No 1272/2008 have been taken into account.

Contains:

~~Contains 270-066-5~~ ~~ACIDES GRAS RAMIFIES EN C6-19, SELS DE COBALT. May produce an allergic reaction.~~

Particular hazards associated with the preparation and safety recommendations:

~~S 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).~~

~~S 41 In case of fire and/or explosion do not breathe fumes.~~

S 23 Ne pas respirer les vapeurs.

16 - OTHER INFORMATION

Full text of risk phrases appearing in section 3:

~~R 22 Harmful if swallowed.~~

~~R 38 Irritating to skin.~~

~~R 51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.~~