

10/24/03 11:27 FAX 819 821 4151

PEBEO SHERBROOKE

011

02973-
0045, 0250Date de révision : 04/02/02
Date d'impression : 24/10/03
Page 1 sur 4

12-03-03

SAFETY DATA SHEET

1 - IDENTIFICATION OF PREPARATION AND COMPANY/BUSINESS

Preparation:

Name: VITRIL THINNER.
Product code: ZF0778A.

Company/business:

Registered company name: PEBEO INDUSTRIES.
Address: 305 AVENUE DU PIC DE BERTAGNE - BP108 - 13881.GEMENOS CEDEX.FRANCE
Telephone: 33 (0) 4.42.32.08.08. Fax:33 (0) 4.42.32.01.70. Telex:
Emergency telephone No.: 33 (0) 1.45.45.67.67.
Association/Organisation: INRS.

Normal use:

N/A !

2 - INFORMATION REGARDING CONSTITUENTS

Hazardous substances present on their own.

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

This preparation contains no hazardous substance in this category.

Other substances representing a hazard:

849-327-00-8 Cas 64742-49-9 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY Concentration >=50.00% and <100.00%. Symbol: Xn R: 65

Substances present at a concentration below the minimum danger threshold.

No known substance in this category present.

Other substances with occupational exposure limits.

No known substance in this category present.

3 - IDENTIFICATION OF HAZARDS

This product is classed: Highly flammable liquid.

This preparation presents a suck up danger due to the low viscosity associated with a petroleum by-product.

Other data:

Packaging < 125 ml.

4 - FIRST AID.

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing in an unconscious person.

In the event of exposure by inhalation.

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

In the event of splashes or contact with eyes.

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

In the event of splashes or contact with skin.

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.
DO NOT use solvents or thinners.

In the event of swallowing.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.
If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

In the event of fire, the recommended extinguishing agents are:

Carbon dioxide, chemical powders, foams, and other extinguishing gases.

V-3406

10/24/03 11:28 FAX 819 821 4151

PEBEO SHERBROOKE

012

Date de révision : 04/02/02

Date d'impression : 24/10/03

Page 2 sur 4

In the event of fire, use specifically suitable extinguishing agents. Never use water.

Extinguishing agents not to be used

Water is not generally recommended since it can be ineffective; however, it can be used successfully to cool containers exposed to the fire and to disperse fumes.

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Special equipment for fire-fighting personnel.

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

6 - MEASURES TO BE TAKEN IN THE EVENT OF ACCIDENTAL SPILLAGE**Safety precautions:**

Eliminate any possible source of ignition and ventilate the premises.

Avoid inhaling the fumes.

Consult the safety measures listed under headings 7 and 8.

Environmental safety precautions:

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatom earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures.

Cleaning methods:

Clean preferably with a detergent, do not use solvents.

7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workchops where the product is handled.

Handling:

Handle in well-ventilated areas.

The fumes are denser than air. They can spread along the ground and form explosive mixtures with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapour concentrations higher than the occupational exposure limits.

Never suck up this product.

Fire prevention:

Prevent the accumulation of electrostatic charges with connections to earth.

The preparation may become electrostatically charged; always place on the ground during transfer. Wear antistatic shoes and clothes and make floors of conductive materials.

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures

For personal safety, see §9.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Avoid inhaling fumes.

Prohibited equipment and procedures.

Smoking, eating and drinking are prohibited in premises where the preparation is used.

Never open the packages under pressure.

Storage.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

8 - EXPOSURE CONTROL - PERSONAL SAFETY

10/24/03 11:28 FAX 810 821 4151

PEBEO SHERBROOKE

013

Date de révision : 04/02/02

Date d'impression : 24/10/03

Page 3 sur 4

Technical measures.

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

If this ventilation is insufficient to maintain the concentration of solvent fumes below the exposure limits, wear breathing apparatus.

Exposure limits per INRS ND 1945-153-93/(1998) and ND 2022-183-96:

Substance in this category unknown.

Exposure limits per 2000/39/EC and 98/24/EC:

VME-ppm: VME-mg/m3: VLE-ppm: VLE-mg/m3: Notes:

Safety breathing apparatus:

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

Hand protection.

Protective creams may be used for exposed skin, but they should not be applied after contact with the product.

Due to the solvents present, it is recommended that neoprene rubber or nitrile rubber gloves be worn.

Eye and face protection.

Use eye protectors designed to protect against liquid splashes.

Skin protection.

For further information, see § 11 of S.D.S. - Toxicological information.

9 - PHYSICAL PROPERTIES

Density:	< 1
Acid/base character of preparation:	not relevant.
Solubility of preparation in water:	insoluble.
Vapour tension at 50°C of volatile constituents:	Below 110Kpa (1.10 bar).
Physical state:	fluid liquid
Flash point interval:	Flash point: <= 21°C.
The pH is impossible to measure or its value is not relevant.	
Self-ignition temperature:	not specified.
Decomposition temperature:	not specified.
Melting temperature interval:	not relevant.
Average distillation temperature of solvents contained:	150 °C.

10 - STABILITY AND REACTIVITY

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide.

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

11 - TOXICOLOGICAL INFORMATION

No data is available regarding the preparation itself.

Exposure to fumes from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys; liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage.

12 - ECOLOGICAL INFORMATION

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

13 - DISPOSAL CONSIDERATIONS

Do not pour into drains or waterways.

14 - TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

UN 1263 = Paint flammable (including lacquer, enamel, stain, shellac, varnish, polish and related material).

ADR/RID Class: Number: Code: Identif.: Label:

10/24/03 11:28 FAX 819 821 4151

PEBEO SHERBROOKE

014

Date de révision : 04/02/02
 Date d'impression : 24/10/03
 Page 4 sur 4

IMDG	Page	5° b N°ONU	33 Class	1263 Number	3 2°Label	Identif.	N°GSMU
		1263	3.2	II	-	3-07	-

The page number 3230 should not appear anymore on the Dangerous Goods Declaration (Amendment 28-99).

IATA	N°ONU	Class	2°Label	Number	Passenger	Passenger	Freighter	Freighter	nota
	1263	3	-	II	305	5 L	307	60 L	A3
	1263	3	-	II	Y305	1 L	-	-	A7

15 - STATUTORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 88/379/EEC and its adaptations
 In addition directive 2000/32/EC with the 28° adaptation of directive 67/548/EC (Hazardous substances) have been taken into account.

Packaging < 125 ml:

Preparation classification.

Harmful. Highly flammable.

Contains:

649-327-00-6 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Particular hazards associated with the preparation and safety recommendations:

R 11	Highly flammable.
R 65	Harmful, may cause lung damage if swallowed.
S 2	Keep out of reach of children.
S 48	If swallowed, seek medical advice immediately and show this container or label.
S 62	If swallowed, do not induce vomiting. Seek medical advice immediately and show this container or label.
S 16	Keep away from sources of ignition - no smoking.
S 23	Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
S 24	Avoid contact with skin.
S 29	Do not empty into drains.
S 51	Use only in well ventilated areas.
S 9	Keep container in a well-ventilated place.

Particular provisions:

Child-resistant fastenings (Annex a- 91/442/EEC)
 Tactile warning of danger.

16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties.