

<b>08925-1000</b>
<b>-1500</b>

REVISION DATE: 01/07/08

**SAFETY DATA SHEET**  
**WINSOR & NEWTON OIL PAINTING PRIMER**

**1 IDENTIFICATION OF THE SUBSTANCE/ PREPARATION AND COMPANY UNDERTAKING**

PRODUCT NAME            WINSOR &amp; NEWTON OIL PAINTING PRIMER

APPLICATION                    Oil primer for art and creative use

SUPPLIER                        ColArt America Inc.  
11 Constitution Avenue  
Piscataway  
New Jersey  
08855-1396Emergency telephone number    1-800-628-3385  
Tel. number for information      732-562-0770**2. COMPOSITION INFORMATION ON INGREDIENTS**

COMPOSITION COMMENTS:

<b>Hazardous Components</b>	<b>CAS Number</b>	<b>OSHA PEL</b>	<b>TLV</b>
Petroleum hydrocarbons	64742-82-1	No data	No data
2-butanone oxime	96-29-7	No data	No data

**3. HAZARD IDENTIFICATION**

CLASSIFICATION

In accordance with ASTM D-4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Effects this product labeled as:

**WARNING: MAY BE HARMFUL BY BREATHING VAPORS. OVEREXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. CONTAINS PETROLEUM DISTILLATES. Avoid breathing vapors. Use extraction fan to ensure adequate cross ventilation.**

KEEP OUT OF REACH OF CHILDREN

**4. FIRST AID MEASURES**

INHALATION

Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Drink plenty of water. Get medical attention if any discomfort

1

**SKIN CONTACT**

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get prompt medical attention if any discomfort continues.

**EYE CONTACT**

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lid. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

**5. FIRE FIGHTING MEASURES****EXTINGUISHING MEDIA**

Fire can be extinguished using foam, dry chemicals, sand, dolomite etc.

**6. ACCIDENTAL RELEASE MEASURES****SPILL CLEAN UP METHODS**

Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place in to containers. Do not contaminate water courses or sewer. Dispose of the colour in accordance with local regulations.

**7. HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapors.

**STORAGE PRECAUTIONS**

Keep in original container. Store at moderate temperatures in dry, well ventilated area.

**8. EXPOSURE CONTROLS/ PERSONAL PROTECTION****ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contamination.

**EYE PROTECTION**

If risk of splashing, wear safety goggles or face shield.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapor contact.

**HYGEINE MEASURES**

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Paste
COLOR	White
ODOR	Hydrocarbon
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	> 200 760 mm Hg
RELATIVE DENSITY	1.5
VOLATILE BY VOL (%)	25
FLASH POINT (°C)	42 (Closed cup)
FLAMMABLE LIMITS	LEL = 0.9; UEL = 6.0
pH-VALUE CONC. SOL .	Not applicable

**10. STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid contact with acids and oxidizing substances.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire generates fumes of carbon dioxide and carbon monoxide.

**11. TOXICOLOGICAL INFORMATION****GENERAL INFORMATION****INHALATION**

Prolonged inhalation of high concentrations may damage respiratory system.

**INGESTION**

May cause discomfort if swallowed

**SKIN CONTACT**

Acts as a defatting agent. May cause cracking of skin and eczema. Prolonged contact may cause irritation..

**EYE CONTACT**

Spray and vapor in the eyes may cause irritation and smarting.

**ROUTE OF ENTRY**

Inhalation. Skin and eye contact.

**MEDICAL SYMPTOMS**

Inhalation of large quantities of vapor may cause dizziness, headache. Prolonged contact with skin may cause irritation.

**12. ECOLOGICAL INFORMATION****ECOTOXICITY**

This product is insoluble in water.

**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements.

**14. TRANSPORT INFORMATION**

PROPER SHIPPING NAME	PAINT RELATED MATERIAL		
UN NO. ROAD	1263	ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids	ADR pack group	III
ADR label number	3		
RID CLASS NO.	3	RID pack group	III
UN NO. SEA	1263	IMDG CLASS	3
IMDG PACK GROUP	III		
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GROUP	III		

**15. REGULATORY INFORMATION**

This product has been evaluated by a toxicologist and is labeled for acute and chronic health hazards in accordance with the Labeling of Hazardous Art Materials Act and Federal regulation 16 CFR 1500.14 of the Federal Hazardous Substances Act.

This product conforms to ASTM D 4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Hazards. The warning given on the product label is:

In accordance with ASTM D-4236 Standard Practice for Labeling Art Materials for Chronic Adverse Health Effects this product labeled as:

WARNING: MAY BE HARMFUL BY BREATHING VAPORS. OVEREXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. CONTAINS PETROLEUM DISTILLATES. Avoid breathing vapors. Use extraction fan to ensure adequate cross ventilation.

KEEP OUT OF REACH OF CHILDREN

**16. OTHER INFORMATION**

INFORMATION SOURCE

Material Safety ~Data Sheet, Misc. manufacturers.

REVISION DATE  
01/07/08