

13202-1003
-1013
-1014
-9005



NOV 11 1994 01:46PM HUNT CUST SERVICE
Material Safety Data Sheet (9082-10) ✓
-25
May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) **QUICK STIK FOAMBOARD, INCLUDING HI-TACK**

Section I

Manufacturer's Name HUNT BIENFANG	Emergency Telephone Number (704)872-9511
Address (Number, Street, City, State, and ZIP Code) 2020 West Front St.	Telephone Number for Information (704)872-9511
Statesville, NC 28677	Date Prepared February 21, 1994
	Signature of Preparer (optional) <i>Burl Martin</i>

Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Isopentane 78-78-4	NA	NA		
Polystyrene 9003-53-6	NA	NA		
Talc 14807-96-6	NA	NA		

Nonhazardous according to 29 CFR 1910.1200
Product contains one or more of the following as major ingredients:
Ethylene vinyl acetate polymer; styrene butadiene polymer, polyolefin polymers
Styrene isoprene polymer; petroleum derived tackifying resins
Rosin derived tackifying resins; paraffin waxes and oils, terpene derived tackifying resins
Microcrystalline waxes and oils; naphthanic waxes and oils

Section III -- Physical/Chemical Characteristics

Boiling Point	NA	Specific Gravity (H ₂ O = 1)	< 1
Vapor Pressure (mm Hg.)	NA	Melting Point	220°F
Vapor Density (AIR = 1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility in Water	Not Soluble		
Appearance and Odor	Off-white to tan colored solid with resinous odor		

Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used)	NA	Flammable Limits	LEL NA	UEL NA
Extinguishing Media	Water Spray			
Special Fire Fighting Procedures	Decomposition may produce hazardous chemicals such as CO, NO, and other unknown hazards and smoke. Material is combustible. Wear self contained breathing apparatus.			
Unusual Fire and Explosion Hazards	Polystyrene emits styrene, CO, and other hydrocarbons when burning.			

V-2260

NOV 11 '94 01:47PM HUNT CUST SERVICE

F.4

Section V -- Reactivity Data

Stability	Unstable	X	Conditions to Avoid Oxidizing materials may cause reaction
	Stable		

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Oxides of carbon and smoke

Hazardous Polymerization	May Occur	X	Conditions to Avoid
	Will Not Occur		

Section VI -- Health Hazard Data

Route(s) of Entry:	Inhalation? NA	Skin? NA	Ingestion? Not likely
--------------------	-------------------	-------------	--------------------------

Health Hazards (Acute and Chronic)
May be obstruction if swallowed. Excessive heating may produce vapors causing irritation of mucous membrane and respiratory tract.

Carcinogenicity:	NTP? No	IARC Monographs? No	OSHA Regulated? No
------------------	---------	---------------------	--------------------

Signs and Symptoms of Exposure
Eyes : irritation or redness

Medical Conditions Generally Aggravated by Exposure
Eyes: irritation or redness

Emergency and First Aid Procedures
Eyes: flush with water

Section VII -- Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled
Sweep up and place in container for recycle or disposal

Waste Disposal Method
Disposal should be done in accordance with all local, state, and federal laws & regulations.

Precautions to Be Taken in Handling and Storing
Keep in dry place. Keep containers closed. Prolonged exposure to sun or UV light may effect color.

Other Precautions
Take precautions for static electricity generated during mechanical/pneumatic transfer of product.

Section VIII -- Control Measures

Respiratory Protection (Specify Type)
NA

Ventilation	Local Exhaust	Special
	Mechanical (General)	Other

Protective Gloves
Generally not needed

Eye Protection
Generally not needed

Other Protective Clothing or Equipment
None

Work/Hygienic Practices
Normal good working practices should be adopted.