

LUPE PLASTICS Fax: 3090912047
MAY-17-2002 10:30 PLASKOLITE
PLASKOLITE Polystyrene PLASTIC

May 17 2002 9:39 P.02

297 7287 P.01
Page 1 of 5

(60425-xx)
Rev'd 5-20-02

attn: Dennis

18908-XXXX

Return to Plaskolite Products

PLASKOLITE, INC.
1770 Joyce Avenue
Columbus, OH 43219

EMERGENCY HOTLINE:
(614) 294-3281

Date Issued: 1/4/2000
Date Revised:

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

Material: Plaskolite Polystyrene Plastic
(includes Polystyrene (PS) Sheet, Run-to-Size Polystyrene Sheet, Patterned Styrene Sheet, Styrene Lighting Sheet)
Chemical Name or Synonyms: Polystyrene

2. PRODUCT COMPONENTS

COMPONENTS

CAS REG. NO.

WEIGHT (%)

1. Polystyrene (PS) 9003-53-6 100

3. PHYSICAL PROPERTIES

Appearance: Clear to opaque solid
Odor: N/A
Viscosity: N/A
Melting Point: 104° C/220° F
Boiling Point: N/A
Vapor Pressure: N/A
Vapor Density: N/A (Air =1)
Specific Gravity: 1.05 (Water =1)
pH: N/A
Solubility in Water: Negligible
Volatility: Negligible (Weight %)
Evaporation Rate: Negligible (Butyl Acetate = 1)

V-1085

4. FIRE AND EXPLOSION HAZARD INFORMATION

file //D:\Tim Ling's Working Files\Product Certifications and Safety\MSDS\18908-XXXX

COPE PLASTICS Fax: 3096912047
 MAY-17-2002 10:30 PLASKOLITE

May 17 2002 9:39 P.03

297 7287 P.02
 Page 2 of 5

Flash Point: 340° C/650° F
Auto Ignition Temperature: 490° C/910° F
Upper Explosion Limit (%): N/A
Lower Explosion Limit (%): N/A
Extinguishing Media: Carbon dioxide, dry chemical, or water.
Fire Protection Equipment: Wear self-contained, positive pressure breathing apparatus (MSHA/NIOSH approved, or equivalent) and full protective gear.
Unusual Fire and Explosion Hazard: Product is combustible thermoplastic material that burns vigorously with intense heat.

5. WORKPLACE EXPOSURE LIMITS

<u>COMPONENTS</u>	<u>OSHA</u>		<u>ACGIH</u>	
	<u>PEL</u>	<u>STEL</u>	<u>TLV</u>	<u>STEL</u>
1. PS	None	None	None	None
2. Nuisance dusts (as particulates)	5 mg/m ³	None	10 mg/m ³	None

6. HAZARD INFORMATION

Hazard Scale: 0 = Insignificant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme

Health Designation: 0

Fire Designation: 1

Reactivity Designation: 0

Inhalation: Inhalation of vapors from heated product can cause nausea, headache, dizziness as well as irritation of lungs, nose, and throat.

Eye Contact: Vapors from heated product can irritate the eyes.

Ingestion: Low hazard associated with normal conditions.

Skin Contact: Possible skin irritation. Contact with molten material can result in burns.

Carcinogenicity: N/A

7. EMERGENCY AND FIRST AID PROCEDURES

~~file://D:\Tim Ling's Working Files\Product Certifications and Safety\MSDS\PLA MSD-PS hr 1/17/00~~

Item Numbers: 18908-1501, 18908-1505, 18908-1951, 18908-1952, 18908-1953, 18908-1955, 18908-1956, 18908-1957, 18908-1958, 18908-1959

Page 2 of 5

COPE PLASTICS Fax: 3096912047
 MAY-17-2002 10:30 PLASKOLITE

May 17 2002 9:40 P.04

297 7287 P.03
 Page 3 of 5

Inhalation: Move subject to fresh air.

Eye Contact: Flush eyes with plenty of water for at least 15 minutes. Call a physician.

Ingestion: This material is not expected to be absorbed within the gastrointestinal tract, so induction of vomiting should not be necessary.

Skin Contact: If molten material contacts skin, cool rapidly with cold water and obtain medical attention for thermal burn.

8. REACTIVITY INFORMATION

Stability: Stable

Conditions to Avoid: None

Hazardous Decomposition Products: Thermal decomposition or combustion may emit vapors, carbon monoxide, or carbon dioxide.

Incompatible Compounds: N/A

9. SPILL OR LEAK INFORMATION

Sweep or scoop up and remove.

10. WASTE DISPOSAL

Landfill or incinerate at a facility that complies with local, state and federal regulations.

11. EXPOSURE CONTROLS/PERSONAL PROTECTION MEASURES

Respiratory Protection: None required under normal conditions. See Section 12.

Hand Protection: Canvas or cotton gloves.

Eye Protection: Safety glasses with side shields (ANSI Z87.1 equivalent).

Other Protection: N/A

Ventilation: Local exhaust ventilation systems should be constructed and installed in accordance with ANSI Z9.2 or ACGIH guidelines to control potential emissions near the source.

12. STORAGE AND HANDLING INFORMATION

file://D:\Tim Ling's Working Files\Product Certifications and Safety\MSDS\PLA MSD-PS.txt 1/12/00

Item Numbers: 18908-1501, 18908-1505, 18908-1951, 18908-1952, 18908-1953, 18908-1955, 18908-1956, 18908-1957, 18908-1958, 18908-1959

CUPE PLASTICS Fax: 5096912047 May 17 2002 9:40 P.05
 MAY-17-2002 10:31 PLASKOLITE 297 7287 P.04
 Page 4 of 5

Maximum Storage Temperature: N/A

Storage Measures: If material is stored under ambient temperature conditions, it is not hazardous. However, extensive storing at higher than the maximum temperature will emit vapors, carbon monoxide or carbon dioxide.

Handling Measures: Processing of the material under high temperatures will cause hazardous emissions of vapors, carbon monoxide or carbon dioxide. Blower collecting and local exhaust ventilation systems should be installed to prevent contaminant dispersion into the air. Sawing of this product generates particulates regulated as "inert" or "nuisance" dusts. To minimize dust emissions, engineering controls should be employed, such as baghouse filters and cyclone separators.

13. REGULATORY INFORMATION

Environment

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA): Under section 102(a) of the Act, this product is NOT designated as hazardous. In addition, no reportable quantities and no notification requirements to the National Response Center in Washington, DC are set forth for its release from a vessel, an offshore or an onshore facility (40 CFR Part 302).

Resource Conservation and Recovery Act (RCRA): When this product becomes a waste, it is identified as solid but NOT hazardous waste under RCRA criteria (40 CFR Part 261).

Toxic Substances Control Act (TSCA): The components of this product are on the TSCA inventory list. Any impurities present in this product are exempt from listing.

Superfund Amendment and Reauthorization Act of 1986 (SARA) Title III: N/A

Transportation

DOT Hazard Class: Not regulated.

DOT Shipping Name: N/A

Labor Awareness

This product as supplied is non-hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). However, under processing conditions it may become a health hazard to employees because vapors and/or particulates could be released. See Section 12 for Storage and Handling Information.

14. GLOSSARY

LUPE PLASTICS
MAY-17-2002 10:31

Fax: 3096912047

May 17 2002 9:40 P.06

PLASKOLITE

297 7287 P.05

ACGIH	American Conference of Governmental Industrial Hygienists
CFR	Code of Federal Regulations
DOT	United States Department of Transportation
mg/m ³	milligrams per cubic meter (concentration)
MSHA	Mine Safety and Health Administration
N/A	Not Applicable or Not Available
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Safety and Health Administration (Department of Labor)
PEL	Permissible Exposure Limit (time-weighted average)
ppm	parts per million (concentration)
PS	Polystyrene
STEL	Short-Term Exposure Limit (15-minute)
TLV	Threshold Limit Value (time-weighted average)

The information presented herein is believed to be factual and reliable. It is offered in good faith, but without guarantee, since conditions and methods for the use of our products are beyond our control. We recommend that the prospective user determine the suitability of our products and these suggestions before adopting them on a commercial scale.

Please direct comments and questions to Plaskolite Environmental, Health and Safety

Return to Plaskolite Products

file://D:\Tim Ling's Working Files\Product Certifications and Safety\MSDS\Plaskolite\MSD-PS ht 1/12/00