

21101-XXXX**MATERIAL SAFETY DATA SHEET**

May be used to comply with OSHA's 29 CFR 1910.1200

IDENTITY (AS USED ON LABEL AND LIST)

Note: blank spaces are not permitted. If any item is not applicable,

DICK BLICK BLACK CAT INDIA INK

or no information available, the space must be marked appropriately

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION**ROCK PAINT DISTRIBUTING CORP.****(608) 868-6873**

MANUFACTURER

TELEPHONE NUMBER FOR INFORMATION

365 SUNNYSIDE DR. P.O. BOX 482**(920) 563-8545**

ADDRESS

EMERGENCY TELEPHONE NUMBER

MILTON, WI 53563**JULY 2008**

DATE PREPARED

SECTION 2 - MATERIAL IDENTIFICATION AND INFORMATION

OTHER LIMITS

COMPONENTS: CHEMICAL NAME & COMMON NAMES

%

OSHA PEL

ACGIH TLV

RECOMMENDED

Contains no hazardous substand per OSHA
29 CFR 1910.1200

Material is a water based product with the AP Seal. Products with the AP Approved Products Seal of the Art and Craft Materials Institute Inc. are certified in a program of toxicological evaluation by a medium expert to contain no material in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems. These products are certified by the Institute to be in accordance with the voluntary chronic hazard labeling standard ASTM D-4236.

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT -	Range 212 F	SPECIFIC GRAVITY (H ₂ O = 1) -	Range 1.00-1.10
VAPOR PRESSURE (mm Hg & TEMPERATURE) -	N/A	MELTING POINT -	< 32 F
VAPOR DENSITY (AIR=1) -	lighter than air	EVAPORATION RATE (WATER = 1) -	lower than ether
SOLUBILITY IN WATER -	dilutable in water	WATER REACTIVE -	N/A
APPEARANCE & ODOR -	black, low viscosity, low odor		

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT & METHOD USED	FLAMMABILITY LIMITS IN AIR % BY VOLUME		
N/A	N/A		
EXTINGUISHER MEDIA	LEL	UEL	
CO ₂ , Foam or Water	N/A	N/A	
SPECIAL FIRE FIGHTING PROCEDURES			
Wear self-contained breathing apparatus (pressure demand, MSHA/NIOSH approved or equivalent) and full protective gear			
UNUSUAL FIRE AND EXPLOSION HAZARDS			
Material can spatter above 212F. Film can burn.			

SECTION 5 - REACTIVITY HAZARD DATA		BLACK CAT INDIA INK Page 2 of 2	
STABILITY		CONDITIONS TO AVOID	
<input checked="" type="checkbox"/> STABLE		Onset of decomposition 350 F	
<input type="checkbox"/> UNSTABLE		<u>None</u>	
INCOMPATIBILITY (MATERIALS TO AVOID)		N/A	
HAZARDOUS DECOMPOSITION PRODUCTS		N/A	
HAZARDOUS POLYMERIZATION		CONDITIONS TO AVOID	
<input type="checkbox"/> MAY OCCUR		<u>N/A</u>	
<input checked="" type="checkbox"/> WILL NOT OCCUR		<u>None known</u>	
SECTION 6 - HEALTH HAZARD DATA			
PRIMARY ROUTES OF ENTR		CARCINOGEN LISTED IN	
N/A		N/A	
<input type="checkbox"/> INHALATION	<input type="checkbox"/> INGESTION	<input type="checkbox"/> NTP	<input type="checkbox"/> OSHA
<input type="checkbox"/> SKIN ABSORTION	<input type="checkbox"/> NOT HAZARDOUS	<input type="checkbox"/> IARC MONOGRAPH	<input checked="" type="checkbox"/> NOT LISTED
HEALTH HAZARDS		ACUTE	
Refer to Section 2		CHRONIC	
SIGNS AND SYMPTOMS		Not known	
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE		Not known	
EMERGENY FIRST AID PROCEDURES -		Consult a Physician Immediatley.	
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES			
STEPS TO BE TAKEN IS MATERIAL IS SPILLED OR RELEASED			
Usual Clean Up Procedure			
WASTE DISPOSAL METHODS			
Dispose of in accordance with Federal and Local State Regulations			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE			
Store at room temperature.			
OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS			
Not known			
SECTION 8 - CONTROL AND PROTECTIVE MEASURES			
RESPIRATORY PROTECTION (SPECIFY TYPE)			
None required			
VENTILATION TO BE USED		LOCAL EXHAUSE	
Adequate		OTHER (SPECIFY)	
		MECHANICAL (GENERAL)	
		SPECIAL	
PROTECTIVE GLOVES		EYE PROTECTION	
N/A		N/A	
OTHER PROTECTIVE CLOTHING AND EQUIPMENT		N/A	
HYGIENIC WORK PRACTICES		N/A	