

Rev'd 5-05-04 ✓  
 MAY-04-04 15:11 FROM:HUNT/CUST.SERVICE  
 \* Painter Paint Markers \*

ID: 7048710116

21312 - all codes except  
 - 4050  
 - 4051  
 - 4055  
 9100  
 - 9300  
 - 9400

**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072



IDENTITY (As Used on Label and List) SPEEDBALL PAINTERS (water-based)

**Section I**

Manufacturer's Name Hunt Manufacturing Co.	Emergency Telephone Number 704-872-9511
Address (Number, Street, City, State, and ZIP Code) Speedball Road Statesville, NC 28677	Telephone Number for Information 704-872-9511
	Date Prepared August 16, 2001
	Signature of Preparer (Optional) <i>[Signature]</i>

**Section II - Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Approved for the AP Seal as per the Art and Craft Materials Institute, Inc. (ACMI). Labeling conforms to ASTM D4236.				
Dipropylene Glycol Monomethyl Ether (CAS #34590-94-8)	100ppm	100ppm	N/A	

Note: This product has been evaluated by a toxicologist only as per intended usage. Do not deviate from intended usage!

V.2260

**Section III - Physical/Chemical Characteristics**

Boiling Point	212-473°F	Specific Gravity (H <sub>2</sub> O = 1)	1.06-1.38
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F.
Vapor Density (AIR = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than 1
Solubility in Water	Dilutable		

Appearance and Odor  
 Low viscosity, semi-aromatic odor

**Section IV - Fire and Explosion Hazard Data**

Flash Point (Method Used) Not applicable (N/A)	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A	Special Fire Fighting Procedures wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.		
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F.
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water. Induce vomiting if large amounts are ingested.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method Incinerate at a permitted facility according to current local, state and federal regulations.

Precautions to Be Taken in Handling and Storing Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (Specify Type) None required with adequate ventilation & normal operating conditions

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work Hygienic Practices Use protective cream where excessive skin contact is likely.