

V3660



A Newell Rubbermaid Company

MATERIAL SAFETY DATA SHEET

MSDS # 543-549

21716-1001  
- 1004  
= 1011  
= 1014

Section One: Identification

Sanford, L.P.  
2707 Butterfield Road  
Oak Brook, IL 60523 USA  
800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name: Prismacolor Tuffilm Final Fixative, Gloss and Matte; Prismacolor Fixative

Product Sizes: 4.75 oz. and 12.75 oz.

Product Class: Aerosols

Section Two: Hazard Identification

\*\*\*DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. EYE IRRITANT. SKIN IRRITANT. CANCER AGENT BASED ON EXPERIMENTAL DATA. EXPOSURE MAY CAUSE DAMAGE TO THE LIVER.

CONTAINS: ACETONE, ETHYL BENZENE, XYLENE

KEEP OUT OF REACH OF CHILDREN.

\*\*WARNING: This product contains a chemical known to the State of California to cause cancer.

Section Three: Composition

Ingredients	CAS Number	Max. Weight %	PEL/TLV
Xylene	1330-20-7	40%	100 ppm
Acetone	67-64-1	40%	750 ppm
Liquefied Petroleum Gas	68476-85-7	30%	1000 ppm

Section Four: First Aid Measures

February 19, 2007



A *NewellRubbermaid* Company

**MATERIAL SAFETY DATA SHEET**

**MSDS # 543-549**

**Inhalation:** If inhalation symptoms occur, move to fresh air.

**Skin Contact:** Wash with soap and water.

**Eye Contact:** If eye contact occurs, rinse immediately with water then flush with tap water for 15 minutes.

**Ingestion:** Consult a physician. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following products: 643, 649, 04595, 04596

February 19, 2007

Page 2 of 6



A *NewellRubbermaid* Company

## MATERIAL SAFETY DATA SHEET

MSDS # 543-549

### Section Five: Fire Fighting Measures

Flash Point: 0F Closed Cup (Acetone)

Flammability Limits (% by volume): Lower: 2.5% (Acetone) Upper: 12.8% (Acetone)

Extinguishing Media: Foam, carbon dioxide, dry chemical

Special Fire Fighting Measures: Foam, carbon dioxide, dry chemical

Unusual Fire and Explosion Hazards: Water may be used to cool closed containers to prevent pressure buildup and possible bursting when exposed to high temperatures. Firemen should wear self-contained respiratory equipment.

### Section Six: Accidental Release Measures

Remove all ignition sources. Evacuate area. Contain liquid; transfer to closed containers. Keep out of water entries.

### Section Seven: Handling and Storage

Handling: Use only with adequate ventilation.

Storage: Do not store above 120F. KEEP OUT OF REACH OF CHILDREN.

### Section Eight: Exposure Controls and Personal Protection

Respiratory Protection and Special Ventilation Requirements: NIOSH or Bureau of Mines approved organic vapor-type respirator is required in absence of proper environmental control.

Other Protective Equipment (Gloves, Goggles, Etc.): Impervious gloves and safety glasses recommended.

Work/Hygiene Practices: PRECAUTIONS: Avoid prolonged contact with skin, and contact with heat, sparks, and open flame. Wash hands immediately after use. When using, do not eat, drink, or smoke. Do not smoke when using, or store or use near heat or flame. Keep away from eyes. Vapors can ignite explosively. If using indoors, turn off all pilot lights. Use only with adequate ventilation.

### Section Nine: Physical and Chemical Properties

Boiling Point: 133F (Acetone) Melting Point: -140F (Acetone)

Vapor Pressure: 180 mm Hg (Acetone) Specific Gravity: 0.87

February 19, 2007



A Newell/Rubbermaid Company

## MATERIAL SAFETY DATA SHEET

MSDS # 543-549

Specific Vapor Density: Heavier than air      Evaporation Rate: >1  
 Solubility in Water: Slight      Reactivity in Water: Non-reactive  
 Appearance and Odor: Clear liquid, characteristic odor

### Section Ten: Stability and Reactivity

Stability: Stable

Conditions to Avoid: Ignition sources or excessive heat

Chemical Incompatibility: Nitric plus acetic acids, nitric plus sulfuric acid, amines, strong oxidizing agents

Hazardous Decomposition: Carbon monoxide, carbon dioxide

Hazardous Polymerization: Will not occur



A *NewellRubbermaid* Company

**MATERIAL SAFETY DATA SHEET**

**MSDS # 543-549**

**Section Eleven: Toxicological Information**

IARC Monographs: No

National Toxicology Program: No

OSHA Regulated: No

Effects/Symptoms of Acute Exposure: If cross-ventilation is not adequate, eye watering, headache, nausea, dizziness, and loss of coordination may occur. Deliberate inhalation may be harmful or fatal.

Effects/Symptoms of Chronic Exposure: Repeated and prolonged overexposure may lead to permanent brain damage and nervous system damage.

Medical Conditions Usually Aggravated By Overexposure of This Product: Unknown

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Do not incinerate closed or empty containers. Dispose in accordance with Federal, State, and Local Regulations.

**Section Fourteen: Transport Information**

DOT: ORM-D Consumer Commodity

IATA: Consumer Commodity, 9, ID8000, packing instruction 910

IMO: Aerosols, Class 2.1, UN1950 Limited Quantities, EmS# 2-13

**Section Fifteen: Regulatory Information**

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency's Toxic Substances Control Act Inventory. However, all components used in the manufacture of this product are included in the TSCA Inventory.

**Section Sixteen: Other Information**

February 19, 2007

Page 5 of 6

**MATERIAL SAFETY DATA SHEET**



*A Newell/Rubbermaid Company*

**MSDS # 543-549**

HMIS Code	
Health	2
Flammability	4
Reactivity	0
Personal Protection	1

Sanford Corporation is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.