

05/15/2006 16:03 6507378887

YASUTOMO AND COMPANY

PAGE 03/07

21911-0129  
- 0249  
- 0349

**MATERIAL SAFETY DATA SHEET**

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200 ~ Standard must be consulted for specific requirements

U.S. DEPARTMENT OF LABOR  
OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION  
(Non Mandatory Form) FORM APPROVED  
OMB No. 1218-0072

IDENTITY: (As used on Label & List) **NIJI OIL PASTEL: NOP 12, 24, 36** NOTE: Blank spaces are not permitted. If any items are not applicable, or no information is available, the space must be marked to indicate that N/A

**SECTION I**

MANUFACTURER'S NAME: **YASUTOMO & COMPANY**  
ADDRESS (Number, Street, City, State & Zip): **490 ECCLES AVENUE  
SOUTH SAN FRANCISCO, CA 94080**

EMERGENCY PHONE NUMBER: \_\_\_\_\_  
CALL YOUR LOCAL POISON CONTROL CENTER  
INFORMATION NUMBER: **650-737-8888**  
DATE PREPARED: **updated: MAY 10, 2006**  
SIGNATURE OF PREPARED (optional): \_\_\_\_\_

**SECTION II - HAZARDOUS INGREDIENTS / IDENTIFY INFORMATION**

HAZARDOUS COMPONENTS (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (OPTIONAL)
<b>N/A HAZARDOUS MATERIALS.</b>				

**SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS**

BOILING POINT: <b>N/A</b>	SPECIFIC GRAVITY (H <sub>2</sub> O = 1): <b>N/A</b>
VAPOR PRESSURE (mm Hg): <b>N/A</b>	MELTING POINT: <b>N/A</b>
VAPOR DENSITY (AIR = 1): <b>N/A</b>	EVAPORATION RATE: (butyl acetate = 1): <b>N/A</b>
SOLUBILITY IN WATER: <b>N/A</b>	
APPEARANCE & ODOOR: <b>NONE</b>	

**SECTION IV - FIRE & EXPLOSION HAZARD DATA**

FLASH POINT (Method Used): <b>N/A</b>	FLAMMABLE LIMITS: <b>N/A</b>	LEL: _____	UEL: _____
EXTINGUISHING MEDIA: <b>N/A</b>			
SPECIAL FIRE FIGHTING PROCEDURES: <b>NONE</b>			
USUAL FIRE & EXPLOSION HAZARDS: <b>NONE</b>			

**SECTION V - REACTIVITY DATA**

STABILITY: <b>UNSTABLE</b>	CONDITIONS TO AVOID: <b>NONE</b>
<b>STABLE</b>	

INCOMPATIBILITY (Materials to Avoid): \_\_\_\_\_

