

SEP 26 '01 10:26 FR BEMIS-JR TO 18006218293 P.02/02
Oct 25 00 06:04p P.1



This is not a MSDS Sheet.
This is an informational sheet per Sonya - Bemis - Jason Corp.

Rec'd 9-26-01 ✓

PROTECTO FILM
CLEAR SELF ADHESIVE VINYL

ADHESIVE QUALITIES

Adhesive is recommended for clean, smooth, sealed surfaces. Results may vary for rough surfaces, fibrous surfaces, cloth, uncoated paper and drywall.

Repositionable during application, i.e.: can be lifted, smoothed etc. This applies to any clean, smooth, sealed surface including coated paper. Uncoated paper may tear or mar if product is repositioned during application.

After final application adhesive strength will increase creating a permanent bond, i.e.: adhesive film will not generally release unless it's intentionally peeled off.

After final application, product will not slip or shift.

Product should be applied at normal room temperature. Bond strength is not affected within a reasonable temperature range (20° - 115°)

Adhesive is designed to inhibit yellowing and "clouding" over time. Not recommended for exposure to direct sunlight.

FILM DESCRIPTION

Transparent, Polyvinylchloride (PVC), Matt finished film

FILM QUALITIES

After application, film surface can be wiped clean with warm water. Not recommended for dishwasher, washing machine, or household cleaners.

PVC Film does have memory. Rolling, folding etc., may result in permanent creases.

PVC Film inhibits yellowing over time. Not recommended for outdoor use or exposure to sunlight.

V-420