

## E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE

Page 1 of 9

23720-1350



# Material Safety Data Sheet

## 1. Chemical Product and Company Identification

DESCRIPTION: ELMER'S EXTRA STRENGTH SPRAY ADHESIVE  
 PRODUCT TYPE: RUBBER BASED ADHESIVE  
 APPLICATION: E-456

### • Manufacturer/Supplier Information

MSDS Prepared by:  
 Elmer's Products, Inc.  
 1 Easton Oval  
 Columbus, OH 43219  
 For additional health, safety or regulatory information, call 888-435-6377.  
 Call 1-800-848-9400 to place an order or request additional MSDSs.

Emergency Phone Number  
 Poison Control Center  
 888-516-2502

## 2. Composition, Information on Ingredients

The ingredients listed below have been associated with one or more immediate and/or delayed(\*) health hazards. Risk of damage and effects depends upon duration and level of exposure. BEFORE USING, HANDLING, OR EXPOSURE TO THESE INGREDIENTS, READ AND UNDERSTAND THE MSDS.

	% by weight
67-64-1 *Acetone	10-30
74-98-6 Propane	10-30
75-28-5 Isobutane	10-30
107-83-5 2-Methylpentane	30-50
109-66-0 Pentane	1-5
115-10-6 Dimethyl Ether	1-5

## 3. Hazards Identification

### 3.1 Emergency Overview



**E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE**

Page 3 of 9

**• Delayed Hazards**

Acetone 67-64-1

Ingestion may cause liver damage.

Ingestion may cause kidney damage.

-- See Footnote C.

Footnote C: As of the date of issuance of this document, this material has not been listed by NTP, classified by IARC nor regulated by OSHA as a carcinogen.

**4. First Aid Measures**

**INGESTION:** If accidentally swallowed, dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.

**INHALATION:** If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Call a physician.

**SKIN:** Flush with plenty of water. Remove contaminated clothing. Call a physician if irritation persists.

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held apart during irrigation to insure water contact with entire surface of eyes and lids. Call a physician.

**5. Fire Fighting Measures**

Autoignition Temperature	Not available
Upper/Lower Flammable Limits	Not available
Up/Lower Explosive Limits, % by Vol	18/1
Flash Point	-156 deg F (pensky-martens c.c.)

**EXTREMELY FLAMMABLE.**  
DO NOT INCINERATE (BURN) CONTAINER. AVOID HEAT. KEEP CONTAINER BELOW 120 F (50 C). High temperatures may cause bursting. Do not place container on radiator, stove, in direct sunlight or near other heat sources. DO NOT PUNCTURE CONTAINER. Contents under pressure will discharge. AVOID OPEN FLAMES, SPARKS, PILOT LIGHTS. DO NOT SMOKE. Vapor may ignite explosively. Spray mist or vapor evaporating from a deposited film is heavier than air and may settle in low places or travel outward to a source of ignition and flashback. In case of fire, use dry chemical, foam or CO2. Water may be ineffective, but should be used to keep fire-exposed containers cool.

**6. Accidental Release Measures**

Eliminate all ignition sources. Soak up with absorbent material and remove to a chemical disposal area. Prevent entry into natural bodies of water.

---

**E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE**

Page 4 of 9

**7. Handling and Storage**

---

**7.1 Handling**

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing.

Wash thoroughly after handling. Always use appropriate Personal Protective Equipment (PPE).

**INHALATION:** USE WITH ADEQUATE VENTILATION. To avoid breathing vapors or spray mist, open windows and doors or use other means, such as an exhaust fan to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC23C or equivalent), or leave the area.

**SKIN:** Avoid contact with skin and clothing.

**EYES:** Avoid contact with eyes.

---

**7.2 Storage**

Store in a cool, well-ventilated area.

Store in cool, dry area away from sun, heat, oxidizing materials and alkaline materials.

Keep containers tightly closed.

Do not store at temperatures above 50 C.

Keep away from heat, sparks, flame and other ignition sources.

---

**8. Exposure Controls/Personal Protection**

---

**8.1 Exposure Controls**

**ENGINEERING CONTROLS:** The following exposure control techniques may be used to effectively minimize employee exposure: local exhaust ventilation, enclosed system design, process isolation and remote control in combination with appropriate use of personal protective equipment and prudent work practices. These techniques may not necessarily address all issues pertaining to your operations. We, therefore, recommend that you consult with experts of your choice to determine whether or not your programs are adequate.

If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

---

## E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE

Page 5 of 9

**8.2 Personal Protection**

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance with OSHA laws and regulations or other applicable standards or guidelines, including ANSI standards regarding respiratory protection. Use goggles if contact is likely. Wear impervious gloves as required to prevent skin contact.

**8.3 Exposure Guidelines**

Acetone 67-64-1  
 ACGIH TLV: 500 ppm (1188 mg/m<sup>3</sup>) TWA; 750 ppm (1782 mg/m<sup>3</sup>) STEL  
 OSHA PEL: 1000 ppm (2400 mg/m<sup>3</sup>) TWA  
 REMANDED PEL: 750 ppm (1800 mg/m<sup>3</sup>) TWA; 1000 ppm (2400 mg/m<sup>3</sup>) STEL  
 OSHA 1989 PEL remanded, but in effect in some states

Propane 74-98-6  
 ACGIH TLV: 2500 ppm (4508 mg/m<sup>3</sup>) TWA  
 OSHA PEL: 1000 ppm (1800 mg/m<sup>3</sup>) TWA

Isobutane 75-28-5  
 ACGIH TLV: NONE ESTABLISHED  
 OSHA PEL: NONE ESTABLISHED

2-Methylpentane 107-83-5  
 ACGIH TLV: HexIso.500ppm(1760mg/m<sup>3</sup>)TWA;1000ppm(3500mg/m<sup>3</sup>)STEL  
 OSHA PEL: REMANDED PEL: HexIso.500ppm(1800mg/m<sup>3</sup>)TWA;1000ppm(3600mg/m<sup>3</sup>)STEL  
 OSHA 1989 PEL remanded, but in effect in some states

Pentane 109-66-0  
 ACGIH TLV: 600 ppm (1770 mg/m<sup>3</sup>) TWA  
 OSHA PEL: 1000 ppm (2950 mg/m<sup>3</sup>) TWA  
 REMANDED PEL: 600 ppm (1800 mg/m<sup>3</sup>) TWA; 750 ppm (2250 mg/m<sup>3</sup>) STEL  
 OSHA 1989 PEL remanded, but in effect in some states

Dimethyl Ether 115-10-6  
 ACGIH TLV: NONE ESTABLISHED  
 OSHA PEL: NONE ESTABLISHED

**9. Physical and Chemical Properties**

Percent Volatiles	80.5
pH @ 25 C	Not available
Specific Gravity	0.6937
Appearance	White liquid
Autoignition Temperature	Not available
Boiling Point	66 deg C
Vapor Density (Air=1)	> 1
Vapor Pressure, mm Hg @ 20 C	Not determined
Evaporation Rate (Butyl Acetate=1)	> 1
Upper/Lower Flammable Limits	Not available
Up/Lower Explosive Limits, % by Vol	18/1
Flash Point	-156 deg F (pensky-martens c.c.)
Freezing Point	Not available
Odor	Mint when wet
Odor Threshold, ppm	Not available



**E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE**

Page 7 of 9

LC50: Not available  
LD50: Not available  
Pentane 109-66-0  
LC50: Not available  
LD50: Not available  
Dimethyl Ether 115-10-6  
LC50: Not available  
LD50: Not available

---

**12. Ecological Information**

Not determined.

---

**13. Disposal Considerations**

Dispose of according to local, state/provincial, and federal requirements.  
Empty container: May contain explosive vapors. DO NOT cut, puncture or weld on or nearby. Incineration will cause container to burst violently.

---

**14. Transport Information**

---

**14.1 U.S. Department of Transportation (DOT)**

The data provided in this section is for information only and may not be specific to your package size. You will need to apply the appropriate regulations to properly classify your shipment for transportation.  
ORM-D Consumer Commodity.

---

**14.2 Canadian Transportation of Dangerous Goods (TDG)**

Not determined.

---

**15. Regulatory Information (Selected Regulations)**

---

**15.1 U.S. Federal Regulations**

---

**E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE**

Page 8 of 9

---

- **OSHA Hazard Communication Standard 29CFR1910.1200**

This material is a "health hazard" and/or a "physical hazard" as determined when reviewed according to the requirements of the Occupational Safety and Health Administration 29 CFR Part 1910.1200 "Hazard Communication" Standard.

---

- **SARA Title III: Section 311/312**

Fire hazard  
Sudden release of pressure (explosion) hazard  
Immediate health hazard  
Delayed health hazard

---

- **SARA Title III Section 313 and 40 CFR Part 372**

This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.  
None required per SARA TITLE III SECTION 313.

---

- **TSCA Section 8(b) Inventory**

All reportable chemical substances are listed on the TSCA Inventory. We rely on certifications of compliance from our suppliers for chemical substances not manufactured by us.

---

**15.2 Canadian Regulations**

---

- **Workplace Hazardous Materials Information System (WHMIS)**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR.

CLASS D, DIV 2B  
CLASS B, DIV 5  
CLASS A

---

## E456 ELMER'S EXTRA STRENGTH SPRAY ADHESIVE

Page 9 of 9

- **Canadian Environmental Protection Act (CEPA)**

All reportable chemical substances are listed on the Domestic Substances List (DSL) or otherwise comply with CEPA new substance notification requirements.

---

- **National Pollutant Release Inventory (NPRI)**

This product contains the following chemical(s) subject to the reporting requirements of the Canadian Environmental Protection Act (CEPA) subsection 16(1), National Pollutant Release Inventory. None required.

---

## 16. Other Information

CL (Cautionary Labeling): Products bearing the CL (Cautionary Labeling) Seal of The Art & Creative Materials Institute, Inc. (ACMI) are certified to be properly labeled in a program of toxicological evaluation by a medical expert. This program is reviewed by ACMI's Toxicological Advisory Board. These products are certified by ACMI to be labeled in accordance with the chronic hazard labeling standard, ASTM D-4236 and Federal Law, P.L. 100-695.

---

- **User's Responsibility**

The OSHA Hazard Communication Standard 29CFR 1910.1200 and the Workplace Hazardous Materials Information System (WHMIS) require that the information contained on these sheets be made available to your workers. Educate and train your workers regarding OSHA and WHMIS precautions. Instruct your workers to handle this product properly. Consult with appropriate experts to guard against hazards associated with use of this product and its ingredients.

---

- **Disclaimer**

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE, except that the product shall conform to contracted specifications, and that the product does not infringe any valid United States or Canadian patent. No claim of any kind shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

---

CURRENT ISSUE: 07-DEC-06  
PREVIOUS ISSUE: 18-MAY-06