

May 05 2006 1:11PM HP LASERJET 3200

p. 3

25327-XXXX

TOTALLY TATTOO BODY PAINT**MATERIAL SAFETY DATA SHEET****STATEMENT OF HAZARDOUS NATURE**

Classified as hazardous according to the criteria of Worksafe Australia

COMPANY DETAILS

Company: BADGER AIR-BRUSH CO.
 Address: 9128 W. BELMONT AVE
 Fax Number: 847-671-4352
 Telephone Number: 847-671-4352

IDENTIFICATION

Product Name: Airbrush Ink (Assorted Colours)
 For use on skin as a temporary tattoo.

UN Number: None Allocated
Hazchem Code: None Allocated
Dangerous Goods
Class and Sub-risk: 3
Poisons Schedule: 5
Packing Group: II

Physical Description/Properties

Appearance: Coloured liquid with a thick density of various colours
Flash Point (°C): 15.5
Boiling Point: 78.3°
Specific Gravity: ~0.8
pH: Not pertinent
Vapour Density: >1

Solubility (Water): Miscible
Vapour Pressure: ~44mmHg
Volatiles: 100
Melting Point: -117.3°C

Ingredients

Chemical Entity:
 Ethyl Cellulose
 Water
 Castor Oil
 Dewaxed Shellac
 Pigment
 Sucrose Acetate Isobutyrate
 Ethyl Alcohol

Cas No:
 9004-57-3
 7732-18-5
 8001-79-4
 9000-14-0
 Various
 34482-63-8
 64-17-5

Made with FDA approved ingredients

May 05 2006 1:11PM HP LASERJET 3200

p. 4

HEALTH HAZARD INFORMATION**Acute Effects**

Ingestion: Irritating. May cause coughing, headache, dullness, abdominal spasm and diarrhoea.

Eye: Liquid and high vapour concentration are irritating and may cause watering of the eyes.

Inhalation: High vapour concentration can be irritating to eyes nose and throat.

Skin Reactions: No adverse reactions, redness, discoloration or allergic reactions known or reported for exposure during or after the 12 -72 hour tattoo period.

Advice to doctor: Treat Symptomatically

FIRST AID PROCEDURES

Ingestion: Rinse mouth out with water ensuring that mouth wash is not swallowed. Give about 250ml (2 glasses) of water to drink. Do not attempt to induce vomiting.

Eye: Hold eyelids open and rinse the eye continuously with a gentle stream of clean running water for at least 15 minutes.

Inhalation: Remove to fresh air. If breathing is laboured, hold in a half upright position (this assists respiration). Seek medical attention for all but most minor cases of over-exposure.

Skin & Allergic Reactions: Remove the tattoo with 70% isopropyl alcohol cleaning pad or cotton balls. For skin dryness apply non-allergenic moisturizing cream.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Engineering Controls: Ventilation requirements depend on the quantity of product in use and the method of application. Ventilation should be sufficient to maintain vapour levels below the appropriate exposure Standard. Use only in well ventilated areas unless forced air ventilation is employed, this is due to fire hazard as well as risks from inhalation. Local exhaust ventilation may be required.

Personal Protection: Requirements are dependent on working conditions, quantity of product in use and method of application. In confined or poorly ventilated areas use a face mask.

Flammability: Avoid all sources of ignition such as open flames, sparks, hot surfaces or burning cigarettes. The product may react with strong oxidising agents such as liquid or powdered chlorine.

Body Paint Use: Do not spray directly on eyes, nose, mouth, lips or ears. Not recommended for face painting.

SAFE HANDLING PROCEDURES

Storage: Store in a flammable liquids area: designated no smoking, away from all sources of ignition, out of direct sunlight in a cool well ventilated area. Protect containers against physical damage.

Spills and Disposals

Spills: Dam the spill. Cover with an absorbent such as earth, sand or a commercial oil absorber. Sweep up and collect in sealable containers. Dispose to approved land fill.

Disposal: Dispose to controlled waste management.

Fire/Explosion: Containers may explode if heated. If possible remove containers from vicinity of fire.

Otherwise keep containers as cool as possible by spraying with water, from a protected position.

Water is not effective for fire fighting. Extinguish using foam, powder (bicarbonate or ammonium phosphate based) or carbon dioxide.

May 05 2006 1:11PM HP LASERJET 3200

p. 5

OTHER INFORMATION**Contact Points**

Police and Fire Brigade

Dial

Australia

0 0 0

National Poisons Information Centre

Dial

13 1 126

Customer Service

Dial

(03) 9746 8055

This MSDS summarises to the best of our knowledge of the health and safety hazard information of our product in the workplace. Each user must review this MSDS in the context of how the product will be handled and used in the workplace, and the amounts that will be used. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company, so we can attempt to obtain additional information from our suppliers.