

01/22/2002 19:48 8159622037

TESTORS

PAGE 02/09

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

25330-XXXX

Telephone number:(815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: \*(800) 424-9300 Page 1 of 4
\*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 3/11/2005

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)
\*\*\*\*\*

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): Visions ColorArtz Water-Base Paint
(VP000-VP999, VM640-VM835, VA000)

(This MSDS covers all products listed on page 4.)

SECTION II - HAZARDOUS INGREDIENTS & COMPOSITION INFORMATION

Table with 5 columns: SPECIFIC CHEMICAL NAME, CAS #, % WT, OSHA PEL/TWA, ACGIH TLV/TWA. Rows include Ethylene Glycol Monobutyl Ether, Diethylene Glycol Monobutyl Ether, Butyl Benzyl Phthalate, and Carbon Black Pigment\*\*.

\*\* Contained at levels 0.1% or greater in products identified with a "+" on page 4.

Non-Hazardous and Other Not Avail. Balance
Ingredients Below Reportable Levels

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 to 455 deg.F SPECIFIC GRAVITY (Water=1): 1.132 (TYP)
GALLON WEIGHT OF VAPOR PRESSURE:19.1 mm Hg @ 20 deg.C (calc.)
PRODUCT (Lbs/Gal): 9.43 (TYP) VAPOR DENSITY: Lighter than air.
PERCENT VOLATILES EVAPORATION RATE: Slower than Ethyl Ether.
(By Volume): 72.9 (TYP)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): > 200 deg. F
OSHA FLAMMABILITY CLASSIFICATION: Combustible Liquid - CLASS IIIB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.1, UEL 12.5
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, dry chemical or water fog.
SPECIAL FIRE FIGHTING PROCEDURES: A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel to an ignition source and flash back. Overexposure to decomposition products may cause a health hazard.

01/22/2002 19:48

8159622037

TESTORS

PAGE 03/09

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: \*(800) 424-9300

Page 2 of 4

Date prepared: 3/11/2005

\*\*\*\*\*

Product Identity: Visions ColorArtz Water-Base Paint

SECTION V - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Contain spilled product by diking. Eliminate all possible ignition sources. Provide adequate ventilation. Equip emergency responders with appropriate personal protection equipment. Take up spill with an absorbent material and place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local, state, and federal regulations. Do not flush to sewer, watershed or waterway.

SECTION VI - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES\* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Causes irritation and pain, seen as excess tearing and blinking with marked excess redness and swelling of the conjunctiva.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis. May be absorbed through the skin.

BREATHING: Vapors or mist may cause irritation to the eyes and respiratory tract. High concentrations may cause headache, dizziness, nausea, vomiting and malaise.

SWALLOWING: May cause irritation of the gastrointestinal tract and may also cause effects resembling those from inhalation of vapor.

CHRONIC OVEREXPOSURE: Overexposures to Ethylene Glycol Monobutyl Ether and Diethylene Glycol Monobutyl Ether may cause secondary injury to the kidney and liver.

\*Products identified with a "+" on page 4 contain Carbon Black which is an IARC Group 2B-possible carcinogen.

SECTION VII EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Give no more than two (2) glasses of water and two (2) tablespoons of Syrup of Ipecac to induce vomiting. If victim is a child, give no more than one (1) glass of water and one (1) tablespoon of Syrup of Ipecac. Keep head below hips while vomiting.

01/22/2002 19:48 8159622037

TESTORS

PAGE 04/09

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number: \*(800) 424-9300

Page 3 of 4

Date prepared: 3/11/2005

\*\*\*\*\*

Product Identity: Visions ColorArtz Water-Base Paint

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable.

CONDITIONS TO AVOID: None.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents, and alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and/or carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors, mists and/or dusts. If exposure may or does exceed occupational exposure limits (Section II) use a NIOSH-approved respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air purifying respirator with appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s). Heavy solvent vapors should be removed from the lower levels of area, and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.  
Chemical Safety Shoes. Protective Clothing.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions. Do not get in eyes. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

This product is packaged and sold as a consumer good. This information is believed to be reliable and accurate, as of the date indicated. It is supplied on the condition that recipients will make their own determination as to its suitability and completeness for their purposes. The Testor Corporation assumes no responsibility for any damages resulting from reliance on this information.

01/22/2002 19:48 8159622037

TESTORS

PAGE 05/09

MATERIAL SAFETY DATA SHEET  
 THE TESTOR CORPORATION  
 440 BLACKHAWK PARK AVENUE  
 ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
 24 hour Chemtrec telephone number: \*(800) 424-9300

Page 4 of 4

Date prepared: 3/11/2005

\*\*\*\*\*

Product Identity: Visions ColorArtz Water-Base Paint

## Stock Numbers and Description

VP000 White  
 VP006 Eggshell  
 VP008 Bisque  
 VP021 Soft Yellow  
 VP045 Lemon Yellow  
 VP067 Saffron  
 VP126 Apricot  
 VP127 Peach  
 VP164 Orange  
 VP260 Holiday Red  
 VP266 Cinnabar  
 VP295 Barn Red  
 VP310 Misty Mauve  
 VP320 Dusty Rose  
 VP323 Mauve  
 VP361 Burgundy  
 VP364 Loganberry  
 VP363 Purple  
 VP415 Baby Blue  
 VP430 Blueberry  
 VP442 Williamsburg Blue  
 VP443 Cool Blue  
 VP480 Royal Blue  
 VP520 Turquoise  
 VP522 Aqua  
 VP524 Glen Green  
 VP570 Teal  
 VP577 Basil  
 VP584+ Pine Green  
 VP594 Irish Green  
 VP595 Holiday Green  
 VP619+ Raw Sienna  
 VP668+ Cinnamon  
 VP688+ Burnt Umber  
 VP833+ Slate Gray  
 VP999+ Black  
 VM630 Gold  
 VM640 Copper  
 VM835 Silver  
 VA000 Gloss

+ Products that contain Carbon Black 0.1% or greater.