

**25334-2009****25334-1083 -1089**~~1086~~~~-1087~~**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax**PRODUCT IDENTIFICATION**      **REVISION DATE: 04/30/09**

<b>IDENTITY: (As used on label)</b> Wicked Opaque White	<b>Synonyms:</b>
<b>Chemical family:</b> ---	<b>Formula</b>

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Colorless liquid, combustible, sweet ether odor

**Volatile Organic Compound**

<b>Paint 80%:</b> .92
<b>Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.53

- \*\*Paint can be sprayed without reduction
- \*\*Refer to Wicked Reducer MSDS

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable <b>Conditions to avoid:</b> extreme temperatures, open flames
<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored

properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    Conditions to avoid: None

### HEALTH INFORMATION

**Primary Route of Exposure:**  
 Inhalation:                      Skin: X                                      Ingestion:                                      Eyes:

**Carcinogen:**                      IARC: no                                      NTP: no                                      OSHA: no

**Signs and Symptoms of Exposure:**  
 none found

**Medical Conditions Generally Aggravated by Exposure:**  
 none found

**Emergency and First Aid Procedures:**  
Eye Contact, remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.  
Ingestion, If victim is conscious give water, *do not* induce vomiting. Call physician.

### SPECIAL PROTECTION DATA

**Respiratory Protection:**  
 Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.

**Ventilation:**  
 The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.

**Protective Gloves:**  
 Neoprene or rubber gloves with cuffs

**Other Protective Clothing:**  
 Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

**Steps to be taken in case of material spill:**  
 COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

**Storing/Handling:**  
 Store in tightly closed containers in a cool, well-ventilated area.

**Waste Disposal Method:**  
 Sanitary landfill in accordance with local, state, and federal regulations.

**Other Precautions:**  
 None

25334-2023 -2029

-2026

-2027

## MATERIAL SAFETY DATA SHEET

CREATEX  
COLORS14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax

## PRODUCT IDENTIFICATION REVISION DATE: 9/30/08

IDENTITY: (As used on label) Wicked Colors Black	Synonyms:
Chemical family: Acrylic	Formula Acrylic Polymer/ Organic Pigments

## HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

## PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 408°F (209° C)
Solubility in water: Appreciable (>20%)
Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C
Vapor density: (Air=1) 6.6
Specific Gravity (H <sub>2</sub> O=1): (Water=1) 0.972
Evaporation Rate: (BuAct=1): .07
Appearance and Odor: Colorless liquid, combustible, sweet ether odor

## Volatile Organic Compound

*Paint 80%: .91
**Wicked Reducer 20% : .61
Combined VOC: 1.52

\*Paint can be sprayed without reduction  
 \*\*Refer to Wicked Reducer MSDS

## FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat

## REACTIVITY DATA

Stability: ( X ) Stable      ( ) Unstable      Conditions to avoid: extreme temperatures, open flames
Incompatibility (materials to avoid) : strong oxidizers, strong acids
Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    Conditions to avoid: None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
Inhalation:	Skin: X	Ingestion:	Eyes:
<b>Carcinogen:</b>	IARC: no	NTP: no	OSHA: no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> . If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

25334-4013 -4019

-4016

-4017

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax**PRODUCT IDENTIFICATION REVISION DATE: 9/30/08**

<b>IDENTITY: (As used on label)</b> Wicked Colors Yellow	<b>Synonyms:</b>
<b>Chemical family:</b> Acrylic	<b>Formula</b> Acrylic Polymer/ Organic Pigments

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Colorless liquid, combustible, sweet ether odor

**Volatile Organic Compound**

<b>*Paint 80%:</b> .50
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.11

\*Paint can be sprayed without reduction  
\*\*Refer to Wicked Reducer MSDS

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable <b>Conditions to avoid:</b> extreme temperatures, open flames
<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    Conditions to avoid: None

### HEALTH INFORMATION

**Primary Route of Exposure:**  
 Inhalation:                      Skin: X                                      Ingestion:                                      Eyes:

**Carcinogen:**                      IARC: no                                      NTP: no                                      OSHA: no

**Signs and Symptoms of Exposure:**  
 none found

**Medical Conditions Generally Aggravated by Exposure:**  
 none found

**Emergency and First Aid Procedures:**  
Eye Contact, remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.  
Ingestion, If victim is conscious give water, *do not* induce vomiting. Call physician.

### SPECIAL PROTECTION DATA

**Respiratory Protection:**  
 Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.

**Ventilation:**  
 The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.

**Protective Gloves:**  
 Neoprene or rubber gloves with cuffs

**Other Protective Clothing:**  
 Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

**Steps to be taken in case of material spill:**  
 COMBUSTIBLE-Evacuate and ventilate area; remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

**Storing/Handling:**  
 Store in tightly closed containers in a cool, well-ventilated area.

**Waste Disposal Method:**  
 Sanitary landfill in accordance with local, state, and federal regulations.

**Other Precautions:**  
 None

**25334-3013 -3019****-3016****-3017****MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax**PRODUCT IDENTIFICATION REVISION DATE: 9/30/08**

<b>IDENTITY: (As used on label)</b> Wicked Colors Red	<b>Synonyms:</b>
<b>Chemical family:</b> Acrylic	<b>Formula</b> Acrylic Polymer/ Organic Pigments

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Colorless liquid, combustible, sweet ether odor

**Volatile Organic Compound**

<b>*Paint 80%:</b> .46
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.07

\*Paint can be sprayed without reduction  
 \*\*Refer to Wicked Reducer MSDS

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable      Conditions to avoid: extreme temperatures, open flames
<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    Conditions to avoid: None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
Inhalation:	Skin: X	Ingestion:	Eyes:
<b>Carcinogen:</b>	IARC: no	NTP: no	OSHA: no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area; remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

25334-5013 -5019  
-5016  
-5017

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**

14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax

**PRODUCT IDENTIFICATION REVISION DATE: 9/30/08**

<b>IDENTITY: (As used on label)</b> Wicked Colors Blue	<b>Synonyms:</b>
<b>Chemical family:</b> Acrylic	<b>Formula</b> Acrylic Polymer/ Organic Pigments

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	<.05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Colorless liquid, combustible, sweet ether odor

**Volatile Organic Compound**

<b>*Paint 80%:</b> .40
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.01
*Paint can be sprayed without reduction
**Refer to Wicked Reducer MSDS

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable <b>Conditions to avoid:</b> extreme temperatures, open flames
<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    Conditions to avoid: None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
Inhalation:	Skin: X	Ingestion:	Eyes:
<b>Carcinogen:</b>	IARC: no	NTP: no	OSHA: no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs.
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area; remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

## MATERIAL SAFETY DATA SHEET



25334-1003 -1007
-1004 -1009
-1006

14 Airport Park road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax

## PRODUCT IDENTIFICATION REVISION DATE: 9/30/08

IDENTITY: (As used on label)	Synonyms:
Wicked Colors Reducer	
Chemical family:	Formula

## HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

## PHYSICAL/CHEMICAL CHARACTERISTICS

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Colorless liquid, combustibles, sweet ether odor

## Volatile Organic Compound

<b>**Wicked Reducer at 20% reduction with Wicked Colors:</b> .61

\*\*Refer to Wicked Colors for combined VOC

## FIRE AND EXPLOSION HAZARD DATA

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

## REACTIVITY DATA

<b>Stability:</b> ( X ) Stable      ( ) Unstable      Conditions to avoid: extreme temperatures, open flames
<b>Incompatibility (materials to avoid):</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    **Conditions to avoid:** None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
Inhalation:	Skin: X	Ingestion:	Eyes:
<b>Carcinogen:</b>	IARC: no	NTP: no	OSHA: no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b> <u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. . wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area; remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None