

25334-5009

## MATERIAL SAFETY DATA SHEET

CREATEX  
COLORS14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax~~25334-3153  
3156  
3157  
3154~~

## PRODUCT IDENTIFICATION REVISION DATE: 09/01/09

IDENTITY: (As used on label)	Synonyms:
Wicked Colors Detail Carmine Item # W063	
Chemical family:	Formula
---	

## HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	<.05	150 PPM

## PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 408°F (209° C)
Solubility in water: Appreciable (>20%)
Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C
Vapor density: (Air=1) 6.6
Specific Gravity (H <sub>2</sub> O=1): (Water=1) 0.972
Evaporation Rate: (BuAct=1): .07
Appearance and Odor: Carmine colored liquid, combustible, sweet ether odor
Flash Point: 79° C / 174°F

## Volatile Organic Compound

*Paint 80%: .92
**Wicked Reducer 20% : .61
Combined VOC: 1.53

\*Paint can be sprayed without reduction  
 \*\*Refer to Wicked Colors for combined VOC

## FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat

## REACTIVITY DATA

Stability: (X) Stable ( ) Unstable Conditions to avoid: extreme temperatures, open flames
--

<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.
<b>Hazardous Polymerization:</b> ( ) may occur (X) will not occur <b>Conditions to avoid:</b> None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
<b>Inhalation:</b>	<b>Skin:</b> X	<b>Ingestion:</b>	<b>Eyes:</b>
<b>Carcinogen:</b>	<b>IARC:</b> no	<b>NTP:</b> no	<b>OSHA:</b> no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

<b>25334-6523</b>	<b>-6527</b>
<b>-6526</b>	<b>-6529</b>

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**

14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax

**PRODUCT IDENTIFICATION**      **REVISION DATE: 09/01/09**

IDENTITY: (As used on label)	Synonyms:
Wicked Colors Detail Violet Item # W055	
Chemical family:	Formula
---	

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Violet liquid, combustible, sweet ether odor
<b>Flash Point:</b> 79° C / 174°F

**Volatile Organic Compound**

<b>*Paint 80%:</b> .92
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.53

- \*Paint can be sprayed without reduction  
\*\*Refer to Wicked Colors for combined VOC

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable      Conditions to avoid: extreme temperatures, open flames
---

<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.
<b>Hazardous Polymerization:</b> ( ) may occur (X) will not occur      Conditions to avoid: None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
<b>Inhalation:</b>	<b>Skin:</b> X	<b>Ingestion:</b>	<b>Eyes:</b>
<b>Carcinogen:</b>	<b>IARC:</b> no	<b>NTP:</b> no	<b>OSHA:</b> no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

**25334-7523 -7527**  
**-7226 -7529**

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**

14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax

**PRODUCT IDENTIFICATION      REVISION DATE: 09/01/09**

IDENTITY: (As used on label)	Synonyms:
Wicked Colors Detail Moss Green Item # W059	
Chemical family:	Formula
---	

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Moss Green liquid, combustible, sweet ether odor
<b>Flash Point:</b> 79° C / 174°F

**Volatile Organic Compound**

<b>*Paint 80%:</b> .92
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.53

- \*Paint can be sprayed without reduction
- \*\*Refer to Wicked Colors for combined VOC

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable      Conditions to avoid: extreme temperatures, open flames
---

<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.
<b>Hazardous Polymerization:</b> ( ) may occur (X) will not occur      Conditions to avoid: None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
<b>Inhalation:</b>	<b>Skin:</b> X	<b>Ingestion:</b>	<b>Eyes:</b>
<b>Carcinogen:</b>	<b>IARC:</b> no	<b>NTP:</b> no	<b>OSHA:</b> no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

25334-2643 -2647

-2646 -2649

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax**PRODUCT IDENTIFICATION**      **REVISION DATE: 09/01/09**

IDENTITY: (As used on label)	Synonyms:
Wicked Colors Detail Smoke Black Item # W072	
Chemical family:	Formula
---	

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Black colored liquid, combustible, sweet ether odor
<b>Flash Point:</b> 79° C / 174°F

**Volatile Organic Compound**

<b>*Paint 80%:</b> .92
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.53

- \*Paint can be sprayed without reduction
- \*\*Refer to Wicked Colors for combined VOC

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable <b>Conditions to avoid:</b> extreme temperatures, open flames
---

<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.
<b>Hazardous Polymerization:</b> ( ) may occur (X) will not occur <b>Conditions to avoid:</b> None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
<b>Inhalation:</b>	<b>Skin:</b> X	<b>Ingestion:</b>	<b>Eyes:</b>
<b>Carcinogen:</b>	<b>IARC:</b> no	<b>NTP:</b> no	<b>OSHA:</b> no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<b>Eye Contact,</b> remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<b>Ingestion,</b> If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

25334-1003 -1007

-1004 -1009

-1006

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**14 Airport Park road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax**PRODUCT IDENTIFICATION REVISION DATE: 9/30/08**

<b>IDENTITY:</b> (As used on label)	<b>Synonyms:</b>
Wicked Colors Reducer	
<b>Chemical family:</b>	<b>Formula</b>

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O=1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Colorless liquid, combustible, sweet ether odor

**Volatile Organic Compound**

<b>**Wicked Reducer at 20% reduction with Wicked Colors:</b> .61

\*\*Refer to Wicked Colors for combined VOC

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable <b>Conditions to avoid:</b> extreme temperatures, open flames
<b>Incompatibility (materials to avoid) :</b> strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

**Hazardous Polymerization:**  
 may occur     will not occur    Conditions to avoid: None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b>			
Inhalation:	Skin: X	Ingestion:	Eyes:
<b>Carcinogen:</b>	IARC: no	NTP: no	OSHA: no
<b>Signs and Symptoms of Exposure:</b> none found			
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found			
<b>Emergency and First Aid Procedures:</b>			
<u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists.			
<u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations.
<b>Other Precautions:</b> None

**MATERIAL SAFETY DATA SHEET****CREATEX  
COLORS**14 Airport Park Road  
P.O. Box 120  
East Granby, CT. 06026  
(860) 653-5505  
(860) 653-0643 fax**PRODUCT IDENTIFICATION****REVISION DATE: 09/01/09**

IDENTITY: (As used on label)	Synonyms:
Wicked Colors Detail Driscoll Tone Item # W073	
Chemical family: ---	Formula

**HAZARDOUS INGREDIENTS**

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

**PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling /melting point:</b> 408°F (209° C)
<b>Solubility in water:</b> Appreciable (>20%)
<b>Vapor pressure (mm Hg):</b> <0.2 mm Hg @ 20° C
<b>Vapor density: (Air=1)</b> 6.6
<b>Specific Gravity (H<sub>2</sub>O-1): (Water=1)</b> 0.972
<b>Evaporation Rate: (BuAct=1):</b> .07
<b>Appearance and Odor:</b> Tone colored liquid, combustible, sweet ether odor
<b>Flash Point:</b> 79° C / 174°F

**Volatile Organic Compound**

<b>*Paint 80%:</b> .92
<b>**Wicked Reducer 20% :</b> .61
<b>Combined VOC:</b> 1.53

\*Paint can be sprayed without reduction

\*\*Refer to Wicked Colors for combined VOC

**FIRE AND EXPLOSION HAZARD DATA**

<b>Extinguisher Media:</b> Water, CO <sub>2</sub> foam, water fog, dry chemical, chemical foam
<b>Fire fighting Procedures:</b> Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
<b>Unusual Fire and Explosion Hazards:</b> Closed containers can explode due to buildup of pressure when exposed to extreme heat

**REACTIVITY DATA**

<b>Stability:</b> ( X ) Stable      ( ) Unstable      Conditions to avoid: extreme temperatures, open flames
---

<b>Incompatibility (materials to avoid)</b> : strong oxidizers, strong acids
<b>Hazardous Decomposition or Byproducts:</b> Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.
<b>Hazardous Polymerization:</b> ( ) may occur (X) will not occur <b>Conditions to avoid:</b> None

### HEALTH INFORMATION

<b>Primary Route of Exposure:</b> Inhalation:                      Skin: X                                      Ingestion:                                      Eyes:
<b>Carcinogen:</b> IARC: no                                      NTP: no                                      OSHA: no
<b>Signs and Symptoms of Exposure:</b> none found
<b>Medical Conditions Generally Aggravated by Exposure:</b> none found
<b>Emergency and First Aid Procedures:</b> <u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.

### SPECIAL PROTECTION DATA

<b>Respiratory Protection:</b> Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
<b>Ventilation:</b> The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
<b>Protective Gloves:</b> Neoprene or rubber gloves with cuffs
<b>Other Protective Clothing:</b> Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

### SPILL AND LEAK PROCEDURES

<b>Steps to be taken in case of material spill:</b> COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
<b>Storing/Handling:</b> Store in tightly closed containers in a cool, well-ventilated area.
<b>Waste Disposal Method:</b> Sanitary landfill in accordance with local, state, and federal regulations. <b>Other Precautions:</b> None