

Jan 23 02 05:36p

Caldex Enterprises

303 323 1185

P.L.

27013-8119

* Revd 1-23-02 MATERIAL SAFETY DATA SHEET (Old World Copper Leaf Kit)

Product: 812, 814 Composition Gold Leaf; 812B, 814B Black Variegated Gold Leaf; 812H 814H Blue Variegated Gold Leaf; 812K 814K Red Variegated Gold Leaf; *812C, 814C Composition Copper Leaf*

SECTION I -- SUPPLIER INFORMATION

Importer : OLD WORLD ART
 Address : 1953 SOUTH LAKE PLACE
 City, St, Zip : ONTARIO, CA 91761
 Phone : (909)947-4928 (909)917-9945 FAX(909)923 1185

SECTION II -- HAZARDOUS INGREDIENT INFORMATION

Ingredient	% Wt.	PEL-OSHA	TLV-ACGIH
COPPER	85±2	1 MG/M ³	1 MG/M ³
ZINC	15±2	NOT ESTABLISHED	5 MG/M ³

SECTION III -- PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor : EXTREMELY THIN COPPER ALLOY SHEET
 Boiling Point : 3,270°F
 Specific Gravity (Water = 1) : 8.7
 Vapor Density (Air = 1) : HEAVIER THAN AIR
 Evaporation Rate (Butyl Acetate = 1) : SLOWER THAN ETHER

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point : NOT ESTABLISHED
 Flammable Limits : NOT ESTABLISHED
 Extinguishing Media : DRY CHEMICAL

Special Fire Fighting Procedures: DO NOT USE WATER ON THIS PRODUCT. USE ONLY AN NFPA CLASS-D FIRE EXTINGUISHER CONTAINING DRY CHEMICAL

Unusual Fire & Explosion Hazards: THIS PRODUCT CONTAINS BRASS SHEETS WHICH IS AN ALLOY OF COPPER AND ZINC. SINCE IT CONTAINS ZINC, MAY REACT WITH WATER TO LIBERATE HYDROGEN GAS WHICH WILL SPREAD THE FIRE.

SECTION V -- REACTIVITY DATA

Stability : STABLE
 Conditions to Avoid : AVOID CONTACT WITH MINERAL ACIDS AND STRONG OXIDIZING AGENTS
 Incompatibility : MINERAL ACIDS AND OTHER COPPER/ZINC REACTIVE AGENTS
 Hazardous Polymerization : WILL NOT OCCUR

SECTION VI -- HEALTH HAZARD DATA

Carcinogenicity : NTP NO IARC-NO OSHA-NO

V-159

Jan 23 02 05:37p

Caldex Enterprises

909 929 1185

P. 3

*** NOTE *** COPPER/ZINC LEAF IS NOT EASILY INHALED OR INGESTED. WHILE USING THE PRODUCT, SMALL PIECES ARE LOOSENED. HEALTH INFORMATION COULD NOT BE DETERMINED FOR METAL LEAFING. THE FOLLOWING INFORMATION IS FOR COPPER/ZINC ALLOY POWDER, WHICH IS MUCH SMALLER THAN WOULD BE ENCOUNTERED WITH LEAFING.

Chronic Health Hazards :CHRONIC TOXICITY IS CONFINED TO THOSE PERSONS SUFFERING FROM PRE-EXISTING WILSON'S DISEASE

Medical Conditions Generally Aggravated by Exposure :THE FOLLOWING CONDITIONS MAY BE AGGRAVATED BY EXPOSURE TO COPPER OR COPPER/ZINC ALLOY POWDER:

- (A) PERSONS AFFLICTED WITH CHRONIC RESPIRATORY DISEASE AND/OR IMPAIRED PULMONARY FUNCTIONS, ESPECIALLY THOSE WITH OBSTRUCTIVE AIRWAY DISEASES.
- (B) PERSONS AFFLICTED WITH PRE-EXISTING LIVER DISEASE.
- (C) PERSONS AFFLICTED WITH PRE-EXISTING KIDNEY DISEASE.
- (D) PERSONS AFFLICTED WITH PRE-EXISTING SKIN DISORDERS.
- (E) PERSONS AFFLICTED WITH PRE-EXISTING BLOOD DISORDERS.
- (F) PERSONS AFFLICTED WITH PRE-EXISTING WILSON'S DISEASE.

Effects of Over Exposure :COPPER METAL IS SLIGHTLY TOXIC. INHALATION OF COPPER OR COPPER/ZINC ALLOY POWDER MAY CAUSE ACUTE IRRITATION OF THE NOSE AND/OR TRACHEA; MAY PRODUCE ACUTE GASTROENTERIC SYMPTOMS RESULTING IN VOMITING AND/OR INFLAMMATION, AND/OR MAY CAUSE ACUTE METAL FUME FEVER. EXPOSURE OF SKIN TO COPPER OR COPPER ZINC ALLOY POWDER MAY CAUSE ACUTE DERMATITIS. IN THE CASE OF CHRONIC EXPOSURE, THE LIVER, KIDNEYS, AND/OR SPLEEN MAY BE INJURED, AND/OR ANEMIA MAY DEVELOP. CHRONIC TOXICITY IS CONFINED TO THOSE PERSONS SUFFERING FROM PRE-EXISTING WILSON'S DISEASE.

Emergency First Aid Procedures :

Eye Contact:FLUSH IMMEDIATELY WITH ADEQUATE AMOUNTS OF WATER FOR FIFTEEN (15) MINUTES, OCCASIONALLY LIFTING THE EYELIDS. CONSULT A PHYSICIAN, ESPECIALLY IF IRRITATION PERSISTS.

Skin Contact:REMOVE CONTAMINATED CLOTHING; LAUNDRER BEFORE RE-USE. WASH SKIN WITH MILD SOAP AND WATER; APPLY A GOOD QUALITY SKIN CREAM. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

Ingestion:DRINK SEVERAL GLASSES OF WATER AND CONSULT A PHYSICIAN. IF LARGE AMOUNTS ARE INGESTED, GET MEDICAL ASSISTANCE IMMEDIATELY.

Inhalation:REMOVE PERSON FROM CONTAMINATED AREA TO FRESH AIR. IF UNCONSCIOUS, KEEP BREATHING PASSAGE OPEN AND HAVE EMERGENCY MEDICAL ASSISTANCE SUMMONED IMMEDIATELY. IF BREATHING IS IRREGULAR OR HAS STOPPED, START RESUSCITATION IMMEDIATELY; ADMINISTER OXYGEN IF AVAILABLE, AND HAVE EMERGENCY MEDICAL ASSISTANCE SUMMONED IMMEDIATELY.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Waste Disposal:OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS. DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS, OR UNDERGROUND WATER SUPPLY.

Precautions to be taken in handling and storage:STORE IN A COOL DRY ENVIRONMENT.

Dec 14 01 10:19a

Caldex Enterprises

909 923 1185

P. 6

MATERIAL SAFETY DATA SHEET

Product: 802 Adhesive Size

SECTION I -- SUPPLIER INFORMATION

Manufacturer : Old World Art
 Address : 1953 South Lake Place
 City, St, Zip : Ontario, CA 91761
 Phone : (909)947-4928 (909)947-9945 Fax(909)923-1185
 Date : 02/27/1997

SECTION II -- HAZARDOUS INGREDIENT INFORMATION

Ingredient	% Wt.	Pel-OSHA	TLV-ACGIH
VINYL ACETATE-DIOCTYL MALEATE-2-ETHYLHEXYL ACRYLATE	31	NON HAZARDOUS	
PROPYLENE GLYCOL	2	NON HAZARDOUS	

SECTION III -- PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor : MILKY WHITE LIQUID
 Boiling Point : ABOUT 212 F
 Specific Gravity (Water=1) : ABOUT 1
 Melting Point : N/A
 Vapor Pressure : ABOUT SAME AS WATER
 Vapor Density (Air=1) : N/A
 Evaporation Rate (Butyl Acetate=1) : EQUAL TO WATER

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point : NON COMBUSTIBLE
 Flammable Limits : NA
 Extinguishing Media : EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE
 Special Fire Fighting Procedures: NA
 Unusual Fire & Explosion Hazards: BURNING WILL PRODUCE TOXIC FUMES

SECTION V -- REACTIVITY DATA

Stability : STABLE
 Conditions to Avoid : NONE
 Incompatibility : NA
 Hazardous Polymerization : BURNING WILL PRODUCE TOXIC FUMES

SECTION VI -- HEALTH HAZARD DATA

Carcinogenicity : NTP:NO IARC:NO NTP:NO
 Chronic Health Hazards : Refer to Effects of Overexposure
 Medical Conditions Generally Aggravated by Exposure : A review of available data does not identify any worsening of existing conditions not elsewhere mentioned in this MSDS.
 Effects of Over Exposure : LIQUID PRODUCT CONTACT MAY POSSIBLE CAUSE SOME SKIN AND EYE IRRITATION.

Dec 14 01 10:19a

Caldex Enterprises

909 923 1185

p. 7

Emergency First Aid Procedures :

Inhalation: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED.

Ingestion: INDUCE VOMITING IF VICTIM IS CONSCIOUS. CALL A PHYSICIAN.

Skin Contact: WASH SKIN WITH SOAP AND WATER.

Eye Contact: FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. CALL A PHYSICIAN IF IRRITATION PERSISTS.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Spill and Leak Procedure: FLUSH WITH PLENTY OF WATER AND COVER WITH INERT ABSORBENT MATERIAL AND REMOVE TO SUITABLE DISPOSAL CONTAINER.

Waste Disposal: OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS.

Precautions to be taken in handling and storage: PROTECT FROM EXTREME COLD.

SECTION VIII -- CONTROL MEASURES

Respiratory Protection: A NIOSH/MSHA APPROVED RESPIRATOR AS NECESSARY.

Ventilation: GENERAL; LOCAL EXHAUST VENTILATION AS NECESSARY TO CONTROL MIST OR DUST.

Protective Gloves: IMPERMEABLE GLOVES TO MINIMIZE SKIN CONTACT.

Eye Protection: CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Measures:

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS BELIEVED TO BE ACCURATE, AND OUR COMPANY DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR THE USE OR RELIANCE UPON SAME. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS. BEFORE USING ANY PRODUCT READ ITS LABEL.

THIS PRODUCT HAS BEEN REVIEWED AND APPROVED TO BE LABELED AS NON-TOXIC BY THE ART AND CRAFT MATERIAL INSTITUTE.

Dec 14 01 10:19a

Caldex Enterprises

909 923 1185

p. 8

MATERIAL SAFETY DATA SHEET

Product: 803 Satin Sealer

SECTION I -- SUPPLIER INFORMATION

Manufacturer : Old World Art
 Address : 1953 South Lake Place -
 City, St. Zip : Ontario, CA 91761
 Phone : (909)947-4928 (909)947-9945 Fax(909)923-1185
 Date : 02/27/1997

SECTION II -- HAZARDOUS INGREDIENT INFORMATION

Ingredient	% Wt.	Pel-OSHA	TLV-ACGIH
MINERAL SPIRITS	21.6	100 ppm	100 ppm
PETROLEUM NAPHTHA	52.1	300 ppm	300 ppm

SECTION III -- PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor : SOLVENT THINNED CLEAR LIQUID
 Boiling Point : 135 F
 Specific Gravity (Water = 1) :
 Melting Point : N/A
 Vapor Pressure : 1 mm Hg @ 68 F
 Vapor Density (Air = 1) : HEAVIER THAN AIR
 Evaporation Rate (Butyl Acetate = 1) : SLOWER THAN ETHER

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash Point : Over 100 F P.M.C.C. DRY LEL 1.0% COMBUSTIBLE
 Flammable Limits : NA
 Extinguishing Media : FOAM, DRY CHEM., CO2, H2O SPRAY
 Special Fire Fighting Procedures: DO NOT USE WATER STREAM ON BURNING LIQUID COOL EXPOSED CONTAINERS WITH WATER.
 Unusual Fire & Explosion Hazards: EXTREMELY FLAMMABLE. KEEP CONTAINERS CLOSED WHEN NOT IN USE. ISOLATE FROM FLAME AND SPARKS. AVOID TOBACCO SMOKING WHEN USING THIS MATERIAL.

SECTION V -- REACTIVITY DATA

Stability : STABLE
 Conditions to Avoid : NONE
 Incompatibility : NA
 Hazardous Polymerization : BURNING WILL PRODUCE TOXIC FUMES

SECTION VI -- HEALTH HAZARD DATA

Medical Conditions Generally Aggravated by Exposure : A review of available data does not identify any worsening of existing conditions not elsewhere mentioned in this MSDS.
 Effects of Over Exposure : METHANOL VAPORS CAUSE LOCAL IRRITATION OF EYES, HEADACHE, SENSATION OF HEAT, FATIGUE AND DROWSINESS.

Dec 14 01 10:19a

Caldex Enterprises

909 923 1185

P. 9

Emergency First Aid Procedures :

Inhalation: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED.

Ingestion: INDUCE VOMITING IF VICTIM IS CONSCIOUS. CALL A PHYSICIAN.

Skin Contact: WASH SKIN WITH SOAP AND WATER.

Eye Contact: FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES. CALL A PHYSICIAN IF IRRITATION PERSISTS.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Spill and Leak Procedure: REMOVE SOURCES OF IGNITION. FLUSH WITH PLENTY OF WATER AND COVER WITH INERT ABSORBENT MATERIAL AND REMOVE TO SUITABLE DISPOSAL CONTAINER.

Waste Disposal: OBEY RELEVANT LOCAL, STATE AND FEDERAL LAWS.

Precautions to be taken in handling and storage: PROTECT FROM EXTREME COLD.

SECTION VIII -- CONTROL MEASURES

Respiratory Protection: A NIOSH/MSHA APPROVED RESPIRATOR AS NECESSARY.

Ventilation: GENERAL, LOCAL EXHAUST VENTILATION AS NECESSARY TO CONTROL MIST OR DUST.

Protective Gloves: IMPERMEABLE GLOVES TO MINIMIZE SKIN CONTACT.

Eye Protection: CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Measures:

* THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS BELIEVED TO BE ACCURATE, AND OUR COMPANY DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR THE USE OR RELIANCE UPON SAME. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS. BEFORE USING ANY PRODUCT READ ITS LABEL.