

04/30/2003 10:42 16094662450

SCULPTURE HOUSE

PAGE 02/03

MICROCRYSTALLINE WAX, PG. 1 of 2

33115-1006

Material Safety Data Sheet No.

Revd 4-30-03

| | |
|--|---|
| Manufacturer: Sculpture House, Inc. 100 Camp Meeting Avenue Skillman, NJ 08558 | Emergency Telephone No.: (609) 466-2986 |
|--|---|

| SECTION I: PRODUCT IDENTIFICATION | |
|--|----------------------------------|
| Trade Names & Synonyms MICROCRYSTALLINE WAX | Part No.: 503 CAS No.: |
| Chemical Name & Synonyms: HYDROCARBON Chemical Family: WAX | Formula: |

| SECTION II: HAZARDOUS INGREDIENTS | | | | | |
|-----------------------------------|---|-------------|--|---|-------------|
| PAINTS, PRESERVATIVES & SOLVENTS | % | TLV (Units) | ALLOYS & METALLIC COATINGS | % | TLV (Units) |
| Pigments N/A | | | Base Metal N/A | | |
| Catalyst N/A | | | Alloys N/A | | |
| Vehicle N/A | | | Metallic Coatings N/A | | |
| Solvents N/A | | | Filler Material + Coating or Core Flux N/A | | |
| Additives N/A | | | Others N/A | | |
| Others N/A | | | Hazardous Mixtures of Other Liquids, Solids or gases N/A | | |

V-3750

| SECTION III: PHYSICAL DATA | |
|---|--|
| Appearance/Odor: SOLID MATERIAL - NO ODOR | Vapor Density (Air = 1): |
| Boiling Point (°F.): ABOVE 700 DEGREES F. | Vapor Pressure (mm Hg): |
| Solubility in Water: INSOLUBLE | Specific Gravity (H ₂ O = 1): 0.927 |
| Evaporation Rate: | Volatile % by Volume: |
| Melting Point: | |

04/30/2003 10:42 16094662450

SCULPTURE HOUSE

PAGE 03/03

MICROCRYSTALLINE WAX, PG. 2 of 2

MSDS No.

| SECTION IV: FIRE AND EXPLOSION HAZARD DATA | | |
|---|-------------------------|-------------------------|
| Flash Point (Method Used): 530 DEGREES F., COC, ASTM D-92 | Flammable Limits (LEL): | Flammable Limits (LEL): |
| Extinguishing Media: WATER, CO2, FOAM, AND DRY CHEMICAL | | |
| Special Fire Fighting procedures: NONE | | |
| Unusual Fire & Explosion Hazards: | | |

| SECTION V: HEALTH HAZARD DATA | |
|---|--|
| Threshold Limit Value: | |
| Effects of Overexposure: NO KNOWN EFFECTS. | |
| Emergency & First Aid Procedures: A BURN FROM MOLTEN WAX SHOULD BE TREATED AS A THERMAL BURN. | |

| SECTION VI: REACTIVITY DATA | |
|---------------------------------------|----------------------|
| Stability | Conditions to Avoid: |
| Unstable: Stable: X ___ | |
| Incompatibility (Materials to Avoid): | |
| Hazardous Decomposition Products: | |
| Hazardous Polymerization | Conditions to Avoid: |
| May Occur: Will Not Occur: X | |

| SECTION VII: SPILL OR LEAK PROCEDURES | |
|--|--|
| For Spills or Leakage: ALLOW MOLTEN WAX TO SOLIDIFY. SCRAPE UP AND DISPOSE OF. | |
| Waste Disposal Method: NORMAL SOLID WASTE DISPOSAL. | |

| SECTION VIII: SPECIAL PROTECTION INFORMATION | |
|---|-----------------|
| Respiratory Protection (Specify type): NONE REQUIRED. | |
| Protective Gloves: WHEN HANDLING MOLTEN WAX | Eye Protection: |
| Other Protective Equipment: | |
| Ventilation: | Special: NONE |
| Local Exhaust: ADEQUATE | |
| Mechanical (General): | Other: |

| SECTION IX: SPECIAL PRECAUTIONS | |
|---|--|
| Handling & Storage: STORE AWAY FROM OPEN FLAME AND BOILERS. | |