

11/17/2001 12:55 625-333-7694

LAGUNA CLAY CO

58560-01

Ovencraft Clay

33231-1004

MATERIAL SAFETY DATA SHEET

6/9/00

Revd 1149-01

SECTION I - MANUFACTURER & PRODUCT INFORMATION

LAGUNA CLAY COMPANY
14400 LOMITAS AVE.
CITY OF INDUSTRY, CA 91746

Phone: (626) 330-0632
Fax: (626) 333-7694

TRADE NAME: CP-601-W

CHEMICAL NAME: N/AP

CHEMICAL FAMILY: Dry Hard White Clay

SECTION II - POTENTIAL HAZARDOUS INGREDIENTS

Note: Existing 1% or more of the product mixture, or (0.1)% or more if considered to be a carcinogen as established in the Federal OSHA Standard (29 CFR 1910.1200).

INGREDIENT NAME:

- 1. Crystalline Silica (Quartz) Cass # 14808-60-7
2. Clay Cass # 1332-58-7
3. Titanium Dioxide Cass # 13463-67-7
4. Inorganic Pigments (See Section VI)

SECTION III - PHYSICAL DATA

Specific Gravity: 1.7 Appearance and Odor: N/AP
Melting Point: N/AP Evaporation Rate: N/AP
Solubility in Water: N/AV

Boiling point/ Vapor pressure/ Vapor Density/ are all N/A

SECTION IV - FIRE AND EXPLOSION DATA

Flammable Limits: LEVEL: N/AP UEL: Ignition N/AP Ignition Range: N/AP
Extinguishing Media: Water
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: None

SECTION V - REACTIVITY DATA

Stability Factor Stable: X Unstable:
Hazardous Polymerization: Will not occur.
Conditions to Avoid: Breathing Dust
Incompatibility: None
Hazardous Decomposition: Will not occur.

V.4SSO

11/17/2001 12:55 525-333-7594

OVENCRAFT CLAY CO

PAGE 001

2

MATERIAL SAFETY DATA SHEET

6/9/00

SECTION VI – HEALTH HAZARD DATA**SILICA:**

PRIMARY ROUTES of ENTRY: Inhalation, Dermal, and Ingestion. In DRY FORM ONLY.

OVEREXPOSURE EFFECTS: This product contains crystalline silica, which may cause delayed respiratory disease (silicosis) if inhaled over a long period of time. IRAC, NTP, and California Prop. 65 concludes there is or may be evidence that inhaled crystalline silica causes cancer. This product contains a small amount of Titanium Dioxide as a part of a clay composition. This has been listed by NIOSH as a potential carcinogen.
Respirable Quartz: OSHA PEL: TWA-TLV= 0.1mg/m³, ACGIH TLV= 0.1mg/m³, NIOSH TWA:= 0.05 mg/m³

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with a lung disease condition (E.g. bronchitis, emphysema, chronic pulmonary disease) can be aggravated by exposure.

EMERGENCY and FIRST AID PROCEDURES: No specific first aid is necessary since the adverse health effects associated with these compound results from chronic exposures. If there is a gross inhalation of dust, remove the person to fresh air, give artificial respiration as need, and seek medical help.

EYES: May cause irritation.

SKIN: May cause local dermatitis, which is relieved when removed.

INHALATION: See section V.

INGESTION: Toxicity due to ingestion is low.

PHYSICIANS NOTE: None.

Rutile (Titanium Dioxide) : TiO₂. Inhalation may cause damage to respiratory system. Identified as a potential carcinogen by NIOSH. OSHA TWA is 15 mg/M³.

INORGANIC PIGMENTS (if applicable):

SECTION VII – TOXICOLOGY INFORMATION

The above liquid glazes (if listed) are certified to NON TOXIC, conforming to ASTM D-4236 and C-1023 under the federal Labeling of Hazardous Art Materials Act (LHAMA). Toxicology data of some components is available upon request.

SECTION VIII – SPILL AND LEAK PROCEDURES

WASTE DISPOSAL METHODS: Dispose of in accordance with Federal, State, and Local regulations.

SECTION IX – SPECIAL PROTECTIVE INFORMATION

Provide adequate ventilation to keep dust or vapor concentrations below acceptable exposure limits.

Use gloves as needed for handling material containers.

Wear safety glasses when needed.

Appropriate respiratory protection may be required to protect from certain dusts.

11/17/2001 12:55 525-333-7594

LAGUNA CLAY CO

3

MATERIAL SAFETY DATA SHEET

6/9/00

Respirators must be selected and used in accordance with OSHA SUB PART 1 (29 CFR 1910.134).

SECTION X – REGULATORY INFORMATION

This product may contain component(s) that require reporting under Section 313 of the Emergency Planning and Community Right-To-Know Act (Superfund Amendments and Reauthorization Act), and 40 CFR Part 372.

SARA TITLE III DATA: Titanium Dioxide (Rutile)

SECTION XI – TOXIC SUBSTANCE CONTROL ACT (TSCA)

This product (and all of its components) is in compliance with the U.S. EPA 15 U.S. C. 2604 regulation.

SECTION XII – DEFINITIONS AND ABBREVIATIONS

ACCIH	American Conference of Governmental Industrial Hygienists
C(CIEL)	The concentration that shall not be exceeded during any part of the working exposure.
CALOSHA	California Occupational Safety and Health Administration
CAS	Chemical Abstracts Service Registry Number
EPA	Environmental Protection Agency
IARC	International Agency for Research on Cancer
LEL	Lower Explosion Limit
N/AP	Not Applicable
N/AV	Not Available
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limits
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit. Usually a 15-minute time weighted average. Exposure should not be exceeded at any time during a workday.
TLV	Threshold Limit Values
TSCA	Toxic Substance Control Act
TWA	Time Weighed Average. Exposure concentration for a normal 8 hour day.

SECTION XIII – DISCLAIMER

Judgement as to the suitability of information herein or to the purchaser's purposes is solely the purchaser's responsibility. Reasonable care has been taken in the preparation of this information.

LAGUNA CLAY COMPANY EXTENDS NO WARRANTIES, MAKES NO REPRESENTATIONS AND ASSUMES NO RESPONSIBILITY OF THIS INFORMATION FOR ANY PURCHASER'S USE OR FOR ANY CONSEQUENCES OF ITS USE.