

12/20/2006 14:53
JEP 20 06 12:25p

6094662450

SCULPTUREHOUSE

PAGE 01/08

WHITE MINERAL OIL : MSDS

P. 1

12/05/2006 15:30

9813630060

IDEAL CUSTOMER SERI

PAGE 03/10

34936-1030



CITGO Duoprime® Oil 70 Material Safety Data Sheet



CITGO Petroleum Corporation
P.O. Box 4689
Houston, TX 77210

MSDS No. 669347001
Revision Date 05/05/2005

Hazard Rankings		
	HMS	NFPA
Health Hazard	0	0
Fire Hazard	1	1
Reactivity	0	0
* 0 Chronic Health Hazard		

IMPORTANT: Read this MSDS before handling or disposing of this product and pass this information on to employees, customers, and users of this product.

Emergency Overview			
Physical State	Liquid.	Odor	Oderless.
Color	Colorless.		
WARNING!			
If liquid material is swallowed, contact a physician.			
Do not induce vomiting.			
If liquid material enters the lungs, it can cause severe damage.			
Spills may create a slipping hazard.			

Protective Equipment
Minimum Recommended See Section 8 for Details
 

SECTION 1. PRODUCT IDENTIFICATION

Trade Name	CITGO Duoprime® Oil 70	Technical Contact	(800) 248-4684
Product Number	669347001	Medical Emergency	(832) 400-4700
CAS Number	8042-47-5	CHEMTREC Emergency (United States Only)	(800) 424-9300
Product Family	White Mineral Oil		
Synonyms	White Mineral Oil CITGO SAP Product Code No. 669347001 and 669347		

SECTION 2. COMPOSITION

Component Name(s)	CAS Registry No.	Concentration (%)
White Mineral Oil	8042-47-5	100
d1 alpha tocopherol (Vitamin E) (Stabilizer)	59-02-9	<0.1

SECTION 3. HAZARDS IDENTIFICATION

Also see Emergency Overview and Hazard Ratings on the top of Page 1 of this MSDS.

Major Route(s) of Entry Not applicable.

Signs and Symptoms of Acute Exposure

Inhalation	No significant adverse health effects are expected to occur upon short-term exposure.
Eye Contact	Minimal eye irritation may result from short-term contact with liquid, mist, and/or vapor
Skin Contact	No significant irritation is expected to occur upon short-term exposure.

MSDS No. 669347001 Revision Date 05/05/2005 Continued on Next Page Page Number: 1



12/20/2005 14:53
DEC 20 05 12:48p

6094662450

SCULPTUREHOUSE

PAGE 02/08
P - 1

CITGO Duoprime® Oil 70

Ingestion Ingestion can cause a laxative effect. If liquid material enters into the lungs, it can cause severe damage.

Chronic Health Effects Summary No significant signs or symptoms indicative of any adverse health effects are expected to occur.

Conditions Aggravated by Exposure None known.

Target Organs No target organ effects are anticipated.

Carcinogenic Potential This product is not known to contain any components at concentrations above 0.1% which are considered carcinogenic by OSHA, IARC or NTP.

OSHA Hazard Classification is indicated by an "X" in the box adjacent to the hazard GHS. If no "X" is present, the product does not exhibit the hazard as defined in the OSHA Hazard Communication Standard (29 CFR 1910.1200).

OSHA Health Hazard Classification		OSHA Physical Hazard Classification							
Irritant	<input type="checkbox"/>	Sensitizer	<input type="checkbox"/>	Combustible	<input type="checkbox"/>	Explosive	<input type="checkbox"/>	Pyrophoric	<input type="checkbox"/>
Toxic	<input type="checkbox"/>	Highly Toxic	<input type="checkbox"/>	Flammable	<input type="checkbox"/>	Oxidizer	<input type="checkbox"/>	Water-reactive	<input type="checkbox"/>
Corrosive	<input type="checkbox"/>	Carcinogenic	<input type="checkbox"/>	Compressed Gas	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>	Unstable	<input type="checkbox"/>

SECTION 4. FIRST AID MEASURES

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid. For more specific information, refer to Exposure Controls and Personal Protection in Section 8 of this MSDS.

Inhalation Vaporization is not expected at ambient temperatures. This material is not expected to cause inhalation-related disorders under anticipated conditions of use. In case of overexposure, move the person to fresh air.

Eye Contact Check for and remove contact lenses. Flush eyes with cool, clean, low-pressure water while occasionally lifting and lowering eyelids. Seek medical attention if excessive tearing, redness, or pain persists.

Skin Contact If burned by hot material, cool skin by quenching with large amounts of cool water. For contact with product at ambient temperatures, remove contaminated shoes and clothing. Wipe off excess material. Wash exposed skin with mild soap and water. Seek medical attention if tissue appears damaged or if pain or irritation persists. Thoroughly clean contaminated clothing before reuse. Discard contaminated leather goods. If material is injected under the skin, seek medical attention immediately.

Ingestion Do not induce vomiting. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Never give anything by mouth to a person who is not fully conscious. Do not leave victim unattended. Seek medical attention immediately.

Notes to Physician SKIN: In the event of injection in underlying tissue, immediate treatment should include extensive incision, debridement and saline irrigation. Inadequate treatment can result in ischemia and gangrene. Early symptoms may be minimal.

INGESTION: If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

MSDS No. 569347001 Revision Date 05/05/2005 Continued on Next Page Page Number: 2

12/20/2006 14:53
DEC 20 06 12:44p

6094662450

SCULPTUREHOUSE

PAGE 03/08
p. 1

12/06/2006 15:30 9013630060

IDEAL CUSTOMER SER!

PAGE 05/10

CITGO Duoprime® Oil 70

SECTION 5. FIRE FIGHTING MEASURES

NFPA Flammability Classification NFPA Class-III B combustible material.

Flash Point Open cup: 166°C (331°F) (Cleveland).

Lower Flammable Limit No data. **Upper Flammable Limit** No data.

Autoignition Temperature AP 400°C (AP 752°F)

Hazardous Combustion Products Carbon dioxide, carbon monoxide, smoke, fumes, and unburned hydrocarbons.

Special Properties This material can burn but will not readily ignite. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point.

Extinguishing Media Use dry chemical, foam, Carbon Dioxide or water fog.

Protection of Fire Fighters Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up. For more specific information, refer to the Emergency Overview on Page 1, Exposure Controls and Personal Protection in Section 8 and Disposal Considerations in Section 13 of this MSDS.

Do not touch damaged containers or spilled material unless wearing appropriate protective equipment. Slipping hazard; do not walk through spilled material. Stop leak if you can do so without risk. For small spills, absorb or cover with dry earth, sand, or other inert non-combustible absorbent material and place into waste containers for later disposal. Contain large spills to maximize product recovery or disposal. Prevent entry into waterways or sewers. In urban area, cleanup spill as soon as possible. In natural environments, seek cleanup advice from specialists to minimize physical habitat damage. This material will float on water. Absorbent pads and similar materials can be used. Comply with all laws and regulations.

SECTION 7. HANDLING AND STORAGE

Handling Avoid contamination and extreme temperatures to minimize product degradation. Empty containers may contain product residues that can ignite with explosive force. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to flames, sparks, heat or other potential ignition sources. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

Storage Keep container closed. Do not store with strong oxidizing agents. Do not store at elevated temperatures. Avoid storing product in direct sunlight for extended periods of time. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers or waste residues of this product.

12/20/2006 14:53 6094662450

SCULPTUREHOUSE

PAGE 04/08
P. 1

12/06/2006 15:30 9013630050

IDEAL CUSTOMER SERI


PAGE 06/10

CITGO Duoprime® Oil 70

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits (see below). An eye wash station and safety shower should be located near the work station.

Personal Protective Equipment: Personal protective equipment should be selected based upon the conditions under which this material is used. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. The following pictograms represent the minimum requirements for personal protective equipment. For certain operations, additional PPE may be required.



Eye Protection: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Wear goggles if splashing or spraying is anticipated. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available.

Hand Protection: Use gloves constructed of chemical resistant materials such as heavy nitrile rubber if frequent or prolonged contact is expected. Use heat-protective gloves when handling product at elevated temperatures.

Body Protection: Use clean protective clothing if splashing or spraying conditions are present. Protective clothing may include long-sleeve outer garment, apron, or lab coat. If significant contact occurs, remove oil-contaminated clothing as soon as possible and promptly shower. Launder contaminated clothing before reuse or discard. Wear heat-protective boots and protective clothing when handling material at elevated temperatures.

Respiratory Protection: The need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).

General Comments: Use good personal hygiene practices. Wash hands and other exposed skin areas with plenty of mild soap and water before eating, drinking, smoking, use of toilet facilities, or leaving work. DO NOT use gasoline, kerosene, solvents or harsh abrasives as skin cleaners. Since specific exposure standards/control limits have not been established for this product, the "Oil Mist, Mineral" exposure limits shown below are suggested as minimum control guidelines.

Occupational Exposure Guidelines

Substance	Applicable Workplace Exposure Levels
Oil Mist, Mineral	ACGIH (United States): TWA: 5 mg/m ³ STEL: 10 mg/m ³ OSHA (United States): TWA: 5 mg/m ³

MSDS No. 60947001 Revision Date 09/03/2005 Continues on Next Page Page Number: 4

12/20/2006 14:53
DEC 20 06 12:38p

6094662450

SCULPTUREHOUSE

PAGE 05/08

p. 1

12/06/2006 15:30

9013630060

IDEAL CUSTOMER SERI "

PAGE 07/10

CITGO Duoprime® Oil 70

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES (TYPICAL)

Physical State	Liquid.	Color	Colorless.	Odor	Odorless.
Specific Gravity	0.84 (Water = 1)	pH	Not Applicable.	Vapor Density	>1 (Air = 1)
Boiling Range	Not available.			Melting/Freezing Point	Not available.
Vapor Pressure	<0.1 mm of Hg (@ 20°C)			Volatility	43 g/l VOC (w/v)
Solubility in Water	Negligible solubility in cold water.			Viscosity (cSt @ 40°C)	13
Flash Point	299.0 C/568.2 F (Closed Cup)				
Additional Properties	Gravity, API (ASTM D287) = AP 34.0 @ 60° F Density = AP 7.10 Lbs/gal. Viscosity (ASTM D2161) = AP 72 SUG @ 100° F				

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability	Stable	Hazardous Polymerization	Not expected to occur.
Conditions to Avoid	Keep away from extreme heat, sparks, open flame, and strongly oxidizing conditions.		
Materials Incompatibility	Strong oxidizers.		
Hazardous Decomposition Products	No additional hazardous decomposition products were identified other than the combustion products identified in Section 3 of this MSDS.		

SECTION 11. TOXICOLOGICAL INFORMATION

For other health-related information, refer to the Emergency Overview on Page 1 and the Hazards Identification in Section 3 of this MSDS.

Toxicity Data	<p>White Mineral Oil: Low-viscosity and High-viscosity White Mineral Oils: ORAL (LD50), Acute: >5000 mg/kg (Rat). DERMAL (LD50), Acute: >2000 mg/kg (Rabbit). DRAIZE EYE, Acute: Non-irritating (Rabbit). DRAIZE DERMAL, Acute: Non-irritating (Rabbit). BUEHLER, Acute: Non-sensitizing (Guinea Pig). 28-Day DERMAL, Sub-Chronic: Non-irritating (Rabbit). 104-Week DERMAL, Chronic: No skin tumors at site of application (Mouse). MUTAGENICITY: Modified Ames Assay: Negative (Salmonella typhimurium). In-vitro Lymphoma Assay: Negative or no toxicity (Mouse).</p> <p>Lifetime mouse skin painting studies indicated that white mineral oils are not mutagenic or carcinogenic. Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipid granuloma formation and lipid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists</p>
----------------------	--

MSDS No. 665347001 Revision Date: 03/03/2005 Continued on Next Page Page Number: 5

12/20/2006 14:53 6094662450
Dec 20 06 12:37p

SCULPTUREHOUSE

PAGE 06/08
P. 1

12/06/2006 15:30 9013630060

IDEAL CUSTOMER SER!"

PAGE 08/18

CITGO Duoprime® Oil 70

at or near current work place exposure levels produced no significant toxicological effects. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.

Environmental Fate An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

SECTION 13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Conditions of use may cause this material to become a "hazardous waste", as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a "hazardous waste" at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues. Empty drums and pails retain residue. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose this product's empty container to heat, flame, or other ignition sources. DO NOT attempt to clean it. Empty drums and pails should be drained completely, properly bunged or sealed, and promptly sent to a reconditioner.

SECTION 14. TRANSPORT INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

US DOT Status Not regulated by the U.S. Department of Transportation as a hazardous material.

Proper Shipping Name Not regulated.

Hazard Class Not regulated. **Packing Group(s)** Not applicable.
UN/NA Number Not regulated.

Reportable Quantity A Reportable Quantity (RQ) has not been established for this material.

MSDS No. 689347001 Revision Date 05/05/2005 Continued on Next Page Page Number: 6

12/20/2006 14:53 6094662450
 Dec 20 06 12:31p

SCULPTUREHOUSE

PAGE 07/08
 P. 1


12/06/2006 15:30 9013630050

IDEAL CUSTOMER SER1"

PAGE 09/10

CITGO Duoprime® Oil 70

Placard(s)



Emergency Response
 Guide No.

Not applicable.

MARPOL 73 Status

Not a DOT "Marine
 Pollutant" per 49 CFR
 171.8

SECTION 15. REGULATORY INFORMATION

TSCA Inventory	This product and/or its components are listed on the Toxic Substances Control Act (TSCA) Inventory.
SARA 302/304 Emergency Planning and Notification	The Superfund Amendments and Reauthorization Act of 1988 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.
SARA 311/312 Hazard Identification	The Superfund Amendments and Reauthorization Act of 1988 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: No SARA 311/312 hazard categories identified.
SARA 313 Toxic Chemical Notification and Release Reporting	This product contains the following components in concentrations above de minimis levels that are listed as toxic chemicals in 40 CFR Part 372 pursuant to the requirements of Section 313 of SARA. No components were identified.
CERCLA	The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQs) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. This product or refinery stream is not known to contain chemical substances subject to this statute. However, it is recommended that you contact state and local authorities to determine if there are any other reporting requirements in the event of a spill.
Clean Water Act (CWA)	This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.
California Proposition 65	This product is not known to contain any components for which the State of California has found to cause cancer, birth defects or other reproductive harm.
New Jersey Right-to-Know Label	Petroleum Oil
Additional Regulatory Remarks	Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.63(a)(13): This product contains "Petroleum Distillates" which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: DANGER: Contains Petroleum Distillates! Harmful or fatal if swallowed! Call Physician Immediately. KEEP OUT OF REACH OF CHILDREN!

MSDS No. 609247001 Revision Date 05/05/2005 Continued on Next Page Page Number: 7

12/20/2006 14:53 6094662450
Dec 20 06 12:32p

SCULPTUREHOUSE

PAGE 08/08
p. 1

12/06/2006 15:30 9013630060

IDEAL CUSTOMER SERVICE

PAGE 10/10

CITGO Duoprime® Oil 70

SECTION 16. OTHER INFORMATION

Refer to the top of Page 1 for the HMIS and NFPA Hazard Ratings for this product.

REVISION INFORMATION

Version Number 1.3
Revision Date 05/05/2005
Print Date Printed on 05/05/2005.

ABBREVIATIONS

AP: Approximately	EQ: Equal	>: Greater Than	<: Less Than	NA: Not Applicable	ND: No Data	NE: Not Established
ACGIH: American Conference of Governmental Industrial Hygienists				AHA: American Industrial Hygiene Association		
IARC: International Agency for Research on Cancer				NTP: National Toxicology Program		
NIOSH: National Institute of Occupational Safety and Health				OSHA: Occupational Safety and Health Administration		
NPCA: National Paint and Coating Manufacturers Association				HMIS: Hazardous Materials Information System		
NFPA: National Fire Protection Association				EPA: US Environmental Protection Agency		

DISCLAIMER OF LIABILITY

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

***** END OF MSDS *****