

SECTION V - HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Dermal contact or open wound.

MEDICAL CONDITIONS WHICH MIGHT BE AGGRAVATED: None expected.

OVEREXPOSURE TO VAPOR MAY CAUSE:(ACUTE)

No adverse effects are expected. However, because fumes are occasionally observed arising from fabrics which are being heat cured, it is suggested that in accordance with good industrial hygienic practice that all heat curing equipment should be properly vented and exhausted to prevent irritation to eyes, nose and throat. (These fumes often arise from sizings, starches and other coatings which have been earlier applied to the textiles being printed.)

REPEATED OVEREXPOSURE TO VAPOR MAY CAUSE: (CHRONIC)

Occupational exposure to this material has not been reported to cause significant adverse human health effect. On the basis of available information, exposure to the product is not expected to produce adverse human health effects when recommended ventilation and safety precautions are followed.

EMERGENCY AND FIRST AID PROCEDURES:

Handle in accordance with good industrial hygiene and safety practices including unnecessary exposure to eyes, skin and clothing. In case of eye contact, flush eyes with plenty of water for at least 15 minutes and SEE A PHYSICIAN.

SECTION VI - REACTIVITY DATA

STABILITY: Stable **CONDITIONS TO AVOID:**

INCOMPATIBILITY Strong acids, alkalis, oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce oxides of Nitrogen, Carbon Dioxide/Monoxide.

HAZARDOUS POLYMERIZATION: Will Not Occur.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Contain spill and pick up and transfer to containers for recovery if uncontaminated or disposal if contaminated. If necessary dike and contain spill with absorbent or inert material.

WASTE DISPOSAL METHOD:

Small amounts can be fused in a microwave or vented oven and disposed of as solid waste according to local, state, and federal regulations. (Do not use same ovens for cooking food.)

SECTION VIII - SPECIAL PROTECTION INFORMATION

VENTILATION:

Use local or central exhaust systems to remove fumes which may arise during any heat curing operation. (These fumes often arise from sizings, starches and other coatings which have been earlier applied to the textiles being printed.)

RESPIRATORY PROTECTION:

IN OPEN AREAS: Use approved mechanical filter respirator if there is not exhaust system in operation during any heat curing procedure.

IN RESTRICTED VENTILATION AREAS:

Use NIOSH/MSHA approved chemical/mechanical filter respirators or positive pressure air hoods if local mechanical exhaust is not sufficient.

PROTECTIVE GLOVES:

Impervious type required for prolonged or repeated contact (during mixing or when washing up).

EYE PROTECTION:

Use safety goggles or face shields (ANSI Z87.1 or equiv.).

OTHER PROTECTIVE EQUIPMENT:

Eye bath, safety shower, aprons.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

KEEP AWAY FROM HEAT AND OPEN FLAME
LIQUID MAY CAUSE EYE AND SKIN IRRITATION
FOR INDUSTRIAL USE ONLY

USE ONLY WITH ADEQUATE VENTILATION
WASH HANDS THOROUGHLY AFTER USING
KEEP OUT OF THE REACH OF CHILDREN

DO NOT USE UNTIL MANUFACTURER'S SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD