

6118-99 ✓

43217-1007



**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072



**IDENTITY (As Used on Label and List)** SPEEDBALL Permanent Acrylic Extender Base (46219, 46419 & 46619)

**Section I**

<b>Manufacturer's Name</b>  P. O. Box 5157 Statesville, NC 28687 ©1997 Speedball Art Products Company	<b>Emergency Telephone Number</b> 704-838 1475
	<b>Telephone Number for Information</b> 704-838 1475
	<b>Date Prepared</b> 3/11/96
	<b>Signature of Preparer (optional)</b> 

**Section II — Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Approved for the AP Seal (Non-toxic) by the Art & Creative Materials Institute, Inc. (ACMI)				
Product labeling conforms to ASTM D4236.				

**Note:** This product has been evaluated by a Toxicologist only as per intended usage.  
 Do not deviate from intended usage!

V 3921

VOC: 0

**Section III — Physical/Chemical Characteristics**

<b>Boiling Point</b>	212°F.	<b>Specific Gravity (H<sub>2</sub>O = 1)</b>	1.05
<b>Vapor Pressure (mm Hg.)</b>	unknown	<b>Melting Point</b>	<32°F.
<b>Vapor Density (AIR = 1)</b>	less than 1	<b>Evaporation Rate (Butyl Acetate = 1)</b>	less than 1
<b>Solubility in Water</b> Dilutable			
<b>Appearance and Odor</b> Translucent semi-paste with slight odor			

**Section IV — Fire and Explosion Hazard Data**

<b>Flash Point (Method Used)</b> Not applicable (N/A)	<b>Flammable Limits</b> N/A	<b>LEL</b> N/A	<b>UEL</b> N/A
<b>Extinguishing Media</b> N/A			
<b>Special Fire Fighting Procedures</b> wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.			
<b>Unusual Fire and Explosion Hazards</b> Material can spatter above 212°F. Film can burn.			

**Section V — Reactivity Data**

Stability	Unstable		Conditions to Avoid Onset of decomposition is 350°F.
	Stable	X	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur		Conditions to Avoid N/A
	Will Not Occur	X	

**Section VI — Health Hazard Data**

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

**Section VII — Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled  
Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method  
Landfill according to Federal, State and local regulations.

Precautions to Be Taken in Handling and Storing  
Keep from freezing - product may coagulate.

Other Precautions N/A

**Section VIII — Control Measures**

Respiratory Protection (Specify Type)  
None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves Impervious Eye Protection Safety glasses

Other Protective Clothing or Equipment N/A

Work/Hygienic Practices  
Use protective cream where excessive skin contact is likely.