

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard, 29 CFR 1910.1200
Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved OMB No. 1218-0072

43233 - all codes
except - 1009

IDENTITY (As Used on Label and List) Opaque Fabric Screen Printing Ink (8 oz) 4800-4809		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.	
Section I Manufacturer's Name Speedball Art Products, LLC		Emergency Telephone Number 704-838-1475	
Address (Number, Street, City, State, and ZIP Code) 2226 Speedball Road Statesville, NC 28677 USA		Telephone Number for Information 704-838-1475	
Date Prepared: March 1, 2005		Signature of Preparer (optional)	

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)): VOC: 85-199 grams per litre (.71-1.66 lbs. per gallon)	OSHA PEL	ACGIH TLV	Other Limits	% (optional)
Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.				

Section III - Physical/Chemical Characteristics

Boiling Point	212°F - 369°F	Specific Gravity (H ₂ O = 1)	1.11 – 1.57
Vapor Pressure (mm Hg.)	17mmHg	Melting Point	<32°F
Vapor Density (AIR = 1)	Less than 1	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	High viscosity; acrylic emulsion odor

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures Wear self-contained breathing apparatus (pressure-demand MSHA/NIOSH approved or equivalent) and full protective gear.			
Unusual Fire and Explosion Hazards Material can spatter above 212°F. Film can burn.			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Acrylic & Fabric Transparent Base

Page 2

Stability	Unstable	Stable ✓	Conditions to Avoid Onset of decomposition is 350°F
Incompatibility (<i>Materials to Avoid</i>) N/A			
Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen			
Hazardous Polymerization	May Occur	Will Not Occur ✓	Conditions to Avoid N/A

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (<i>Acute and Chronic</i>) N/A			
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure None known			
Emergency and First Aid Procedures Contact with eyes may cause slight irritation: Flush with water.			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.
Waste Disposal Method Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.
Precautions to Be taken in Handling and Storing Keep from freezing-product may coagulate
Other Precautions N/A

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) None required with adequate ventilation & normal usage conditions.			
Ventilation	Local Exhaust N/A	Special N/A	
	Mechanical (<i>General</i>) N/A	Other N/A	
Protective Gloves Impervious	Eye Protection Safety Glasses or goggles		
Other Protective Clothing or Equipment N/A			
Work/Hygienic Practices Use protective cream where excessive skin contact is likely.			