

43301-1007



## MATERIAL SAFETY DATA SHEET

PRODUCT NAME


**STA-SHARP ADHERING LIQUID UN 1993**

### SECTION I

|   |   |
|---|---|
| Manufacturer's Name<br><b>ULANO CORPORATION</b>     | Emergency Telephone Number<br><b>CHEMTREC: (800)424-9300 or (703)527-3887</b> |
| Address (Number, Street)<br><b>110 THIRD AVE.</b>   | Telephone Number for Information<br><b>(718)237-4700 Fax#: (718)802-1119</b>  |
| City, State, ZIP Code<br><b>BROOKLYN, NY, 11217</b> | Date Prepared<br><b>June 20, 2007</b>   |
| Signature of Preparer (optional)                    |   |

### SECTION II - Ingredients/Identity Information

Supplier's Chemical Identity (Common Name(s))

| Ingredients       | C.A.S. #      | OSHA PEL | ACGIH TLV  | APPROX. CONC. | HAZARD TYPE |
|-------------------|---------------|----------|------------|---------------|-------------|
| HEPTANE           | CAS# 142-82-5 | 400PPM   | 400PPM (I) | 40%           | FLAMMABLE   |
| ETHYL ACETATE     | CAS# 141-78-6 | 400PPM   | 400PPM     | 30%           | FLAMMABLE   |
| BUTYL ACETATE     | CAS# 123-86-4 | 150PPM   | 150PPM     | 5%            | FLAMMABLE   |
| ISOPROPYL ALCOHOL | CAS# 67-63-0  | 400PPM   | 400PPM     | 25%           | FLAMMABLE   |

THIS PRODUCT CONTAINS SARA TITLE III SECTION 313 REPORTABLE CHEMICALS

ULANO PRODUCTS ARE NOT MANUFACTURED WITH, NOR DO THEY CONTAIN CLASS-I OR CLASS-II OZONE DEPLETING CHEMICALS

### SECTION III - Physical/Chemical Characteristics

|   |  |
|---|--|
| Boiling Point<br><b>168 F</b>                                   | Specific Gravity (H <sub>2</sub> O=1)<br><b>0.78</b>   |
| Vapor Pressure (mm Hg)<br><b>76</b>                             | Melting Point<br><b>N.A.</b>                           |
| Vapor Density (AIR=1)<br><b>HEAVIER THAN AIR</b>                | Evaporation Rate (H <sub>2</sub> O=1)<br><b>HIGHER</b> |
| Solubility in Water<br><b>PARTIALLY SOLUBLE</b>                 |  |
| Appearance and Odor<br><b>COLORLESS LIQUID, FRUIT-LIKE ODOR</b> |  |

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

|  |                                  |     |                    |
|--|----------------------------------|-----|--------------------|
| Flash Point (Method Used)<br><b>40 F</b>   | Flammable Limits<br><b>1.12%</b> | LEL | UEL<br><b>6.7%</b> |
| Extinguishing Media<br><b>WATER FOG, CARBON DIOXIDE OR DRY CHEMICAL</b>  |                                  |     |                    |
| Special Fire Fighting Procedures<br><b>SELF-CONTAINED BREATHING APPARATUS WITH PRESSURE DEMAND OR POSITIVE PRESSURE SOURCES.</b> |                                  |     |                    |
| Unusual Fire and Explosion Hazards<br><b>VAPOR HEAVIER THAN AIR. MAY TRAVEL ALONG GROUND TO OTHER IGNITION SOURCES.</b>          |                                  |     |                    |

### SECTION V - Reactivity Data

|   |              |                    |                           |
|---|--------------|--------------------|---------------------------|
| Stability<br><b>IGNITION SOURCES</b>  | Unstable     | Stable             | <b>X</b>                  |
| Incompatibility (Material to Avoid)<br><b>STRONG OXIDIZING AGENTS</b>                                     |              |                    |                           |
| Hazardous Decomposition or Byproducts<br><b>COMBUSTION CAN PRODUCE CARBON DIOXIDE AND CARBON MONOXIDE</b> |              |                    |                           |
| Hazardous Polymerization<br><b>NONE KNOWN</b>   | May Occur    | Will Not Occur     | <b>X</b>                  |
| Conditions to Avoid<br><b>NONE KNOWN</b>  |              |                    |                           |
| HMIS  | Health [ 2 ] | Flammability [ 3 ] | Reactivity [ 0 ]          |
|   |              |                    | Personal Protection [ C ] |

**SECTION VI - Health Hazard Data**

|                   |                  |            |                 |
|-------------------|------------------|------------|-----------------|
| Route(s) of Entry | Inhalation?<br>X | Skin?<br>X | Ingestion?<br>X |
|-------------------|------------------|------------|-----------------|

Health Hazards (*Acute and Chronic*)  
**EYES:** CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION. **SKIN:** PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION AND DEFATTING DERMATITIS. **INHALATION:** EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS AND EVEN ASPHYXIATION.  
**INGESTION:** CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS.

|                  |            |                        |                       |
|------------------|------------|------------------------|-----------------------|
| Carcinogenicity: | NTP?<br>NO | IARC Monographs?<br>NO | OSHA Regulated?<br>NO |
|------------------|------------|------------------------|-----------------------|

Signs and Symptoms of Exposure  
**SKIN, EYE OR NASAL IRRITATION, DIZZINESS OR NAUSEA**

Medical Condition Generally Aggravated by Exposure  
**NONE KNOWN**

Emergency and First Aid Procedures  
**SKIN:** WASH THOROUGHLY WITH SOAP AND WATER. WASH CONTAMINATED CLOTHING BEFORE REUSE. **EYES:** FLUSH WITH WATER FOR AT LEAST 15 MINUTES. LIFTING AND RINSING UNDER UPPER AND LOWER LIDS.  
**INGESTION:** DO NOT INDUCE VOMITING. KEEP PERSON CALM, WARM AND GET MEDICAL ATTENTION IMMEDIATELY. ASPIRATION OF MATERIAL INTO LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. IF BREATHING, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER INDIVIDUAL OXYGEN. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

**SECTION VII - Precautions for Safe Handling and Use**

Steps to be taken in case Material is Released or Spilled  
**STOP AND CONTAIN SPILL. ABSORB MATERIAL WITH SUITABLE MEDIA. ELIMINATE SOURCES OF IGNITION. PLACE MEDIA INTO SEALED, SOLVENT RESISTANT CONTAINER.**

Waste Disposal Method  
**HANDLE AS AN IGNITABLE WASTE. DISPOSE OF IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS.**

Precautions to be Taken in Handling and Storing  
**KEEP AWAY FROM SPARKS, FLAMES AND OTHER SOURCES OF IGNITION. STORE AND USE ONLY WITH PROPER VENTILATION. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS. KEEP CONTAINER CLOSED WHEN NOT IN USE. AVOID CONTACT WITH SKIN AND EYES.**

Other Precautions  
**PREVENT BUILD UP OF VAPORS. EXTINGUISH ALL PILOT LIGHTS AND HEATERS THAT COULD CAUSE IGNITION OF FUMES.**

**SECTION VIII - Control Measures**

Respiratory Protection (*Specify Type*)  
**IN THE CASE OF A LARGE SPILL, USE NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS.**

| <u>Ventilation</u> |                               |         |       |
|--------------------|-------------------------------|---------|-------|
| Local Exhaust      | Mechanical ( <i>General</i> ) | Special | Other |
|                    | X                             |         |       |

|  |                               |
|--|-------------------------------|
| Protective Gloves                      | Eye Protection                |
| <b>SOLVENT RESISTANT RUBBER GLOVES</b> | <b>NIOSH APPROVED GOGGLES</b> |

Other Protective Clothing or Equipment  
**IMPERVIOUS APRON**

Work / Hygienic Practices  
**WORK CAREFULLY, AVOID SPILLS.**

*WHILE THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF ULANO CORP. MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.*