

U. S. DEPARTMENT OF LABOR

Occupational Safety and Health Administration

OSHA No. 44-01357

(947-00)

MATERIAL SAFETY DATA SHEET

45210-1006 *
947-00

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Burnishine Products Div. The Herbert Stanley Company		EMERGENCY TELEPHONE NO. (312) 583-1810
ADDRESS (Number, Street, City, State, and ZIP Code) 8140 North Ridgeway, Skokie, Illinois 60076		
CHEMICAL NAME AND SYNONYMS		TRADE NAME AND SYNONYMS Burnishine Putz Pomade Roller Cleaner
CHEMICAL FAMILY	FORMULA	

SECTION II HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE			METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Kerosene				5.5	

V-1930

SECTION III PHYSICAL DATA

BOILING POINT (°F.)		SPECIFIC GRAVITY (H ₂ O=1)	
VAPOR PRESSURE (mm Hg.)		PERCENT VOLATILE BY VOLUME (%)	5.78
VAPOR DENSITY (AIR=1)		EVAPORATION RATE (_____ = 1)	
SOLUBILITY IN WATER	Insol.		
APPEARANCE AND ODOR Reddish Heavy Paste			

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used) over 200° F (tag open cup)	FLAMMABLE LIMITS	LeL	UeL
EXTINGUISHING MEDIA Foam			
SPECIAL FIRE FIGHTING PROCEDURES Same as for oil or grease			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE

EMERGENCY AND FIRST AID PROCEDURES

Remove from skin with soap and water

If ingested, call a physician

SECTION VI - REACTIVITY DATA

STABILITY

UNSTABLE

CONDITIONS TO AVOID

High Heat

STABLE

XX

INCOMPATIBILITY (Materials to avoid)

HAZARDOUS DECOMPOSITION PRODUCTS

HAZARDOUS
POLYMERIZATION

MAY OCCUR

CONDITIONS TO AVOID

WILL NOT OCCUR

XX

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Product is a viscous liquid at room temperature. If spilled, scoop up and wipe surface dry and wash with detergent and water.

WASTE DISPOSAL METHOD

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type)

VENTILATION

LOCAL EXHAUST

SPECIAL

MECHANICAL (General)

OTHER

PROTECTIVE GLOVES

EYE PROTECTION

Keep away from eyes

OTHER PROTECTIVE EQUIPMENT

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from excessive heat and open flames

OTHER PRECAUTIONS

PAGE (2)

GPO 934-110

Form OSHA-20
Rev. May 72