

50979-XXXX

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 That, IdeaPaint WB Part A

FILE NO.:
MSDS DATE: 1 / 29 /2010

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: IdeaPaint CRE -8 That, IdeaPaint WB Part A
SYNONYMS: IdeaPaint CRE -8 That-light gray, IdeaPaint CRE -8 That-white sand, IdeaPaint CRE -8 That-off white, IdeaPaint CRE -8 That-light beige

PRODUCT CODES:

MANUFACTURER: IdeaPaint, Inc.
DIVISION:
ADDRESS: 25 First Street
 Suite 100
 Cambridge, MA 02141

EMERGENCY PHONE: 617-714-1050
CHEMTREC PHONE: 800-424-9300
OTHER CALLS:
FAX PHONE: 617-714-1070

CHEMICAL NAME:
CHEMICAL FAMILY: Paint
CHEMICAL FORMULA:

PRODUCT USE:
PREPARED BY:

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS NO.</u>	<u>Component</u>	<u>% WT</u>
17732-18-5	Water	39-59
3463-67-7	Titanium Dioxide	15-25
Trade Secret	Component A1	15-25
71-36-3	n-Butyl Alcohol	3-8
7631-86-9	Silica, Amorphous	2-7
21645-51-2	Aluminum Hydroxide	1-5
Trade Secret	Component A2	1-5
Trade Secret	Component A3	1-5
Not Available	Alkylarylalkoxylate	0.5-0.65
Not Available	Ester/Styrene Maleic Anhydride Copolymer	0.3-0.80
Trade Secret	Component A4	0.2-0.70
100-42-5	Styrene	
0.1-0.06		
107-21-1	Ethylene Glycol	0.1-0.06
10605-21-17	Methyl -2-Benzimidazole Carbamate	0.1-0.06
1332-58-7	Kaolin	0.1-0.06
126-86-3	5-Decyne-4, 7-Diol, 2,4,7,9 Tetramethyl-	0.1-0.06
Trade Secret	Component A5	0.05-0.10
Trade Secret	Component A6	0.05-0.10
55406-53-6	3-Iodo-2-Propynyl Butylcarbamate	0.05-0.10
77-58-7	Dibutyltin Dilaurate	0.02-0.07
Trade Secret	Component A7	0.01-0.06
111-76-2	2-Butoxyethanol	0.01-0.06
Trade Secret	Yellow Oxide	0-0.080
Trade Secret	Lamp Black	0-0.080
Trade Secret	Red Oxide	
0-0.060		

Component Exposure Limits

	<u>ppm</u>	<u>mg/m3</u>
Titanium Dioxide		
OSHA PEL-TWA:		10
OSHA PEL STEL :		
OSHA PEL CEILING:		
ACGIH TLV-TWA:		10
ACGIH TLV STEL:		
ACGIH TLV CEILING:		

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 That, IdeaPaint WB Part A

FILE NO.:
MSDS DATE: 1 / 29 /2010

n-Butyl Alcohol		
OSHA PEL-TWA:		
OSHA PEL STEL :	50 (Ceiling)	150 (Ceiling) [Prevent or Reduce Skin Absorption]
ACGIH TLV-TWA:	20	
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
NIOSH TWA		
NIOSH STEL	50 (Ceiling)	150 (Ceiling) [Potential for Dermal Absorption]
Silica, Amorphous		
OSHA PEL – TWA		10
OSHA PEL STEL		
ACGIH TLV-TWA:		10
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
NIOSH TWA		
NIOSH STEL		6
Ethylene Glycol		
OSHA PEL – TWA	50 (Ceiling)	125 (Ceiling)
OSHA PEL STEL		
ACGIH TLV-TWA:		100 (Ceiling)
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
Styrene		
OSHA PEL – TWA	50	215
OSHA PEL STEL	100	425
ACGIH TLV-TWA:	20	
ACGIH TLV STEL:	40	
ACGIH TLV CEILING:		
NIOSH TWA		
NIOSH STEL	10	30
	15	45
Kaolin		
OSHA PEL – TWA		5 (Respirable Dust)
OSHA PEL STEL		
ACGIH TLV-TWA:		2 (Respirable
Dust)		
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
NIOSH TWA		
NIOSH STEL		5 (Respirable Dust)
2-Butoxyethanol		
OSHA PEL – TWA	25	120 (Prevent or Reduce Skin Absorption)
OSHA PEL STEL		
ACGIH TLV-TWA:	20	
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
NIOSH TWA		
NIOSH STEL	5	24 (Potential for Dermal Absorption)

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

PAGE 2 OF 7

MATERIAL SAFETY DATA SHEET**IdeaPaint CRE-8 That, IdeaPaint WB Part A**

FILE NO.:

MSDS DATE: 1 / 29 /2010

'Skin' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur. No biological limits allocated.

SECTION 3: HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW:** Combustible Liquid. Hazardous Substance**ROUTES OF ENTRY:** Lungs, Gastrointestinal Tract, Skin, and Eyes**POTENTIAL HEALTH EFFECTS****EYES:** May be irritating to eyes. Upon eye contact, this product will cause, tearing, stinging, blurred vision, and redness.**SKIN:** May be harmful in contact with the skin. Irritating to the skin. The symptoms may include redness, itching, and swelling. Repeated exposure may cause skin dryness and cracking.**INGESTION:** Ingestion of this product may irritate the gastric tract causing nausea and vomiting.**INHALATION:** Harmful via inhalation. Inhalation of product vapors may cause irritation of the nose, throat, and respiratory system. Vapors may cause drowsiness and dizziness.**ACUTE HEALTH HAZARDS:** Very hazardous in case of ingestion. Hazardous in case of skin contact (irritation), of eye contact (irritant), of inhalation. Slightly hazardous in case of skin contact (permeator).**CHRONIC HEALTH HAZARDS:** See Carcinogenicity data below.**MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:****CARCINOGENICITY****Titanium Dioxide**

OSHA: Not Listed

ACGIH: A-4 Not Classifiable as a Human Carcinogen NTP: Not Listed

IARC: Group 2B (Possibly Carcinogenic to Humans)

NIOSH: Potential Occupational Carcinogen

Silica, Amorphous

OSHA: Not Listed

ACGIH: Not Listed NTP: Not Listed

IARC: Group 3 (Not Classifiable)

NIOSH: Not Listed

Ethylene Glycol

OSHA: Not Listed

ACGIH: A-4 Not Classifiable as a Human Carcinogen NTP: Not Listed

IARC: Not Listed

NIOSH: Not Listed

Styrene

OSHA: Proven Human Carcinogen

ACGIH: A-4 Not Classifiable as a Human Carcinogen

NTP: Not Listed

IARC: Group 2B (Possibly Carcinogenic to Humans)

NIOSH: Not Listed

Kaolin

OSHA: Not Listed

ACGIH: A-4 Not Classifiable as a Human Carcinogen NTP: Not Listed

IARC: Not Listed

NIOSH: Not Listed

2-Butoxyethanol

OSHA: Not Listed

ACGIH: A-3 Confirmed Animal Carcinogen NTP: Not Listed

IARC: Group 3 (Not Classifiable)

NIOSH: Potential Occupational Carcinogen

SECTION 4: FIRST AID MEASURES**EYES:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.**SKIN:** Wash affected area thoroughly with soap and water. If symptoms develop, seek medical attention.**INGESTION:** Do not induce vomiting. Wash out mouth thoroughly with water. If symptoms develop, seek medical attention.

PAGE 3 OF 7

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 That, IdeaPaint WB Part AFILE NO.:
MSDS DATE: 1 / 29 /2010**INHALATION:** If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist, seek medical attention.**NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:** Treat symptomatically.**SECTION 5: FIRE-FIGHTING MEASURES****FLAMMABLE LIMITS IN AIR, UPPER:** Not Flammable at Test Temperature of 22°C
(% BY VOLUME) **LOWER:** Not Flammable at Test Temperature of 22°C**FLASH POINT:**

F: 142°

C:

METHOD USED: Closed Cup**AUTOIGNITION TEMPERATURE:** ND

F:

C:

NFPA HAZARD CLASSIFICATIONHEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0
OTHER:**HMS HAZARD CLASSIFICATION**HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0
PROTECTION: H**EXTINGUISHING MEDIA:** Use Carbon Dioxide, Dry Chemical, Foam, Water Fog or Water Spray**SPECIAL FIRE FIGHTING PROCEDURES:** Fire fighters should wear NIOSH approved Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapors or fumes. Water spray may be used to cool down heat-exposed containers.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Combustible liquid and vapor. When heated above the flash point, emit combustible vapors which, when mixed with air, can burn or be explosive. Runoff to sewer may create fire or explosion hazard.**HAZARDOUS DECOMPOSITION PRODUCTS:** Not Determined.**SECTION 6: ACCIDENTAL RELEASE MEASURES****ACCIDENTAL RELEASE MEASURES:** Wear appropriate personal protective clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible, contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean, non-sparking tools to collect the material and place into suitable labeled containers for subsequent recycling or disposal. Dispose of waste according to applicable local and national regulations. If contamination of sewers or waterways occurs, inform the local water authorities and EPA in accordance with local regulations.**SECTION 7: HANDLING AND STORAGE****HANDLING AND STORAGE:** Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved combustible liquid storage containers in the work area. Prevent release of vapors and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static

discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

OTHER PRECAUTIONS: Store in a cool, dry, well-ventilated area away from sources of ignition, oxidizing agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures.**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS:**

PAGE 4 OF 7

MATERIAL SAFETY DATA SHEET**IdeaPaint CRE-8 That, IdeaPaint WB Part A**

FILE NO.:

MSDS DATE: 1 / 29 /2010

VENTILATION : Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapors or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required.

RESPIRATORY PROTECTION: NIOSH Approved positive pressure air supplied full face respirator is preferred for long term use, for industrial applications. Cartridge filter mask for organic vapors is acceptable for short periods depending on risk assessment. The final choice of appropriate personal protection will vary according to individual circumstances. This can include methods of handling and engineering controls as determined by appropriate applicator risk assessment.

EYE PROTECTION: Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances

SKIN PROTECTION: Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Suitable protective work wear (e.g. cotton overalls buttoned at the neck and wrist) is recommended. Chemical resistant apron is recommended where large quantities are handled

WORK HYGIENIC PRACTICES:

EXPOSURE GUIDELINES: See Section 2 Above

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Off-White Liquid

ODOR: Slight Sweet

PHYSICAL STATE: Liquid

pH AS SUPPLIED: 7.6-7.8

pH (Other):

BOILING POINT: N/A

F:

C:

MELTING POINT: N/A

F:

C:

FREEZING POINT: N/A

F:

C:

VAPOR PRESSURE (mmHg): N/A

@

F:

C:

VAPOR DENSITY (AIR = 1): Heavier Than Air

@

F:

C:

SPECIFIC GRAVITY (H₂O = 1): 1.27 or 10.54 lb/gal

@

F:

C:

EVAPORATION RATE: Slower Than Ether

BASIS (=1):

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (con't)

SOLUBILITY IN WATER: Soluble

PERCENT SOLIDS BY WEIGHT:

PERCENT VOLATILE:

BY WT/ BY VOL @

F:

C:

VOLATILE ORGANIC COMPOUNDS (VOC):

WITH WATER: LBS/GAL
WITHOUT WATER: LBS/GAL

PAGE 5 OF 7

MATERIAL SAFETY DATA SHEET

IdeaPaint CRE-8 That, IdeaPaint WB Part A

MOLECULAR WEIGHT:

VISCOSITY:

@

F:

C:

FILE NO.:

MSDS DATE: 1 / 29 /2010

SECTION 10: STABILITY AND REACTIVITY**STABLE****UNSTABLE****STABILITY:** Under Normal Conditions**CONDITIONS TO AVOID (STABILITY):** Not Determined**INCOMPATIBILITY (MATERIAL TO AVOID):** Not Determined**HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:** Not Determined**HAZARDOUS POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID (POLYMERIZATION):****SECTION 11: TOXICOLOGICAL INFORMATION****TOXICOLOGICAL INFORMATION:** No toxicity data are available for this specific product. See Sections 2 and 3 Above.**SECTION 12: ECOLOGICAL INFORMATION****ECOLOGICAL INFORMATION:** May be harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**OTHER:** Prevent this material from, entering waterways, drains and sewers.**SECTION 13: DISPOSAL CONSIDERATIONS****WASTE DISPOSAL METHOD:** Dispose of waste according to local and national regulations.**RCRA HAZARD CLASS:** Not determined**SECTION 14: TRANSPORT INFORMATION****TRANSPORTATION INFORMATION:****U.S. DEPARTMENT OF TRANSPORTATION****PROPER SHIPPING NAME:** Combustible Liquid**HAZARD CLASS:** IIIA**ID NUMBER:****PACKING GROUP:****LABEL STATEMENT:****WATER TRANSPORTATION****PROPER SHIPPING NAME:****HAZARD CLASS:****ID NUMBER:****PACKING GROUP:****LABEL STATEMENTS:****AIR TRANSPORTATION****PROPER SHIPPING NAME:** Combustible Liquids, n.o.s.**HAZARD CLASS:** 3**ID NUMBER:****PACKING GROUP:** III**LABEL STATEMENTS:**

PAGE 6 OF 7

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 That, IdeaPaint WB Part AFILE NO.:
MSDS DATE: 1 / 29 /2010

OTHER AGENCIES:

SECTION 15: REGULATORY INFORMATION**U.S. FEDERAL REGULATIONS**

TSCA (TOXIC SUBSTANCE CONTROL ACT): 8 (b) Inventory

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Hazardous Substance

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

311/312 HAZARD CATEGORIES:

313 REPORTABLE INGREDIENTS:

STATE REGULATIONS:

Pennsylvania Right-to- Know

Massachusetts Right-to-Know

INTERNATIONAL REGULATIONS:WHMIS (Canada): Class B-3: Combustible Liquid with a Flash Point Above 37.8° C (100° F) but Below 93.3° C (200° F)
Class D-2 Material Causing Other Toxic Effects (Toxic)

DSCL (EEC): R8 Combustible: R-20 Harmful by Inhalation: R36/38 Irritating to Eyes and Skin

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: MSDS Created: January 2010

PREPARATION INFORMATION:**DISCLAIMER:** The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State and or Local laws and regulations.

PAGE 7 OF 7

MATERIAL SAFETY DATA SHEET

IdeaPaint CRE-8 This, IdeaPaint WB Part B

FILE NO.:
MSDS DATE: 1 / 29 /2010

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: IdeaPaint CRE -8 This, IdeaPaint WB Part B
SYNONYMS:
PRODUCT CODES:

MANUFACTURER: IdeaPaint, Inc.
DIVISION:
ADDRESS: 25 First Street
Suite 100
Cambridge, MA 02141

EMERGENCY PHONE: 617-714-1050
CHEMTREC PHONE: 800-424-9300
OTHER CALLS:
FAX PHONE: 617-714-1070

CHEMICAL NAME:
CHEMICAL FAMILY: Paint
CHEMICAL FORMULA:

PRODUCT USE:
PREPARED BY:

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CAS NO.	Component	% WT
28182-81-2 <50	Hexamethylene Diisocyanate Homopolymer	
4435-53-4	Butoxyl	30
53880-05-0 <20	Cyclohexane, 5-Isocyanato-1-(Isocyanatomethyl)-1, 3, 3, Trimethyl-, Homopolymer	
9046-01-9	Tridecyl Alcohol, Ethoxylated, Phosphated	<7
98-94-2	N,N-Dimethylcyclohexamine	<2
4098-71-9	Isophoronediiisocyanate	<0.5
822-06-0	Hexamethylene Diisocyanate	<0.05

Component Exposure Limits

	ppm	mg/m3
Isophorone Diisocyanate		
OSHA PEL-TWA:	0.005 (Prevent or Reduce Skin Absorption)	
OSHA PEL STEL :	0.002	
OSHA PEL CEILING:		
ACGIH TLV-TWA:	0.005	
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
NIOSH TWA	0.005	0.045
NIOSH STEL	0.020	0.180 [Potential for Dermal Absorption]
Hexamethylene Diisocyanate		
OSHA PEL-TWA:		
OSHA PEL STEL :		
OSHA PEL CEILING:		
ACGIH TLV-TWA:	0.005	
ACGIH TLV STEL:		
ACGIH TLV CEILING:		
NIOSH TWA	0.005	0.035
NIOSH STEL	0.020	0.180 [Potential for Dermal Absorption]

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

PAGE 1 OF 6

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 This, IdeaPaint WB Part BFILE NO.:
MSDS DATE: 1 / 29 /2010

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Skin' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur. No biological limits allocated.

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Combustible Liquid. Hazardous Substance

ROUTES OF ENTRY: Lungs, Gastrointestinal Tract, Skin, and Eyes

POTENTIAL HEALTH EFFECTS

EYES: May be irritating to eyes. Upon eye contact, this product will cause, tearing, stinging, blurred vision, and redness.

SKIN: Irritating to the skin. May cause skin sensitization. The symptoms may include redness, itching, and swelling. Repeated exposure may cause skin dryness and cracking.

INGESTION: Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

INHALATION: Harmful via inhalation. May cause respiratory sensitization. Inhalation of product vapors may cause irritation of the nose, throat, and respiratory system. Vapors may cause drowsiness and dizziness.

ACUTE HEALTH HAZARDS: Very hazardous in case of ingestion. Hazardous in case of skin contact (irritation), of eye contact (irritant), of inhalation. Slightly hazardous in case of skin contact (permeator).

CHRONIC HEALTH HAZARDS:

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

CARCINOGENICITY: No evidence of Carcinogenicity.

SECTION 4: FIRST AID MEASURES

EYES: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

SKIN: Wash affected area thoroughly with soap and water. If symptoms develop, seek medical attention.

INGESTION: Do not induce vomiting. Wash out mouth thoroughly with water. If symptoms develop, seek medical attention.

INHALATION: If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms persist, seek medical attention.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

COMBUSTIBLE LIMITS IN AIR, UPPER: Not Flammable at Test Temperature of 22°C
(% BY VOLUME) **LOWER:** Not Flammable at Test Temperature of 22°C

FLASH POINT:

F: 168°

C:

METHOD USED: Closed Cup

AUTOIGNITION TEMPERATURE: ND

F:

C:

PAGE 2 OF 6

MATERIAL SAFETY DATA SHEET**IdeaPaint CRE-8 This, IdeaPaint WB Part B**FILE NO.:
MSDS DATE: 1 / 29 /2010

NFPA HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 0
OTHER:

HMIS HAZARD CLASSIFICATION

HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0
PROTECTION: H**EXTINGUISHING MEDIA:** Use Carbon Dioxide, Dry Chemical, Foam, Water Fog or Water Spray**SPECIAL FIRE FIGHTING PROCEDURES:** Fire fighters should wear NIOSH approved Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to vapors or fumes. Water spray may be used to cool down heat-exposed containers.**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Combustible liquid and vapor. When heated above the flash point, emit combustible vapors which, when mixed with air, can burn or be explosive. Runoff to sewer may create fire or explosion hazard.**HAZARDOUS DECOMPOSITION PRODUCTS:** Not Determined.**SECTION 6: ACCIDENTAL RELEASE MEASURES****ACCIDENTAL RELEASE MEASURES:** Wear appropriate personal protective clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible, contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean, non-sparking tools to collect the material and place into suitable labeled containers for subsequent recycling or disposal. Dispose of waste according to applicable local and national regulations. If contamination of sewers or waterways occurs, inform the local water authorities and EPA in accordance with local regulations.**SECTION 7: HANDLING AND STORAGE****HANDLING AND STORAGE:** Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with adequate ventilation. Use approved combustible liquid storage containers in the work area. Prevent release of vapors and mists into workplace air. Keep containers closed when not in use. Take precautionary measures against static discharges. Keep material away from sparks, flames and other ignition sources. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.**OTHER PRECAUTIONS:** Store in a cool, dry, well-ventilated area away from sources of ignition, oxidizing agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures.**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****ENGINEERING CONTROLS:****VENTILATION :** Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapors or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required.**RESPIRATORY PROTECTION:** NIOSH Approved positive pressure air supplied full face respirator is preferred for long term use, for industrial applications. Cartridge filter mask for organic vapors is acceptable for short periods depending on risk assessment. The final choice of appropriate personal protection will vary according to individual circumstances. This can include methods of handling and engineering controls as determined by appropriate applicator risk assessment.**EYE PROTECTION:** Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances**SKIN PROTECTION:** Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken.**OTHER PROTECTIVE CLOTHING OR EQUIPMENT:** Suitable protective work wear (e.g. cotton overalls buttoned at the neck and wrist) is recommended. Chemical resistant apron is recommended where large quantities are handled**WORK HYGIENIC PRACTICES:****EXPOSURE GUIDELINES:** See Section 2 Above**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE:** Clear, Pale Yellow Liquid

PAGE 3 OF 6

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 This, IdeaPaint WB Part B
 ODOR: Slight Sweet

FILE NO.:
 MSDS DATE: 1 / 29 /2010

PHYSICAL STATE: Liquid

pH AS SUPPLIED: N/A
 pH (Other):

BOILING POINT: N/A

F:
 C:

MELTING POINT: N/A

F:
 C:

FREEZING POINT: N/A

F:
 C:

VAPOR PRESSURE (mmHg): N/A

@

F:
 C:

VAPOR DENSITY (AIR = 1): Heavier Than Air

@

F:
 C:

SPECIFIC GRAVITY (H2O = 1): 1.09 or 9.06 lb/gal

@

F:
 C:

EVAPORATION RATE: Slower Than Ether

BASIS (=1):

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (con't)

SOLUBILITY IN WATER: Soluble

PERCENT SOLIDS BY WEIGHT:

PERCENT VOLATILE:

BY WT/ BY VOL @

F:
 C:

VOLATILE ORGANIC COMPOUNDS (VOC):

WITH WATER:	LBS/GAL
WITHOUT WATER:	LBS/GAL

MOLECULAR WEIGHT:

VISCOSITY:

@

F:
 C:

SECTION 10: STABILITY AND REACTIVITY

STABLE

UNSTABLE

STABILITY: Under Normal Conditions

CONDITIONS TO AVOID (STABILITY): Not Determined

INCOMPATIBILITY (MATERIAL TO AVOID): Not Determined

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Thermal decomposition may result in the release of toxic and/or irritating fumes including oxides of nitrogen, isocyanate vapors, traces of hydrogen cyanide, carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID (POLYMERIZATION):

PAGE 4 OF 6

MATERIAL SAFETY DATA SHEET
IdeaPaint CRE-8 This, IdeaPaint WB Part BFILE NO.:
MSDS DATE: 1 / 29 /2010**SECTION 11: TOXICOLOGICAL INFORMATION**

TOXICOLOGICAL INFORMATION: No toxicity data are available for this specific product. See Sections 2 and 3 Above.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not available. Not expected to be readily biodegradable.

OTHER: Prevent this material from, entering waterways, drains and sewers.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of waste according to local and national regulations.

RCRA HAZARD CLASS: Not determined

SECTION 14: TRANSPORT INFORMATION**TRANSPORTATION INFORMATION:****U.S. DEPARTMENT OF TRANSPORTATION**PROPER SHIPPING NAME: Combustible Liquid
HAZARD CLASS: IIIA
ID NUMBER:
PACKING GROUP:
LABEL STATEMENT:**WATER TRANSPORTATION**PROPER SHIPPING NAME:
HAZARD CLASS:
ID NUMBER:
PACKING GROUP:
LABEL STATEMENTS:**AIR TRANSPORTATION**PROPER SHIPPING NAME: Combustible Liquids, n.o.s.
HAZARD CLASS: 3
ID NUMBER:
PACKING GROUP: III
LABEL STATEMENTS:**OTHER AGENCIES:****SECTION 15: REGULATORY INFORMATION****U.S. FEDERAL REGULATIONS**

TSCA (TOXIC SUBSTANCE CONTROL ACT): 8 (b) Inventory

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Hazardous Substance

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

311/312 HAZARD CATEGORIES:

313 REPORTABLE INGREDIENTS:

STATE REGULATIONS:Pennsylvania Right-to-Know
Massachusetts Right-to-Know**INTERNATIONAL REGULATIONS:**

PAGE 5 OF 6

MATERIAL SAFETY DATA SHEET

IdeaPaint CRE-8 This, IdeaPaint WB Part B

FILE NO.:

MSDS DATE: 1 / 29 /2010

WHMIS (Canada): Class B-3: Combustible Liquid with a Flash Point Above 37.8° C (100° F) but Below 93.3° C (200° F)
Class D-2 Material Causing Other Toxic Effects (Toxic)

DSCL (EEC): R8 Combustible; R-20 Harmful by Inhalation; R36/38 Irritating to Eyes and Skin

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: MSDS Created: January 2010

PREPARATION INFORMATION:

DISCLAIMER: The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State and or Local laws and regulations.