

02/09/2006 12:00 2165819041


GRAFIX

55521-1003  
- 1005

PAGE 02

# MSDS - Drafting Film - Matte 1 or 2 side

2003



Page 1 of 2

**Emergency Contact:**

Grafix, Inc.  
19499 Miles Rd.  
Cleveland, Oh. 44128  
(216) 581-9050

**Product Identification:**

Drafting Film is a polyester film. Various fillers or additives used to modify the physical appearance and/or surface properties may be present. Actual formula is proprietary.

**Hazardous Ingredients:**

This material is not a "health hazard" as defined under the OSHA Hazard Communication Standard, 29 CFR 1910.1200 or S.A.R.A. Title III, Section 313. This material is considered an article under OSHA and TSCA standards.

**Physical-Chemical Data:**

Slightly opaque, odorless film is chemically stable and resistant to water. It has a specific gravity of >1.0 gm/cc. Melting point is approximately 160 degrees C.

**Physical Hazards:**

Heavy gauges of Drafting Film can contain sharp edges. Proper protective gear such as gloves is recommended. The top coating of the film can create a slip hazard when dropped on the floor. Walking areas should be kept clear of this film.

Unwinding, winding and passage of this film through and over rollers will tend to generate a strong electrostatic charge on the web. Static discharge devices should be properly positioned at such points to eliminate the charge and prevent uncontrolled discharge from the web. This is particularly required in potentially explosive atmospheres and to protect personnel from the effects of static discharge.

General exhaust is acceptable except where overheating can occur during processing. High temperature are not recommended.


## GRAFIX<sup>®</sup> Plastics

A Division of GRAFIX, Inc.

19499 Miles Rd. Cleveland, OH. 44128

(800) 447-2349 (216) 581-9050 FAX (216) 581-9041

E-MAIL [info@grafixplastics.com](mailto:info@grafixplastics.com) WEB <http://www.grafixplastics.com>




02/09/2006 12:00 2165819041

GRAFIX

PAGE 03

# MSDS - Drafting Film - Matte 1 or 2 side

2003



Page 2 of 2

## Health Hazard Data:

No adverse health effect have been attributed to this Drafting film film at ambient temperature.

### Hazard Designations

		Key
Health:	0	0-None
Flamability	0	1-Slight
Reactivity	0	2-Moderate
		3-Severe
		4-Extreme

## Control Measure and Safe Handling Procedures

The film will burn if exposed to flame. Fire fighters should protect themselves from decomposition and combustion products that may include carbon dioxide, carbon monoxide, HCL and other such toxic gases. Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to products of combustion exist. Fire fighting extinguishing media include carbon dioxide, alcohol foam or dry chemical. Water spray may be useful in controlling fire by keeping adjacent rolls cool.

## Disposal and Shipping Information:

PVC film is not classified as hazardous waste under the Resource Conservation and Recovery Act, and unless prohibited by state or local regulation, can be disposed of in a municipal landfill or incinerated. This product is not classified by the U.S. Department of Transportation as a hazardous material.

### Information Contact:

Grafix, Inc.  
19499 Miles Rd.  
Cleveland, OH. 44128

To the best of our knowledge the information contained herein is accurate. However, Grafix assumes no liability whatsoever, for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All material may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the on hazards which exist.

## GRAFIX<sup>®</sup> Plastics

A Division of GRAFIX, Inc.

19499 Miles Rd. Cleveland, OH. 44128

(800) 447-2349 (216) 581-9050 FAX (216) 581-9041

E-MAIL [info@grafixplastics.com](mailto:info@grafixplastics.com) WEB <http://www.grafixplastics.com>

