

67101-XXXX

MATERIAL SAFETY DATA SHEET

HANDY ART WASHABLE PAINT

TRAVEL NAME ON LABEL

ROCK PAINT DISTRIBUTING CORP.

MANUFACTURER

MSDS NUMBER

365 SUNNYSIDE DR. P.O. BOX 482

ADDRESS

CAS NUMBER

MILTON, WI 53563

FEBRUARY 2001

DATE PREPARED

(608)868-6873 (920) 563-8545

PHONE NUMBER(FOR INFORMATION)

PREPARED BY

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

OTHER LIMITS

| COMPONENTS: CHEMICAL NAME & COMMON NAMES | % | OSHA PEL | ACGIH TLV | RECOMMENDED |
|--|---|----------|-----------|-------------|
| WATER | | | | |
| WATER SOLUBLE COLORANTS | | | | |
| KAOLIN CLAY | | | | |
| GUMS and/or CELLULOSIC | | | | |
| CALCIUM CARBONATE | | | | |
| MODIFIED STARCH | | | | |
| | | | | |
| | | | | |
| | | | | |

AS PER ASTM D-4236 AND AS PER THE ART AND CRAFT MATERIALS INSTITUTE (ACMI) INC. THIS PAINT HAS BEEN CERTIFIED NON-TOXIC.

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

| | |
|--|--|
| BOILING POINT - ABOUT 212 | SPECIFIC GRAVITY (H ₂ O=1) - ABOUT 9LBS PER GAL |
| VAPOR PRESSURE (mm Hg & TEMPERATURE) - 17mm Hg | MELTING POINT - N/A |
| VAPOR DENSITY (AIR=1) - NOT AVAILABLE | EVAPORATION RATE (WATER=1) - SLOWER |
| SOLUBILITY IN WATER - DILUTABLE | WATER REACTIVE - N/A |
| APPEARANCE & ODOR - | |

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

| | | |
|--|----------------------------------|---|
| FLASH POINT & METHOD USED N/A | AUTO IGNITION TEMPERATURE N/A | FLAMMABILITY LIMITS IN AIR % BY VOLUME N/A |
| EXTINGUISHER MEDIA FOAM - DRY CHEMICAL - CO ₂ - WATER SPRAY OR FOG | LEL | UEL |
| SPECIAL FIRE FIGHTING PROCEDURES N/A | | |
| UNUSUAL FIRE AND EXPLOSION HAZARDS N/A | | |

| SECTION 4 - REACTIVITY HAZARD DATA | | WASH - 2 | |
|---|---------------------------------------|--|--|
| STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE | CONDITIONS TO AVOID NONE KNOWN | | |
| INCOMPATIBILITY (MATERIALS TO AVOID) NONE KNOWN-HOWEVER PRODUCT PROPERTIES MAY BE ALTERED BY MIXING WITH SOME MATERIALS. | | | |
| HAZARDOUS DECOMPOSITION PRODUCTS THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE AND TRACES OF MONOMER. | | | |
| HAZARDOUS POLYMERIZATION <input type="checkbox"/> MAY OCCUR <input checked="" type="checkbox"/> WILL NOT OCCUR | CONDITIONS TO AVOID | | |
| SECTION 5 - HEALTH HAZARD DATA | | | |
| PRIMARY ROUTES OF ENTRY <input type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input type="checkbox"/> SKIN ABSORTION <input checked="" type="checkbox"/> NOT HAZARDOUS | | CARCINOGEN LISTED IN <input type="checkbox"/> NTP <input type="checkbox"/> OSHA <input type="checkbox"/> IARC MONOGRAPH <input checked="" type="checkbox"/> NOT LISTED | |
| HEALTH HAZARDS ACUTE CHRONIC | | | |
| SIGNS AND SYMPTOMS | | | |
| MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE | | | |
| EMERGENCY FIRST AID PROCEDURES - SEEK MEDICAL ASSISTANCE FOR FURHTER TREATMENT, OBSERVATION AND SUPPORT IS NECESSARY. | | | |
| EYE CONTACT - DIRECT CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN. REMOVE CONTACTS FROM VICTIM. | | | |
| SKIN CONTACT - PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED REMOVE AND WASH CLOTHING BEFORE REUSE. | | | |
| INHALATION - N/A | | | |
| INGESTION - IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN. | | | |
| SECTION 6 - CONTROL AND PROTECTIVE MEASURES | | | |
| RESPIRATORY PROTECTION (SPECIFY TYPE) - | | | |
| PROTECTIVE GLOVES - RUBBER GLOVES RECOMMENDED | | EYE PROTECTION - CHEMICAL GOGGLES WITH EYE GUARD | |
| VENTILATION TO BE USED - LOCAL EXHAUSE - OTHER (SPECIFY) - | | MECHANICAL (GENERAL) - SPECIAL - | |
| OTHER PROTECTIVE CLOTHING AND EQUIPMENT - N/A | | | |
| HYGIENIC WORK PRACTICES - | | | |
| SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES | | | |
| STEPS TO BE TAKEN IS MATERIAL IS SPILLED OR RELEASED - ABSORB WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS. | | | |
| WASTE DISPOSAL METHODS - DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS. | | | |
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING AND FROM EXCESSIVE HEAT. | | | |
| OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS - N/A | | | |
| HIMS RATING HEALTH _____ FLAMMABILITY _____ REACTIVITY _____ PERSONAL PROTECTION _____ | | | |