

01725-1001
-3005

CHROMA AUSTRALIA PTY LTD ACN 001 594 609 17 MUNDOWI RD MT KURING-GAI NSW 2080, Australia TEL: (02) 9457 9922 FAX: (02) 9457 8082 EMERGENCY TEL: AS ABOVE, or POISONS INFORMATION CENTRE		PAGE 1 of 2 DATE of ISSUE: 1 SEPTEMBER 2006
Material Safety Data Sheet Not Classified as Hazardous According to the Criteria of Worksafe Australia		
IDENTIFICATION		
Product name: ARCHIVAL ODOURLESS CLASSIC MEDIUM Other names: ---		U.N. No: N/A Hazchem: N/A Dangerous Goods Class & Sub Risk: N/A Poisons Schedule: 5
Manufacturer's Product Code: VARIOUS Use: ARTISTS' PAINTING MEDIUM TO EXTEND DRYING TIME OF PAINT		
Physical Description/Properties		
Appearance: TRANSLUCENT BROWN LIQUID Boiling Point/Melting Point (°C) N/A Vapour Pressure (pascals or mm of Hg at 25°C) N/A Specific Gravity APPROX 0.9 g/ml Other properties SLIGHT ODOUR Ingredients		Flash Point (°C): > 80° C Flammability limits (%): N/A Solubility in Water (g/L): INSOLUBLE
Chemical entity	CAS No.	Proportion
SAFFLOWER OIL	NON HAZARDOUS	18.5 % of volume
ISOPARAFFINIC HYDROCARBON	90622-58-5	52.8% of VOLUME
ALKYD RESIN	NON HAZARDOUS	25% APPROX
PRESERVATIVE	62530-20-1	1%
ALKYD DRIERS	COMMERCIAL IN CONFIDENCE	2.6%
HEALTH HAZARD INFORMATION		
HEALTH EFFECTS:		
ACUTE:		
Swallowed	MINIMAL TOXICITY. MAY CAUSE IRRITATION TO RESPIRATORY TRACT.	
Eye	SLIGHT IRRITATION MAY OCCUR BUT WILL NOT DAMAGE EYE TISSUE.	
Skin	PROLONGED CONTACT MAY IRRITATE OR CAUSE DERMATITIS.	
Inhaled	VAPOURS MINIMAL, UNLESS PRODUCT HEATED, IN WHICH MAY CAUSE IRRITATION TO EYES, RESPIRATORY TRACT & MAY CAUSE HEADACHES.	
Chronic	N/A	
FIRST AID:		
Swallowed	DO NOT INDUCE VOMITING. GIVE WATER TO DRINK & SEEK MEDICAL ATTENTION.	
Eye	WIPE AWAY EXCESS, THEN FLUSH EYES WITH A LARGE AMOUNT OF WATER SEEK MEDICAL TREATMENT IF IRRITATION PERSISTS.	
Skin	WIPE OFF EXCESS, WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER	
Inhaled	MOVE SUBJECT TO FRESH AIR AND SEEK MEDICAL ADVICE.	
ADVICE TO DOCTOR:	CONTACT POISONS INFORMATION CENTRE	

ARCHIVAL CLASSIC MEDIUM

Page 2 of 2

PRECAUTIONS FOR USE**EXPOSURE STANDARDS**

TLV: 300ppm EVAPORATION RATE >1

ENGINEERING CONTROLS

ENSURE ADEQUATE VENTILATION

PERSONAL PROTECTION

USE IN WELL VENTILATED ROOM/AREA

FLAMMABILITY

N/A NON FLAMMABLE

SAFE HANDLING INFORMATION**STORAGE & TRANSPORT**STORE AT AMBIENT TEMPERATURES
TRANSPORT: NON HAZARDOUS**SPILLS & DISPOSAL**CLEAN UP & PLACE IN SUITABLE CONTAINER. DISPOSE OF ACCORDING TO
LOCAL REGULATIONS & REQUIREMENTS**FIRE/EXPLOSION HAZARD**

NON HAZARDOUS

OTHER INFORMATION**CONTACT POINT:**

MT KURING-GAI N.S.W.

DATE OF ISSUE: 1 SEPTEMBER 2006